



GreenSpace Evo Mini Wallmount

WL322W 12S/PW930 DIA HWB FG BK482

GreenSpace Evo Mini Wallmount, 3D printed, 19.2 W, 2.600 lm, 3000 K, CRI>90, DALI, Interact Ready

GreenSpace Evo Mini Wallmount is a sustainable wall mounted fixture that comes with a sleek and subtle design. This makes the wallmount an ideal choice for hospitality and fashion retail applications. The 3D printed housing is crafted from at least 65% recycled or bio-circular materials, while the heatsink is made from 85% recycled aluminium. Because of its circular design, the luminaire is upgradable, reusable, fully serviceable and recyclable. Combined with the high energy efficiency, this makes the GreenSpace Evo Mini wallmount a sustainable choice. The new PerfectAccent deep reflectors ensure a light effect with increased sparkle and improved shopper eye comfort. Further customization of colors and textures is possible via Philips MyCreation

Warnings and Safety

- Cleaning of the optic should only be done with pressurized air. Touching the LED or reflector is forbidden. For food preparation areas and areas with high levels of dust, the use of the optional front glass is strongly advised, as it can be cleaned with a (dry) microfiber cloth

Product data

General Information		Light Technical	
Number of gear units	1 unit	Luminous Flux	2.600 lm
Driver included	Yes	Correlated Color Temperature (Nom)	3000 K
Value ladder	Specification	Luminous Efficacy (rated) (Nom)	136 lm/W
Warranty period	5 years	Color rendering index (CRI)	>90

GreenSpace Evo Mini Wallmount

Light source color	PremiumWhite with CRI ≥90 and color temperature 3000K
Optic type	High-reflective metal reflector Medium beam 20 to 40 degrees
Luminaire light beam spread	36°
Unified glare rating CEN	Not applicable

Operating and Electrical

Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Inrush current	6.7 A
Inrush time	0.027 ms
Power Consumption	19.2 W
Power Factor (Fraction)	0.90
Connection	2 Push-in connector 2-pole
Cable	-
Number of products on MCB of 16 A type B	34
Suitable for random switching	Not applicable
Protection class IEC	Safety class II

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Dali dimming Interact System ready
Control interface	DALI
Constant light output	No
DALI Standard	DALI-2™ with extended data: Parts 251/252/253
Connectivity	Interact Ready

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Aluminum
Optic material	Aluminum
Optical cover material	Tempered glass
Fixation material	-
Housing Color	Black
Optical cover finish	Clear
Overall length	90 mm
Overall height	230 mm
Overall diameter	65 mm

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Net Weight (Piece)	0.400 kg

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	-
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	+10 to +35 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.422, 0.386) SDCM <2
Power consumption tolerance	+/-10%

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 100000 h	10 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 100000 h	L80

Sustainability Data


Sustainability rating	Unclassified
-----------------------	--------------

Product Data

Order product name	WL322W 12S/PW930 DIA HWB FG BK482
Full product name	WL322W 12S/PW930 DIA HWB FG BK482
Full product code	872016983813000
Order code	910505104924
Material Nr. (12NC)	910505104924
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169838130
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169838130

GreenSpace Evo Mini Wallmount


Dimensional drawing



Photometric data

Light Distribution Diagram - WL322W 12S/PW930 DIA HWB FG BK482

Spectral Power Distribution Colour - WL322W 12S/PW930 DIA HWB FG BK482



Polar Normal (separate) - WL320WI - 910505104924

GreenSpace Evo Mini Wallmount

