



GreenSpace Evo Mini Pendant

PT332C 17S/PW930 DIA HVWB BK BK BK

GreenSpace Evo Mini Pendant, 3D printed, 11.9 W, 1700 lm, 3000 K, CRI>90, DALI, Interact Ready

GreenSpace Evo Mini Pendant is a sustainable lighting pendant that comes with a sleek and subtle design. This makes the pendant an ideal choice for hospitality and fashion retail applications. The 3D printed housing is crafted from at least 65% recycled or bio-circular materials, while the heatsink is made from 85% recycled aluminium. Because of its circular design, the luminaire is upgradable, reusable, fully serviceable and recyclable. Combined with the high energy efficiency, this makes the GreenSpace Evo Mini pendant a sustainable choice. The new PerfectAccent deep reflectors ensure a light effect with increased sparkle and improved shopper eye comfort. Further customisation of colours and textures is possible via Philips MyCreation

Warnings and Safety

- Cleaning of the optic should only be done with pressurized air. Touching the LED or reflector is forbidden. For food preparation areas and areas with high levels of dust, the use of the optional front glass is strongly advised, as it can be cleaned with a (dry) microfiber cloth
- During maintenance, the product must be switched off and cooled down

Product data

General Information		Serviceability class
Number of gear units	Unit	Class A, the luminaire is equipped with serviceable parts (when applicable): LED board, driver, control units, surge-protection device, optics, front cover and mechanical parts
Driver included	Yes	
Value ladder	Specification	

GreenSpace Evo Mini Pendant

Warranty period	5 years
Sustainability rating	Signify Circle

Light Technical

Luminous Flux	1,700 lm
Correlated Colour Temperature (Nom)	3000 K
Luminous efficacy (rated) (nom.)	143 lm/W
Colour rendering index (CRI)	>90
Light source colour	PremiumWhite with CRI ≥90 and colour temperature 3,000K
Optic type	High-reflective metal reflector very wide beam >80 degrees
Luminaire light beam spread	80°
Unified Glare Rating (CEN)	Not applicable

Operating and Electrical

Input Voltage	220-240 V
Line Frequency	50 to 60 Hz
Inrush current	6.7 A
Inrush time	0.027 ms
Power Consumption	11.9 W
Power Factor (Fraction)	0.9
Connection	-
Cable	-
Number of products on MCB (16 A type B)	34
Suitable for random switching	Not applicable
Protection class IEC	Safety class II
Feed-through wiring	-
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	Yes
Driver/power unit/transformer	Dali dimming Interact System ready
Control interface	DALI
Constant light output	No
DALI standard	DALI-2™
Connectivity	Interact Ready
Embedded control	-
Photocell	-

Mechanical and Housing

Housing material	Polycarbonate
Reflector material	Aluminium
Optic material	Aluminium
Optical cover/lens material	-
Fixation material	-
Housing Colour	Black
Optical cover/lens finish	-
Overall length	165 mm
Overall height	65 mm

Overall diameter	65 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Explosion hazard class	-
Mounting	Pendant
Net Weight (Piece)	0.400 kg

Emergency Operation

Additional max. power consumption when emergency battery is charging	0 W
Central Emergency	No

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	-
CE mark	Yes
ENEC mark	-
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM)	1
Stroboscopic effect	0.4
Ambient temperature range	+10 to +35 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	(0.422, 0.386)
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤2

Over Time Performance (IEC Compliant)


Control gear failure rate at median useful life 50,000 h	10 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 100000 h	L80

Product Data

Order product name	PT332C 17S/PW930 DIA HVWB BK BK BK
Full product name	PT332C 17S/PW930 DIA HVWB BK BK BK
Full EOC	872016983827700
Order code	910505104938
Material no. (12 NC)	910505104938
Numerator – quantity per pack	1
EAN/UPC – Product/Case	8720169838277
Numerator – packs per outer box	1
EAN/UPC - Case	8720169838277
Product family code	PT332C [GreenSpace Evo Mini Pendant canopy]

GreenSpace Evo Mini Pendant

Dimensional drawing



Photometric data



Polar Normal (separate) - PT332TI - 910505104938

