



Maxos, Accessoires

9MX056 EC7

Maxos, Accessoires, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Données du produit

| Fonctionnement et électricité | |
|-------------------------------|---------------------|
| Tension d'entrée | 220 à 240 V |
| Fréquence linéaire | 50 to 60 Hz |
| Classe de protection CEI | Classe électrique I |

| Mécanique et boîtier | |
|-------------------------|----------|
| Indice de protection | - |
| Couleur des accessoires | - |
| Poids net (pièce) | 0.006 kg |

| Approbation et application | |
|----------------------------|-----|
| Marquage CE | Oui |
| Conforme à RoHS | Oui |

| Données du produit | |
|-------------------------------|--------------------|
| Nom du produit de la commande | 9MX056 EC7 |
| Nom de produit complet | 9MX056 EC7 |
| Code EOC | 403073213179200 |
| Code de commande | 4030732131792 |
| Code 12NC | 910605019226 |
| Numérateur - Quantité par kit | 1 |
| Code EAN - Produit/Boîte | 4030732131792 |
| Conditionnement par carton | 1 |
| Codes EAN/UPC - Boîte | 4030732131792 |
| Code famille de produits | 9MX056 [ACC MAXOS] |