



Maxos accessories

9MX056 EC7

Maxos accessories, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Dane produktu

Eksploatacja i połączenie elektryczne	
Napięcie wejściowe	220 do 240 V
Częstotliwość linii	50 to 60 Hz
Klasa ochrony IEC	Klasa bezpieczeństwa I

Mechanika i korpus	
Kod stopnia ochrony	-
Kolor akcesorium	-
Waga netto (szt.)	0,006 kg

Certyfikaty i zastosowania	
Znak CE	Tak
Zgodność z normą UE RoHS	Tak

Dane techniczne produktu	
Nazwa produktu na zamówieniu	9MX056 EC7
Pełna nazwa produktu	9MX056 EC7
Full EOC	403073213179200
Kod zamówienia	13179200
Materiał Nr (12NC)	910605019226
Numerator – Liczba sztuk w opakowaniu	1
EAN/UPC – Produkt/opakowanie	4030732131792
Numerator - Packs per outer box	1
EAN/UPC – Opakowanie	4030732131792
Rodzina produktów	9MX056 [ACC MAXOS]