



Maxos accessories

9MX056 EC7 (10PCS)

Maxos accessories, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 to 60 Hz
Protection class IEC	Safety class I

Mechanical and Housing	
Ingress protection code	-
Accessory color	-
Net Weight (Piece)	0.060 kg

Approval and Application	
CE mark	Yes
EU RoHS compliant	Yes

Product Data	
Order product name	9MX056 EC7 (10PCS)
Full product name	9MX056 EC7 (10PCS)
Full product code	403073203217400
Order code	910606293921
Material Nr. (12NC)	910606293921
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	4030732032174
Numerator - Packs per outer box	1
EAN/UPC - Case	4030732032174
Product family code	9MX056 [ACC MAXOS]