



Maxos, Accessoires

9MX056 EC7 (10PCS)

Maxos, Accessoires, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Données du produit

Fonctionnement et électricité	
Tension d'entrée	220 à 240 V
Fréquence linéaire	50 to 60 Hz
Classe de protection CEI	Classe électrique I

Mécanique et boîtier	
Indice de protection	-
Couleur des accessoires	-
Poids net (pièce)	0.060 kg

Approbation et application	
Marquage CE	Oui
Conforme à RoHS	Oui

Données du produit	
Nom du produit de la commande	9MX056 EC7 (10PCS)
Nom de produit complet	9MX056 EC7 (10PCS)
Code EOC	403073203217400
Code de commande	4030732032174
Code 12NC	910606293921
Numérateur - Quantité par kit	1
Code EAN - Produit/Boîte	4030732032174
Conditionnement par carton	1
Codes EAN/UPC - Boîte	4030732032174
Code famille de produits	9MX056 [ACC MAXOS]