



# Maxos accessories

## 9MX056 EC7 (10PCS)

Maxos accessories, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

### Dane produktu

Eksploatacja i połączenie elektryczne	
Napięcie wejściowe	220 do 240 V
Częstotliwość linii	50 to 60 Hz
Klasa ochrony IEC	Klasa bezpieczeństwa I

  

Mechanika i korpus	
Kod stopnia ochrony	-
Kolor akcesorium	-
Waga netto (szt.)	0,060 kg

  

Certyfikaty i zastosowania	
Znak CE	Tak
Zgodność z normą UE RoHS	Tak

Dane techniczne produktu	
Nazwa produktu na zamówieniu	9MX056 EC7 (10PCS)
Pełna nazwa produktu	9MX056 EC7 (10PCS)
Full EOC	403073203217400
Kod zamówienia	03217400
Materiał Nr (12NC)	910606293921
Numerator – Liczba sztuk w opakowaniu	1
EAN/UPC – Produkt/opakowanie	4030732032174
Numerator - Packs per outer box	1
EAN/UPC – Opakowanie	4030732032174
Rodzina produktów	9MX056 [ACC MAXOS]