



Maxos accessories

9MX056 CPI

Maxos accessories, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Product data

Operating and Electrical		Full product name	
Protection class IEC	-	Full product name	9MX056 CPI
Mechanical and Housing		Full EOC	403073210809100
Ingress protection code	-	Local code description	9MX056CPI
Accessory colour	-	Order code	910681003526
Net Weight (Piece)	0.220 kg	Material no. (12 NC)	910681003526
Approval and Application		Local order code	9MX056CPI
CE mark	Yes	Numerator – quantity per pack	1
EU RoHS compliant	Yes	EAN/UPC – Product/Case	4030732108091
Product Data		Numerator – packs per outer box	1
Order product name	9MX056 CPI	EAN/UPC - Case	4030732108091
		Product family code	9MX056 [ACC MAXOS]