



Maxos, Accessoires

9MX056 CPI

Maxos, Accessoires, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Données du produit

Fonctionnement et électricité	
Classe de protection CEI	-
Mécanique et boîtier	
Indice de protection	-
Couleur des accessoires	-
Poids net (pièce)	0,220 kg
Approbation et application	
Marquage CE	Oui
Conforme à RoHS	Oui
Données du produit	
Nom du produit de la commande	9MX056 CPI
Nom de produit complet	9MX056 CPI
Code EOC	403073210809100
Description du code local calculé B2B	9MX056CPI
Code de commande	4030732108091
Code 12NC	910681003526
Code de commande local	4030732108091
Numérateur - Quantité par kit	1
Code EAN - Produit/Boîte	4030732108091
Conditionnement par carton	1
Codes EAN/UPC - Boîte	4030732108091
Code famille de produits	9MX056 [ACC MAXOS]