



Maxos, Accessoires

9MX056 CPI

Maxos, Accessoires, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Données du produit

Fonctionnement et électricité		Nom de produit complet	9MX056 CPI
Classe de protection CEI	-	Code EOC	403073210809100
Mécanique et boîtier		Code de commande	4030732108091
Indice de protection	-	Code 12NC	910681003526
Couleur des accessoires	-	Numérateur - Quantité par kit	1
Poids net (pièce)	0.220 kg	Code EAN – Produit/Boîte	4030732108091
Approbation et application		Conditionnement par carton	1
Marquage CE	Oui	Codes EAN/UPC - Boîte	4030732108091
Conforme à RoHS	Oui	Code famille de produits	9MX056 [ACC MAXOS]
Données du produit			
Nom du produit de la commande	9MX056 CPI		