Maxos accessories

9MX056 CPI

Maxos accessories, Normal, 9MX056 | ACC MAXOS

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Dane produktu

Eksploatacja i połączenie elektryczne	
Klasa ochrony IEC	-

Mechanika i korpus	
Kod stopnia ochrony	-
Kolor akcesorium	-
Waga netto (szt.)	0,220 kg

Certyfikaty i zastosowania	
Znak CE	Tak
Zgodność z normą UE RoHS	Tak

Dane techniczne produktu	
Nazwa produktu na zamówieniu	9MX056 CPI
Pełna nazwa produktu	9MX056 CPI
Full EOC	403073210809100
Kod zamówienia	10809100
Materiał Nr (12NC)	910681003526
Numerator – Liczba sztuk w opakowaniu	1
EAN/UPC – Produkt/opakowanie	4030732108091
Numerator - Packs per outer box	1
EAN/UPC – Opakowanie	4030732108091
Rodzina produktów	9MX056 [ACC MAXOS]