



# UniFlood C Pro

## BVP372 16LED 40K 220V 10 40W HP

UniFlood C Pro, 2870 lm, 40 W, 840 neutral white, Safety class I

The Philips UniFlood C Pro offers a unique rugged elegance, with a cylindrical form and flowing lines that connect the front and back housings beautifully. This is a compact architectural floodlighting design where every element has a purpose; the front section provides exceptional lighting, the back section houses all the electrical components. Between the two, the fins dissipate heat and also serve as a decorative element. Exterior-rated, the Philips UniFlood C Pro is a cost-effective, architectural LED floodlight that is designed for façade, landscape and outdoor floodlighting applications. The robust mechanical design and high-efficiency optics make it ideal for illuminating multi-storey exterior façades, bridges, landmarks and monuments. Architects and designers have the freedom to explore a wide range of concepts and designs with no limitations, thanks to a range of colours, multiple spread lenses and a DMX512/RDM control option.

### Warnings and Safety

- For outdoor use only

### Product data

General Information		Color rendering index (CRI)	
Color Code	840 neutral white		>80
Driver included	Yes	Light source color	840 neutral white
Lighting Technology	LED	<b>Operating and Electrical</b>	
Value ladder	Performance	Input Voltage	220 to 240 V
<b>Light Technical</b>		Line Frequency	50 to 60 Hz
Luminous Flux	2,870 lm	Power Consumption	40 W
Correlated Color Temperature (Nom)	4000 K	Power Factor (Fraction)	0.9
Luminous Efficacy (rated) (Nom)	72 lm/W	Connection	Flying leads/wires
		Cable	Cable 0.5 m without plug 3-pole

# UniFlood C Pro

Protection class IEC	Safety class I
----------------------	----------------

## Controls and Dimming

Dimmable	No
Control interface	-

## Mechanical and Housing

Housing Material	Aluminum die cast
Optical cover material	Polycarbonate
Housing Color	Dark gray
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK06 [1 J]
Optical cover type	Clear glass
Net Weight (Piece)	3.000 kg

## Approval and Application

CE mark	Yes
Ambient temperature range	-40 to +50 °C

## Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

## Product Data

Order product name	BVP372 16LED 40K 220V 10 40W HP
Full product name	BVP372 16LED 40K 220V 10 40W HP
Full product code	872016950412799
Order code	911401774303
Material Nr. (12NC)	911401774303
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169504127
Numerator - Packs per outer box	4
EAN/UPC - Case	8720169504127

## Dimensional drawing

