



Ledinaire batten BN045C

BN045C 25S/840 PSU L1200

Ledinaire batten BN045C, 21 W, L1200 mm, 2500 lm, 4000 K, IP20, TW1-ready

L1200 mm, Steel, White, Signal white (RAL9003), Power supply unit (On/Off), 2500 lm, 21 W, 119 lm/W, 4000 K, (0.38, 0.38) SDCM \leq 5, Beam angle 120°, Polycarbonate, IP20 | Finger-protected, IK02 | 0.2 J standard, Safety class I, Push-in connector 3-pole, Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)

Product data

General Information		Optic type	
Light source replaceable	No	Beam angle 120°	
Number of gear units	1 unit	Luminaire light beam spread	
Driver included	Yes	120°	
Service tag	No	Unified glare rating CEN	
Lighting Technology	LED	28	
Value ladder	Value	Operating and Electrical	
Warranty period	5 years	Input Voltage	
Light Technical		220-240 V	
Luminous Flux	2,500 lm	Line Frequency	
Saturated Red (R9)	<50	50 or 60 Hz	
Correlated Color Temperature (Nom)	4000 K	Inrush current	
Luminous Efficacy (rated) (Nom)	119 lm/W	7.2 A	
Color rendering index (CRI)	>80	Inrush time	
Light source color	840 neutral white	0.444 ms	
		Power Consumption	
		21 W	
		Power Factor (Fraction)	
		0.9	
		Connection	
		Push-in connector 3-pole	
		Cable	
		-	
		Number of products on MCB of 16 A type B	
		23	
		Suitable for random switching	
		Yes	
		Protection class IEC	
		Safety class I	

Ledinaire batten BN045C

Feed-through wiring	Simple Connection and removable cover available for feed-through wiring 1-phase (internal wiring is not included)
----------------------------	---

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No

Mechanical and Housing

Housing Material	Steel
Reflector material	-
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	White
Optical cover finish	-
Overall length	1,125 mm
Overall width	58 mm
Overall height	59 mm
Dimensions (Height x Width x Depth)	59 x 58 x 1125 mm
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Net Weight (Piece)	0.900 kg

Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	1.6
Ambient temperature range	-20 to +40 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
--------------------------------	--------

Initial chromaticity	(0.38, 0.38) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L70

Sustainability Data

Sustainability rating	Unclassified
Repair class	Repair Class D, this product is not designed to be repaired.
Embedded carbon (A1-A3)	11.3 kg CO _{2e}
Product non-virgin material ratio	23.3 %
Recyclable content ratio of the finished product	64.7 %
GWP total B6 (kg CO_{2eq}) Declared Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * Service life (hrs) Declared Unit * Energy mix (kg CO _{2eq} / kWh)
GWP total B6 (kg CO_{2eq}) Functional Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * 1000 (lm) /lumen output (lm) Declared Unit * 35000 (hrs) * Energy mix (kg CO _{2eq} / kWh)
Non-virgin material ratio of the packaging	Cardboard > 80% recycled Plastic >35% recycled
Packaging Recyclable content ratio	Cardboard recycling rate > 80% Plastic recycling rate > 40%
Packaging Material	Cardboard Plastic

Product Data

Order product name	BN045C 25S/840 PSU L1200
Full product name	BN045C 25S/840 PSU L1200
Full product code	871951496358099
Order code	911401806385
Material Nr. (12NC)	911401806385
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8719514963580
Numerator - Packs per outer box	12
EAN/UPC - Case	8719514963641

Ledinaire batten BN045C

Dimensional drawing

