



# Ledinaire High-bay

## BY030P LED150\_220\_280S/840\_50\_65 PSU WB

Ledinaire High-bay, All-in, 195 W, 145 W, 100 W,  $\phi$ 320 mm, 15000 lm, 22000 lm, 28000 lm, 4000 K, 5000 K, 6500 K, Symmetrical, IP65, IK07

$\phi$ 320 mm, Aluminum die-cast, Aluminum and black, Jet black (RAL9005), Single layer powder coating, Suspended, Power supply unit, All-in, Multi Lumen, All-in, Multi Color Temperature, 15000 lm, 22000 lm, 28000 lm, 195 W, 145 W, 100 W, 152 lm/W, 142 lm/W, 4000 K, 5000 K, 6500 K, (0.38, 0.38); (0.31, 0.34) SDCM $\leq$ 5, Symmetrical, Clear, Polycarbonate, IP65 | Dust penetration-protected, jet-proof, IK07 | 2 J reinforced, Safety class I, Screw connector

### Product data

General Information	
Number of gear units	1 unit
Driver included	Yes
Value ladder	Value
Warranty period	5 years
Light Technical	
Luminous Flux	15,000 22,000 28,000 lm
Saturated Red (R9)	<50
Correlated Color Temperature (Nom)	4000 5000 6500 K
Luminous Efficacy (rated) (Nom)	152 142 lm/W
Color rendering index (CRI)	>80
Light source color	840 neutral white, neutral white and 865 cool daylight
Optic type	Symmetrical
Luminaire light beam spread	90°

Unified glare rating CEN	31
All-in Type	All-in, Multi Lumen All-in, Multi Color Temperature
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Inrush current	68 A
Inrush time	0.213 ms
Power Consumption	195 145 100 W
Power Factor (Fraction)	0.9
Connection	Screw connector
Cable	Cable 0.3 m with connector 3-pole
Number of products on MCB of 16 A type B	9
Suitable for random switching	No

## Ledinaire High-bay

Protection class IEC	Safety class I
Total harmonic distortion	20 %

### Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit
Control interface	-
Constant light output	No
Embedded control	-
Photocell	-

### Mechanical and Housing

Housing Material	Aluminum die-cast
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	-
Housing Color	Aluminum and black
Optical cover finish	Clear
Reflector Finish	-
Overall height	119 mm
Overall diameter	320 mm
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Mounting	Suspended
Net Weight (Piece)	2.460 kg

### Emergency Operation

Central Emergency	No
-------------------	----

### Approval and Application

Glow-wire test	Temperature 650 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 1 @200mm to EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9
Ambient temperature range	-30 to +50 °C

### Initial Performance (IEC Compliant)

Luminous flux tolerance	-10% / +10%
-------------------------	-------------

Initial chromaticity	(0.38, 0.38); (0.31, 0.34) SDCM≤5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Control gear failure rate at median useful life 75000 h	15 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L80
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	L65

### Sustainability Data

Sustainability rating	Unclassified
Repair class	Repair Class D, this product is not designed to be repaired.
Embedded carbon (A1-A3)	47.5 kg CO <sub>2e</sub>
Product non-virgin material ratio	8.38 %
Recyclable content ratio of the finished product	44.2 %
GWP total B6 (kg CO <sub>2eq</sub> ) Declared Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * Service life (hrs) Declared Unit * Energy mix (kg CO <sub>2eq</sub> / kwh)
GWP total B6 (kg CO <sub>2eq</sub> ) Functional Unit	Please calculate using your local energy mix value: Power Declared Unit (kW) * 1000 (lm) /Lumen output (lm) Declared Unit * 35000 (hrs) * Energy mix (kg CO <sub>2</sub> eq / kwh)

### Product Data

Order product name	BY030P LED150_220_280S/840_50_65 PSU WB
Full product name	BY030P LED150_220_280S/840_50_65 PSU WB
Full product code	872016975897100
Order code	911401822687
Material Nr. (12NC)	911401822687
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8720169758971
Numerator - Packs per outer box	1
EAN/UPC - Case	8720169758971

# Ledinaire High-bay

## Dimensional drawing

BY030P LED150\_220\_280S/840\_50\_65 PSU WB

