



Ledinaire Waterproof

WT060C LED36S/865 PSU L1200 BN

Ledinaire Waterproof, (in brown Eco Packaging), 30 W, L1200 mm, 3600 lm, 6500 K, Symmetrical, Opal, IP66, IK08

Uncomplicated, off-the-shelf quality and reliability – that’s the beauty of LEDINAIRE. LEDINAIRE keeps it simple, delivering the essentials and nothing more. We don’t spend money on things you don’t need: no flashy packaging, no unnecessary brochures. We offer a selection of popular, low-cost LED solutions, ensuring that LED lighting is within your price range, and that our products always meet the highest possible standard. This no-nonsense approach to lighting means that you get exactly what it says on the box – reliability, affordability, and energy efficiency. Designed for mainstream applications, the sturdy LEDINAIRE WT060C Waterproof is a cost-effective, energy-saving LED solution for use in wet and dusty environments.

Product data

General Information	
Light source replaceable	No
Number of gear units	1 unit
Driver included	Yes
Service tag	No
Lighting Technology	LED
Value ladder	Value
Serviceability class	Class C, luminaire without serviceable parts, not serviceable
Warranty period	5 years
Sustainability rating	Unclassified

Light Technical	
Luminous Flux	3,600 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	120 lm/W
Color rendering index (CRI)	>80
Beam angle of light source	120 degree(s)
Light source color	865 cool daylight
Optic type	Symmetrical
Luminaire light beam spread	120°
Unified glare rating CEN	26

Operating and Electrical	
Input Voltage	220 to 240 V

Ledinaire Waterproof

Line Frequency	50 or 60 Hz
Inrush current	3 A
Inrush time	0.101 ms
Power Consumption	30 W
Power Factor (Fraction)	0.9
Connection	Connection unit 2-pole
Cable	-
Number of products on MCB of 16 A type B	45
Suitable for random switching	Yes
Protection class IEC	Safety class II
Total harmonic distortion	20 %

Controls and Dimming

Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Control interface	-
Constant light output	No
Maximum dim level	Not applicable

Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Grey
Optical cover finish	Opal
Overall length	1,201 mm
Overall width	69 mm
Overall height	59 mm
Dimensions (Height x Width x Depth)	59 x 69 x 1201 mm
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Net Weight (Piece)	0.560 kg

Approval and Application

Glow-wire test	Temperature 850 °C, duration 30 s
Flammability mark	For mounting on normally flammable surfaces

CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 0 @200mm to EN62778
EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	1.6
Ambient temperature range	-20 to +45 °C

Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-10%
Initial chromaticity	<5
Power consumption tolerance	+/-10%
Standard Deviation of Colour Matching (McAdam ellipse)	SDCM≤5

Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L70
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	-


Product Data

Order product name	WT060C LED36S/865 PSU L1200 BN
Full product name	WT060C LED36S/865 PSU L1200 BN
Full product code	871016336015799
Order code	36015799
Material Nr. (12NC)	911401877280
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163360157
Numerator - Packs per outer box	12
EAN/UPC - Case	8710163360270

Ledinaire Waterproof

Dimensional drawing

WT060C



Strip type	A	B	C	D	E	F	G	H
L800	88	88	88	871	100 100	100 100		
L1200	88	88	88	1200	200 200	200 200		
L1800	88	88	88	1800	100 100	100 100		
L1800	88	88	88	1800	100 200	100 200	88x4	

