



# Emergency Twin Spot

## EM164C SM TWIN SPOT NM3 ELP IP65

Emergency Twin Spot, 9 W, 9 W, 300x287.5mm; H68.5 mm, 1000 lm, 6500 K, IP65, ELB3h

300x287.5mm; H68.5 mm, Polycarbonate, White, Signal white (RAL9003), 1000 lm, 9 W, 135 lm/W, 6500 K, 0.33, Ribbed, UV stabilized Polycarbonate cover, IP65 | Dust penetration-protected, jet-proof, IK07 | 2 J reinforced, Safety class II, 2 Push-in connector 3-pole, Emergency lighting 3 hours duration basic version

### Product data

General Information	
Lamp family code	-
Number of gear units	1 unit
Driver included	Yes
Light source engine type	LED
Warranty period	5 years
Light Technical	
Upward light output ratio	3.71
Luminous Flux	1,000 lm
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	135 lm/W
Color rendering index (CRI)	>80
Light source color	6500
Optic type	-
Luminaire light beam spread	120°
Optic type outdoor	-
Effective projected area	16 m²

Operating and Electrical	
Input Voltage	220-240 V
Line Frequency	50 Hz
Initial CLO power consumption	9 W
Average CLO power consumption	9 W
End CLO power consumption	9 W
Inrush current	3.95 A
Inrush time	100 ms
Power Consumption	9 W
Power Factor (Fraction)	0.4
Connection	2 Push-in connector 3-pole
Cable	-
Number of products on MCB of 16 A type B	189
Suitable for random switching	Not applicable
Protection class IEC	Safety class II
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	-

## Emergency Twin Spot

Control interface	Internal (no external connection)
Constant light output	No
Maximum dim level	Not applicable
Embedded control	-

### Mechanical and Housing

Housing Material	Polycarbonate
Reflector material	-
Optic material	Polycarbonate
Optical cover material	UV stabilized Polycarbonate cover
Fixation material	-
Housing Color	White
Mounting device	-
Optical cover finish	Ribbed
Reflector Finish	-
Overall length	300 mm
Overall width	288 mm
Overall height	69 mm
Dimensions (Height x Width x Depth)	69 x 288 x 300 mm
Parts color	All parts colored
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Standard tilt angle posttop	0°
Standard tilt angle side entry	0°
Optical cover type	-
Net Weight (Piece)	1.267 kg

### Emergency Operation

Emergency flux	1,000 lm
Rated duration of the emergency lighting (when fully charged)	3 hour(s)
Additional max. power consumption when emergency battery is charging	9 W
Central Emergency	No
Emergency lighting	Emergency lighting 3 hours duration basic version
Emergency function testing method	Manual / Test button
Emergency lighting operation mode	Non-maintained

### Approval and Application

Glow-wire test	-
Flammability mark	-
CE mark	Yes
ENEC mark	-
Photobiological risk	Photobiological risk group 0 @ 200mm to EN62471
Photobiological risk specification	0 m

EU RoHS compliant	Yes
Performance ambient temperature Tq	25 °C
Ambient temperature range	+5 to +45 °C

### Initial Performance (IEC Compliant)

Luminous flux tolerance	+/-5%
Initial chromaticity	0.33
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 35000 h	5 %
Control gear failure rate at median useful life 50000 h	10 %
Control gear failure rate at median useful life 75000 h	25 %
Control gear failure rate at median useful life 100000 h	50 %
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 35000 h	L85
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 50000 h	L85
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 75000 h	L85
Lumen maintenance (EN-IEC 62722-2-1) at median useful life* 100000 h	L85

### Sustainability Data

Sustainability rating	Unclassified
Repair class	Repair Class D, this product is not designed to be repaired.

### Product Data

Order product name	EM164C SM TWIN SPOT NM3 ELP IP65
Full product name	EM164C SM TWIN SPOT NM3 ELP IP65
Full product code	871869979898700
Order code	912401483513
Material Nr. (12NC)	912401483513
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8718699798987
Numerator - Packs per outer box	10
EAN/UPC - Case	8718699799960

## Emergency Twin Spot

### Dimensional drawing

