



HF-Selectalume II for TL-D lamps

HF-S 258 TL-D II 220-240V 50/60Hz

HF-Selectalume II is the most cost-effective, reliable, slim and affordable fluorescent solution, with highly disruptive technology for energy saving, system flexibility and unsurpassed performance. The cost-saving HF-Selectalume II has a robust design which meets all relevant international safety and performance standards. HF-Selectalume II is intended for use with indoor lighting fixtures such as spotlights, downlights and recessed luminaires, which are largely used in office, retail, industry, hotel, restaurant and other applications where control devices are installed with occasional On/Off switching activity

Product data



Operating and Electrical		T-Case Maximum (Max)	75 °C
Input Voltage	220 to 240 V	Mechanical and Housing	
Line Frequency	50 to 60 Hz	Housing	L 280x30x28
Input Frequency	50 to 60 Hz	Ingress protection code	IP20 [Finger-protected]
Earth Leakage Current (Max)	0.5 mA	Net Weight (Piece)	0.193 kg
Inrush Current Width	0.35 ms	Approval and Application	
Inrush Current Peak (Max)	28 A	Energy Efficiency Index	A2 BAT
Number of Products on MCB (16A Type B) (Nom)	12	Approval Marks	F-Marking CE marking ENEC certificate CCC certificate C-Tick certificate PSB certification TISI marking SIRIM approval CB Certificate CCC certificate VDE-EMV certificate
Wiring		CE mark	Yes
Connector Type Input Terminals	WAGO 744 connector	Ambient temperature range	-20 °C to 50 °C
Connector Type Output Terminals	WAGO 744 connector [Suitable for manual wiring]		
Temperature			
T-Case Lifetime (Nom)	75 °C		

HF-Selectalume II for TL-D lamps

Product Data	
Order product name	HF-S 258 TL-D II 220-240V 50/60Hz
Full product name	HF-S 258 TL-D II 220-240V 50/60Hz
Full product code	872790089746300
Order code	913713032566
Material Nr. (12NC)	913713032566

Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8711500999085
Numerator - Packs per outer box	12
EAN/UPC - Case	8727900897463

Dimensional drawing



Product	D1	C1	A1	A2	B1
HF-S 258 TL-D II 220-240V 50/60Hz	4.1 mm	28.0 mm	280.0 mm	265.0 mm	30.0 mm

