Australia and New Zealand Certificate of Suitability- addendum

Certificate
ULL-102959-A1

Issue date
2026-06-09

Expiration date
2031-06-09

This is to acknowledge that

Signify Netherlands B.V.

High Tech Campus 48, EINDHOVEN 5656 AE
Netherlands

has had

Electronic Controlgear for LED modules

[refer following page(s) for models list]

evaluated and meets the requirements of the standard(s)

AS 61347.2.13:2018; AS/NZS 61347.1:2016, Amd 1: 2018, Amd 2: 2025

ANZ Certification Scheme requirements.

Stuart Foster (Certification Officer)

Certification Body:
UL International New Zealand Limited,
54 Tarndale Grove, Albany, Auckland 0632, New Zealand.

Issued for use in Australia and New Zealand only.
All dates are in Year-Month-Day format (YYYY-MM-DD).

JAS-ANZ

www.jasanz.org/register

UL Solutions

© 2026 UL LLC. All rights reserved.

Australia and New Zealand
Certificate of Suitability-addendum

Certificate No: ULL-102959-A1
Original Date of Certification: 2023-05-12
Date of Issue/Revision: 2026-06-09

Trade Name or Trademark: PHILIPS, SIGNIFY, XITANIUM, ADVANCE

Risk Class / NSW Declared Class: EESS OUT OF SCOPE - Non-prescribed / non-declared

IEC Standard Country Differences: AU and NZ

Certification Marking: The RCM may be applied to the product and all the requirements of all relevant parts of AS/NZS 4417 applicable to the article shall be fulfilled.

Additional Certification Conditions: None.

Model Details and Additional Information:
Models Details and rating :
Xi FP 75W 0.2-0.7A SNLDAE 230V S240 sXt:
Uin: 220-240Vac, Iin: 0.43-0.35Aac, Uin: 186-250Vdc, Iin: 0.3Adcmax, fn: 50/60Hz, DC, Pin: 82W, PF: 0.95, Prated: 75W, Uoutput: 50-150V. Uout:190 Vmax (open circuit), Irated: 200-700mA, ta: -40…+55 °C, tc: 85 °C

Xi FP 75W 0.3-1.0A SNLDAE 230V S240 sXt:
Uin: 220-240Vac, Iin: 0.43-0.36Aac, Uin: 186-250Vdc, Iin: 0.3Adcmax, fn: 50/60Hz, DC, Pin: 82W, PF: 0.95, Prated: 75W, Uoutput: 35-108V. Uout: 140Vmax (open circuit), Irated: 300-1050mA, ta: -40…+55 °C, tc: 85 °C

Xi FP 150W 0.2-0.7A SNLDAE 230V S240 sXt:
Xi FP 150W 0.2-0.7A SNLDAE 1pct S240 sXt:
Uin: 220-240Vac, Iin: 0.80-0.70Aac, Uin: 186-250Vdc, Iin: 0.6Adcmax, fn: 50/60Hz, DC, Pin: 163W, PF: 0.95, Prated: 150W, Uoutput: 90-283V. Uout: 340Vmax (open circuit), Irated: 200-700mA, ta: -40…+55 °C, tc: 90 °C

Xi FP 150W 0.3-1.0A SNLDAE 230V S240 sXt:
Uin: 220-240Vac, Iin: 0.80-0.70Aac, Uin: 186-250Vdc, Iin: 0.6Adcmax, fn: 50/60Hz, DC, Pin: 163W, PF: 0.95, Prated: 150W, Uoutput: 70-214V. Uout: 260Vmax (open circuit), Irated: 300-1050mA, ta: -40…+55 °C, tc: 90 °C

Details of addendum :
- Certificate is renewed.
- Trade names “SIGNIFY”, “XITANIUM”, and “ADVANCE” added.

© 2026 UL LLC. All rights reserved.
Form-ULID-013925-CoS - ver 2.0