

CERTIFICATE

Issued to:
Applicant:
Signify Netherlands B.V.
High Tech Campus 48
5656 AE Eindhoven, The Netherlands

Licensee:
Signify Netherlands B.V.
High Tech Campus 48
5656 AE Eindhoven, The Netherlands

Product : LED Driver
Trade name(s) : PHILIPS
Type(s)/model(s) : Xi SR 150W 0.2–0.7A SNEMP 230V S240 sXt, Xi SR 150W 0.3–1.0A SNEMP 230V S240 sXt, Xi SR 75W 0.2–0.7A SNEMP 230V S240 sXt and Xi SR 75W 0.3–1.0A SNEMP 230V S240 sXt

The product and any acceptable variation thereto is specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:

- a type test according to the standard(s) EN 61347-2-13:2014, EN 61347-2-13:2014/A1:2017, EN 61347-1:2015, EN 61347-1:2015/A1:2021 and EN IEC 62384:2020
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 947556


DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 5 December 2022 and expires upon withdrawal of one of the above mentioned standards.

Certificate number: 31-126439

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



K. Lin
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



SPECIFICATION OF THE CERTIFIED PRODUCT**Product data**

Product	: LED Driver
Trade name(s)	: PHILIPS
Type(s)/model(s)	: Xi SR 150W 0.2–0.7A SNEMP 230V S240 sXt, Xi SR 150W 0.3–1.0A SNEMP 230V S240 sXt, Xi SR 75W 0.2– 0.7A SNEMP 230V S240 sXt and Xi SR 75W 0.3– 1.0A SNEMP 230V S240 sXt
Rated voltage	: 220-240 Vac or 186-250 Vdc
Rated frequency	: 50/60 Hz at ac
Power factor	: 0,95
Ambient temperature (ta)	: -40...+55 °C
Description	: Built-in

Product data – type Xi SR 150W 0.2–0.7A SNEMP 230V S240 sXt

Input current	: 0,76-0,67Aac or 0,6-0,07Adc
Input power	: 162 W
Output current	: 200-700 mA
Output voltage	: 90-283 Vdc
Uout	: 350 Vdc
Output power	: 150 W
Max. case temperature (tc)	: 85 °C

Product data – type Xi SR 150W 0.3–1.0A SNEMP 230V S240 sXt

Input current	: 0,76-0,67Aac or 0,6-0,07Adc
Input power	: 162 W
Output current	: 300-1050 mA
Output voltage	: 70-214 Vdc
Uout	: 260 Vdc
Output power	: 150 W
Max. case temperature (tc)	: 85 °C

Product data – type Xi SR 75W 0.2–0.7A SNEMP 230V S240 sXt

Input current	: 0,38-0,34 Aac or 0,3-0,04 Adc
Input power	: 82 W
Output current	: 200-700 mA
Output voltage	: 50-150 V
Uout	: 200 Vdc
Output power	: 75 W
Max. case temperature (tc)	: 80 °C

Product data – type Xi SR 75W 0.3–1.0A SNEMP 230V S240 sXt

Input current	: 0,38-0,34 Aac or 0,3-0,04 Adc
Input power	: 82 W
Output current	: 300-1050 mA
Output voltage	: 35-108 V
Uout	: 150 Vdc
Output power	: 75 W
Max. case temperature (tc)	: 80 °C

TESTS**Test requirements**

EN 61347-2-13:2014
EN 61347-2-13:2014/A1:2017
EN 61347-1:2015
EN 61347-1:2015/A1:2021
EN IEC 62384:2020

Test result

The test results are laid down in DEKRA test file 614108900.

Additional information

constant current type with screwless terminal blocks
LED driver is completely potted with asphalt
Double/reinforced insulation between PRI and SEC
DALI/SR is SELV

The tests were performed by the manufacturer under the conditions of the agreement concerning the manufacturer's right to conduct type tests for the ENEC certification system under supervision of DEKRA (CTF Stage 3).

The list of components is laid down in test report 6141089.50.

Conclusion

The examination proved that all requirements were met.

Factory location

The factory location is registered with the number 674666.