

FO Strip VOcs

Fortimo LED Strip VOcs is an efficient and flexible dual channel LED module from Advance. When paired with CertaDrive Xcs drivers it creates a ready made system to reduce luminaire SKU count by up to 9x (3x CCT and 3x Flux outputs).

Key features and benefits

Features

- Low system cost and optimized performance with five-year limited system warranty if paired with Advance CertaDrive Xcs
- High efficiency LEDs
- CRI80 color rendering
- 50,000 hours lifetime
- Mechanical footprint compatibility with LED Strip product family
- 3 SDCM color consistency at endpoints
- Breakable in half to create two 22in modules

Benefits

- Maximize SKU and component flexibility with fewer luminaire SKUs to produce or warehouse

Applications

- Education
- Office
- Healthcare
- Retail
- Hospitality

Ordering data

Commercial product name	12NC	Box quantity
FO Strip VOcs 44in 5400lm 835-850 LV1	9290 027 47013	120

Drive currents

Parameter	Nominal*	Life**	Max***	Unit
FO Strip VOcs 44in 5400lm 835-850 LV1	770	1100	1350	mA

Module temperatures

Parameter	Nominal*	Life**	Max***	Unit
T_c (case temperature at T_c point)	45	85	90	°C

* Nominal value at which typical performance is specified

** Value at which life time is specified

*** Maximum value for safe operation, do not operate above this value

Suggested maximum current at elevated ambient

Setting	1	2	3	4	Unit
Luminaire maximum ambient	35	45	55	65	°C
Suggested maximum current*	1100	1100	1100	850	mA

* Drive current that may be possible at the reference external ambient temperature. The maximum suggested current given is for a typical non-lensed luminaire design with good thermal transfer capability. Use of a lensed luminaire or luminaires with non-optimal thermal characteristics will require a further current reduction to meet the same maximum ambient temperature. The current suggestion is based on the module Tc-life and thermal testing must be used to verify Tc-life is never exceeded for your specific luminaire. It may be necessary to adjust the final current value in order to meet the Tc-life rating of the module.


Optical characteristics - table per color (CCT)

FO Strip VOcs 44in 5400lm 835-850 LV1 [3500K]

Parameter	Min	Typ	Max	Unit
Luminous flux	4870	5270	5670	lm
Efficacy	157	175		lm/W
Correlated color temperature (CCT)		3500		K
Color consistency			3	SDCM
CRI	80			
R9	0			

Measurement precision ± 5% for the flux data and ± 6% for the efficacy data. Measurement precision for color coordinates ± 0.005. Measurement precision for CRI ± 1.5 and R9 ± 3.

Operation point	835	lm	lm/W
80% I-nom 616mA	Tc 25 °C	4400	184
	Tc-nom 45 °C	4290	181
	Tc-life 85 °C	4020	172
I-nom 770mA	Tc 25 °C	5410	179
	Tc-nom 45 °C	5270	175
	Tc-life 85 °C	4940	167
I-life 1100mA	Tc 25 °C	7500	169
	Tc-nom 45 °C	7300	166
	Tc-life 85 °C	6830	158




FO Strip VOcs 44in 5400lm 835-850 LV1 [4000K]

Parameter	Min	Typ	Max	Unit
Luminous flux	5170	5590	6010	lm
Efficacy	173	192		lm/W
Correlated color temperature (CCT)		4000		K
CRI	80			
R9	0			

Measurement precision ± 5% for the flux data and ± 6% for the efficacy data. Measurement precision for color coordinates ± 0.005. Measurement precision for CRI ± 1.5 and R9 ± 3.

Operation point	840	lm	lm/W
80% I-nom 616mA	Tc 25 °C	4670	202
	Tc-nom 45 °C	4540	198
	Tc-life 85 °C	4260	188
I-nom 770mA	Tc 25 °C	5740	196
	Tc-nom 45 °C	5590	192
	Tc-life 85 °C	5240	183
I-life 1100mA	Tc 25 °C	7960	185
	Tc-nom 45 °C	7740	182
	Tc-life 85 °C	7250	172




FO Strip VOcs 44in 5400lm 835-850 LV1 [5000K]

Parameter	Min	Typ	Max	Unit
Luminous flux	5050	5460	5870	lm
Efficacy	163	182		lm/W
Correlated color temperature (CCT)		5000		K
Color consistency			3	SDCM
CRI	80			
R9	0			


Measurement precision ± 5% for the flux data and ± 6% for the efficacy data. Measurement precision for color coordinates ± 0.005. Measurement precision for CRI ± 1.5 and R9 ± 3.

Operation point	850	lm	lm/W
80% I-nom 616mA	Tc 25 °C	4550	190
	Tc-nom 45 °C	4430	187
	Tc-life 85 °C	4160	178
I-nom 770mA	Tc 25 °C	5600	185
	Tc-nom 45 °C	5460	182
	Tc-life 85 °C	5110	173
I-life 1100mA	Tc 25 °C	7780	176
	Tc-nom 45 °C	7580	173
	Tc-life 85 °C	7080	164



Beam shape

The LED-module has a Lambertian light distribution.



Electrical characteristics

FO Strip VOcs 44in 5400lm 835-850 LV1 [3500K]
FO Strip VOcs 44in 5400lm 835-850 LV1 [5000K]

Parameter	Min	Typ	Max	Unit
Forward voltage	37.3	39.0	40.9	V
Power consumption	28.7	30.0	31.5	W
Number of modules in series per chain			1	

Measurement precision for Vf +/- 3%. Measurement precision for power +/- 3.3%.

FO Strip VOcs 44in 5400lm 835-850 LV1 [4000K]

Parameter	Min	Typ	Max	Unit
Forward voltage	36.0	37.8	39.6	V
Power consumption	27.7	29.1	30.5	W
Number of modules in series per chain			1	

Measurement precision for Vf +/- 3%. Measurement precision for power +/- 3.3%.

System chain limits for Same Length modules


Total length (in)	Total current limit (mA)
88	800
132	540
176	400

Please review the design-in guide or contact the Design-in team for further information.

Tuning information


Flux and efficacy versus current (at Tc nominal)

I [mA]	Flux [%]	Efficacy [%]
1100	139	95
935	120	97
770	100	100
616	81	103
385	52	108



Flux and efficacy versus temperature at Tc (at I nominal)


Tc [°C]	Flux [%]	Efficacy [%]
90	93	94
45	100	100
25	103	102
0	106	104



Lumen maintenance

Operation point	Lumen maintenance x 1000 hours	L70 B50	L80 B50	L90 B50
80% I-nom 616 mA	Ts nom 45°C	>60	>60	50
	Ts 75°C	>60	>60	50
	Ts-life 85°C	>60	>60	50
I-nom 770 mA	Ts nom 45°C	>60	>60	50
	Ts 75°C	>60	>60	50
	Ts-life 85°C	>60	>60	50
I-life 1100 mA	Ts nom 45°C	>60	>60	50
	Ts 75°C	>60	>60	50
	Ts-life 85°C	>60	>60	50

Performance Window



Thermal switching table

Warranted Number of Full Thermal Product Cycles at 25°C ambient temperature


Case Temperature – Tc [°C]	Amount of Cycles
45 (or less)	>100,000
55	>100,000
65	>100,000
75	66,000
85	32,000
90	22,000

Wiring

Specification item	Value	Unit	Condition
Input wire cross-section	0.25...0.75	mm^2	solid, stranded
	18...24	AWG	solid, stranded
Input wire strip length	7.5...9.5	mm	

Mechanical characteristics

Parameter	Min	Typ	Max	Unit
Length	1117.9	1118.4	1118.9	mm
Width	19.8	20	20.2	mm
Height PCB	1.4	1.6	1.8	mm
Height total		4.3		mm
Warpage (IPC-TM-650)			0.75	%



Absolute ratings

Parameter	Min	Max	Unit
Current through the LED module (I-max)		1350	mA
Case temperature (Tc-max)		90	°C
ESD (direct contact)	2		kV
Working voltage		60	V_{dc}
Ambient temperature	-40		°C

This LED module is an ESD sensitive device with ESD protection up to 2kV, tested according CAN/CSA-IEC 61000-4-2. Proper precautions to protect the product must be in place to maintain product reliability and warranty. These precautions are described in the design-in guide for the product and ANSI/ESD S20.20-2014. Precautions include, but are not limited to: ESD protection areas, equipment grounding, personal ESD protective measures and anti-static clothing, conductive flooring, ionizers, ESD packaging, etc. This product is not field replaceable.

Surge protection of the module must be provided by the driver or other components. Advance Xitanium and Certadrive drivers have built in protection circuitry and will protect the module up to the specified driver surge rating. When using third party drivers testing or confirmation from manufacturer is suggested to ensure adequate module protection.

Application information

Certificates and Standards
UL 8750

Environmental
RoHS/REACH

Application	
IP rating	No IP rating
Overheating protection	No protection
Luminaire class ANSI	Class 2
Dimming	Yes

There cannot be any ice/fog/mist on any part of the module surface during the application at -40°C.

Notes

View limited warranty at www.signify.com/warranties for details and restrictions.

© 2021 Signify Holding. All rights reserved. This document may be subject to change. No representation or warranty as to the accuracy or completeness of the information included herein is given and any liability for any action in reliance thereon is disclaimed. All trademarks are owned by Signify Holding or their respective owners.

Signify North America Corporation
200 Franklin Square Drive,
Somerset, NJ 08873
Telephone 855-486-2216

Signify Canada Ltd.
281 Hillmount Road,
Markham, ON
Canada L6C 2S3
Telephone 800-668-9008