



Ref. Certif. No.

DK-149987-M2-UL

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Built-in LED Module

Name and address of the applicant

Signify Netherlands B.V.
High Tech Campus 48 EINDHOVEN 5656 AE
Netherlands

Name and address of the manufacturer

Signify Netherlands B.V.
High Tech Campus 48 EINDHOVEN 5656 AE
Netherlands

Name and address of the factory

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

SELV input, I_{max} 4140 mA  V_{max} 55 V
☒ [Additional Information on page 3-4](#)

Trademark / Brand (if any)

PHILIPS

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Main series: Fortimo SLM C (z)(cc) (d) (m) L(ee) (s) G(i) (a)
☒ [Additional Information on page 2](#)

Additional information (if necessary may also be reported on page 2)

The report was revised to include technical modifications.
National Differences: EU Group Differences
☒ [Additional Information on page 5](#)

A sample of the product was tested and found to be in conformity with

IEC 62031:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

4791109019-2 issued on 2025-02-26

This CB Test Certificate is issued by the National Certification Body



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☒ UL Solutions (Denmark), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2025-03-03

Original Issue Date: 2024-01-31

Signature:

Thomas Wilson



Ref. Certif. No.

DK-149987-M2-UL

Factory(ies):

Additional Model Detail(s):

Product Key:

Main series: Fortimo SLM C (z)(cc) (d) (m) L(ee) (s) G(i) (a)

Where:

(z) = CRI divided by 10 (may be blank when d = "CED", or one digit, may be "7", "8", or "9");

(cc) = CCT divided by 100 (two digits or six characters (or blank when d = "CED"), may be a value between 22 and 57 (or "27-865" or "27-965" (when d = "TW")));

(d) = Flavour of light (two or three characters, may be "Px (x could be W, C, S, A or any character)" or "CW" or "FPR" or "FWW" or "FLS" or "FVF" or "FIS" or "CED" or "TW" or blank);

(m) = Die matrix (four digits, example 1216; chip configuration = 12 chips in series per string & 16 strings in parallels, (or blank when d = "CED"));

(ee) = Diameter of the Light Emitting Surface (LES) in millimeter (one or two digits, example 23; LES dimensions = 23mm);

(s) = PCB size in mm (four digits, example 2828: CoB dimension = 28mm x 28mm);

(i) = Number of generation of CoB (one digit, may be "8");

(a) = Suffix for commercial purposes (optional).

*each of the brackets in product key are optional

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2025-03-03

Original Issue Date: 2024-01-31

Signature:

Thomas Wilson

Additional Ratings:
Maximum ratings of the series:

CoB Type (Die matrix)	Diameter of LES of CoB [mm]	CCT [K]	DC Current [mA]	Power [W]	Power Density/LES of CoB [W/mm ²]	t _c [°C]
1309	15	≤ 4000	1000 (V _{f tot} 40V)	40	0,23	105
1319	23	≤ 4000	2000 (V _{f tot} 40V)	80	0,19	105
1201	6,5	≤ 5000	230 (V _{f tot} 41V)	9,4	0,28	105
1202	6,5	≤ 5000	460 (V _{f tot} 41V)	18,9	0,57	105
1202	6,5	≤ 5000	460 (V _{f tot} 41V)	18,9	0,57	105
1203	9,8	≤ 5000	690 (V _{f tot} 41V)	28,3	0,38	105
1203	9	≤ 5000	690 (V _{f tot} 41V)	28,3	0,44	105
1204	9,8	≤ 5000	920 (V _{f tot} 41V)	37,7	0,50	105
1204	9	≤ 5000	920 (V _{f tot} 41V)	37,7	0,59	105
1205	14,5	≤ 5000	1150 (V _{f tot} 41V)	47,2	0,29	105
1205	13	≤ 5000	1150 (V _{f tot} 41V)	47,2	0,36	105
1206	14,5	≤ 5000	1380 (V _{f tot} 41V)	56,6	0,34	105
1206	13	≤ 5000	1380 (V _{f tot} 41V)	56,6	0,43	105
1208	14,5	≤ 5000	1840 (V _{f tot} 41V)	75,4	0,46	105
1208	15	≤ 5000	1840 (V _{f tot} 41V)	75,4	0,43	105

CoB Type (Die matrix)	Diameter of LES of CoB [mm]	CCT [K]	DC Current [mA]	Power [W]	Power Density/LES of CoB [W/mm ²]	t _c [°C]
1210	14,5	≤ 5000	2300 (V _{f tot} 41V)	94,3	0,57	105
1211	22	≤ 5000	2530 (V _{f tot} 41V)	103,7	0,27	105
1211	18,5	≤ 5000	2530 (V _{f tot} 41V)	103,7	0,39	105
1212	22	≤ 5000	2760 (V _{f tot} 41V)	113,2	0,30	105
1216	22	≤ 5000	3680 (V _{f tot} 41V)	150,9	0,40	105
1216	23	≤ 5000	3680 (V _{f tot} 41V)	150,9	0,36	105
1812	22	≤ 5700	2760 (V _{f tot} 55V)	151,8	0,39	105
1818	22	≤ 5700	4140 (V _{f tot} 55V)	227,7	0,588	105

Additional information (if necessary)



☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2025-03-03

Original Issue Date: 2024-01-31

Signature:



Thomas Wilson

Additional Ratings:

Type / model	Rated current max(mA)	Risk Group 1 Current (mA)
Fortimo SLM C 940 (d) (m) L23 2828 G(i) (a) (m=1319)	2000mA	≤1650mA
Fortimo SLM C 940 (d) (m) L15 2024 G(i) (a) (m=1309)	1000mA	≤734mA

CoB Type (Gen8 HE)											
CoB Type (Die matrix)	1201	1202	1203	1204	1205	1206	1208	1210	1211	1212	1216
Maximum currents for RG1 [mA]	zcc=840	163	325	488	650	813	975	1300	1625	1788	2600
	zcc=940	168	335	503	670	838	1005	1340	1675	1843	2680
	zcc=850	120	240	360	480	600	720	960	1200	1320	1440
	zcc=950	120	240	360	480	600	720	960	1200	1320	1440

CoB Type (Gen8)											
CoB Type (Die matrix)	1201	1202	1203	1204	1205	1206	1208	1210	1211	1212	1216
Maximum currents for RG1 [mA]	zcc=757	125	250	375	500	625	750	1000	1250	1375	2000
	zcc=857	125	250	375	500	625	750	1000	1250	1375	2000
	zcc=940	125	250	375	500	625	750	1000	1250	1375	2000

CoB Type (Gen8) con't			
CoB Type (Die matrix)	1812	1818	
Maximum currents for RG1 [mA]	zcc=757	1500	2250
	zcc=857	1500	2250
	zcc=940	1500	2250

Additional information (if necessary)




☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2025-03-03
 Original Issue Date: 2024-01-31

Signature:



Thomas Wilson



Ref. Certif. No.

DK-149987-M2-UL

Additionally evaluated to:

EN IEC 62031:2020, EN IEC 62031:2020/A11:2021

Summary of Modifications:

- Add G8 non-HE models (lower power density than original models);
 - Update Annex 2.;
 - Add marking plate.;
 - Update product key and ratings;
- See test report for details

Additional information (if necessary)



- ☐ UL Solutions (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- ☒ UL Solutions (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- ☐ UL Solutions (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- ☐ UL Solutions (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2025-03-03

Original Issue Date: 2024-01-31

Signature:

Thomas Wilson