

# ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025 / ISO 21930

**Aluroad Gen 2 mini**  
**BGP020 LED46/740 DN10 SRG10 42/60**  
Signify N.V.



## GENERAL INFORMATION

### MANUFACTURER

Manufacturer	Signify N.V.
Address	High Tech Campus 48, 5656 AE Eindhoven, The Netherlands
Contact details	sustainability@signify.com
Website	<a href="https://www.signify.com/global">https://www.signify.com/global</a>

### EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804+A2:2019 and ISO 14025
PCR	EPD Hub Core PCR version 1.0, 1 Feb 2022
Sector	Electrical product
Category of EPD	Pre-verified EPD
Scope of the EPD	Cradle to gate with options, A4-B7, and modules C1-C4, D
EPD author	Sustainability Signify
EPD verification	Independent verification of this EPD and data, according to ISO 14025: <input checked="" type="checkbox"/> Internal certification <input type="checkbox"/> External verification

The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of lighting products may not be comparable if they do not comply with EN 15804 and if they are not compared in a lighting context.

### PRODUCT

Product name	Aluroad Gen 2 mini
Additional labels	BGP020 LED46/740 DN10 SRG10 42/60
Product reference	910925869631
Place of production	Kętrzyn, Poland
Period for data	2022
Averaging in EPD	No averaging
Variation in GWP-fossil for A1-A3	%

### ENVIRONMENTAL DATA SUMMARY

Declared unit	1 Unit of 4048 lumens over 100000 hours
Declared unit mass	5.345 kg
GWP-fossil, A1-A3 (kgCO <sub>2</sub> e)	7.77E+01
GWP-total, A1-A3 (kgCO <sub>2</sub> e)	7.74E+01
Secondary material, inputs (%)	22.2
Secondary material, outputs (%)	58.0
Total energy use, A1-A3 (kWh)	268.0
Total water use, A1-A3 (m <sup>3</sup> e)	5.38E-01

## PRODUCT AND MANUFACTURER

### ABOUT THE MANUFACTURER

Signify is the world leader in lighting for professionals, consumers and lighting for the Internet of Things. Our energy efficient lighting products, systems and services enable our customers to enjoy a superior quality of light, and make people's lives safer and more comfortable, businesses more productive and cities more liveable.

For more information, please visit: <https://www.signify.com/global>

### PRODUCT DESCRIPTION

BGP020, BGP021, BGP025, BGP026 AluRoad gen2 Simply Performant: The AluRoad gen2 family is available in two sizes, BGP020 mini, BGP025 medium and two sizes with adjustable spigot BGP021 mini, BGP026 AluRoad gen2 enables you to enjoy the benefits of LED technology, designated to further minimize Total Cost of Investment and Ownership. The family is ideally suited for both new build areas and streets as well as renovation of existing installations. This affordable family not only offers a clean and timeless design to blend in with the environment, but also brings high quality lighting solutions with significant energy and maintenance savings over a long operational life. Benefits: Easy to install in both post top and side entry application. Interesting total cost of ownership. Limited initial investment. Considerable reduction in energy usage and carbon footprint; further energy savings achievable when using CLO or stand alone dimming such as Dynadim. Signify Service tag (unique QR identification) for maintenance, installation and spare part information.

### PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	63	China
Minerals	26	China
Fossil materials	11	China
Bio-based materials	0	Not applicable

### BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	0.107

### FUNCTIONAL UNIT AND SERVICE LIFE

Declared unit	1 Product
Mass per declared unit	3.287 kg
Functional unit	4048 lumens over 100000 hours
Reference service life	100000 hours

### SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

# PRODUCT LIFE-CYCLE

## SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Assembly stage		Use stage							End of life stage				Beyond the system boundaries			
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D			
x	x	x	x	x	MNR	MNR	MNR	MNR	MNR	x	MNR	MNR	x	x	x				x
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demol.	Transport	Waste processing	Disposal	Reuse	Recovery	Recycling	

Modules not relevant = MNR.

## MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production as well as packaging materials and other ancillary materials. Also, electricity, and waste formed in the production processes at Signify’s manufacturing facilities are included in this stage.

The product is made of metals, plastics, and electronic components. All components are transported to Signify’s production facility, where the main manufacturing processes primarily are associated with assembly. The finished product is packaged with polyethylene, cardboard, and/or paper as packaging material before being sent to customers. Manufacturing loss, ancillaries and wastes are calculated according to the data that each manufacturing site is sharing with Signify. The total annual amount of waste in kg is allocated to the total annual production in kg at the specific manufacturing site responsible for the production of the studied luminaire.

Thus, it is possible to allocate it according to the weight of the product analysed in this study. Some of the wastes are due to ancillary materials used during manufacturing while the rest is due to material losses.

## TRANSPORT AND INSTALLATION (A4-A5)

Transport distances were calculated on the base of the supplier location and manufacturing location and then made a cumulative group choosing the conservative scenario. Environmental impacts from installation include waste packaging materials (A5). The impacts of energy consumption and the used ancillary materials during installation are considered negligible.


## PRODUCT USE AND MAINTENANCE (B1-B7)

During the use phase, the product consumes electricity from Europe’s electricity grid mix (B6). The total power consumption of the reference product is calculated as follows: Wattage x Reference lifetime = kWh consumed throughout the entire use phase B6.

## PRODUCT END OF LIFE (C1-C4, D)

Consumption of energy and natural resources in demolition process is assumed to be negligible. It is assumed that the waste is collected separately and transported to the waste treatment centre. Transportation distance to treatment is assumed as 150 km and the transportation method is assumed to be lorry (C2). According to EN 50693:2019, the sequence of treatment operations occurring to the product shall include de-pollution, fractions separation and preparation (dismantling, crushing, shredding, sorting), recycling, other material recovery, energy recovery and disposal. In this study, the default values from table G.4 of EN 50693 is used for treating materials in different waste treatment methods. Due to the material and energy recovery potential of parts in the lighting system, the end-of-life product is converted into recycled raw materials, while the energy recovered from incineration displaces electricity and heat production (D). The benefits and loads of incineration and recycling are included in Module D.

# SYSTEM BOUNDARY



## LIFE-CYCLE ASSESSMENT

### CUT-OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. The study includes all major raw material and energy consumption. All inputs and outputs of the unit processes, for which data is available for, are included in the calculation. There is no neglected unit process more than 1% of total mass or energy flows. The module specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

### ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, ancillary materials, energy & water consumption, material loss and waste generation at the manufacturing site are attributed to the bill of materials of the products, therefore, they are allocated by partitioning the quantities on the base of the total production in kg throughout the year. Thus, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	No allocation
Ancillary materials	Allocated by mass or volume
Manufacturing energy and waste	Allocated by mass or volume

This EPD is created with a most conservative scenario in A1-A3 in terms of material composition.

### AVERAGES AND VARIABILITY

Type of average	No averaging
Averaging method	Not applicable
Variation in GWP-fossil for A1-A3	Not applicable

This EPD is product and factory specific and does not contain average calculations. It is created with a most conservative scenario in A1-A3 in terms of material composition.

### LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA EPD Generator. The LCA and EPD have been prepared according to the reference standards and ISO 14040/14044. EcoInvent 3.8 database was used as the source of environmental data.

## ENVIRONMENTAL IMPACT DATA

### CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total <sup>1)</sup>	kg CO <sub>2</sub> e	7.61E+01	1.06E+00	1.93E-01	7.74E+01	1.06E+00	4.00E-01	MNR	MNR	MNR	MNR	MNR	5.64E+02	MNR	MNR	1.08E-01	2.80E+00	1.60E+00	-3.08E+01
GWP – fossil	kg CO <sub>2</sub> e	7.61E+01	1.06E+00	5.83E-01	7.77E+01	1.06E+00	7.15E-03	MNR	MNR	MNR	MNR	MNR	5.63E+02	MNR	MNR	1.08E-01	2.80E+00	1.60E+00	-3.07E+01
GWP – biogenic	kg CO <sub>2</sub> e	1.99E-02	0.00E+00	-3.93E-01	-3.73E-01	4.10E-04	3.93E-01	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	-1.46E-02
GWP – LULUC	kg CO <sub>2</sub> e	5.85E-02	7.76E-04	2.74E-03	6.20E-02	3.91E-04	7.15E-06	MNR	MNR	MNR	MNR	MNR	1.32E+00	MNR	MNR	3.99E-05	9.86E-05	1.08E-04	-7.36E-03
Ozone depletion pot.	kg CFC <sub>11</sub> e	5.19E-06	2.11E-07	7.05E-08	5.47E-06	2.44E-07	7.86E-10	MNR	MNR	MNR	MNR	MNR	2.86E-05	MNR	MNR	2.49E-08	1.08E-08	1.62E-08	-8.21E-07
Acidification potential	mol H <sup>+</sup> e	6.69E-01	3.46E-02	2.48E-03	7.06E-01	4.49E-03	5.04E-05	MNR	MNR	MNR	MNR	MNR	3.22E+00	MNR	MNR	4.58E-04	1.14E-03	8.96E-04	-3.04E-01
EP-freshwater <sup>2)</sup>	kg Pe	4.73E-03	3.79E-06	2.40E-05	4.76E-03	8.68E-06	2.04E-07	MNR	MNR	MNR	MNR	MNR	5.97E-02	MNR	MNR	8.85E-07	2.98E-06	1.24E-05	-1.86E-03
EP-marine	kg Ne	8.16E-02	8.50E-03	9.38E-04	9.10E-02	1.33E-03	1.98E-04	MNR	MNR	MNR	MNR	MNR	4.27E-01	MNR	MNR	1.36E-04	4.01E-04	3.03E-03	-3.35E-02
EP-terrestrial	mol Ne	9.06E-01	9.45E-02	6.54E-03	1.01E+00	1.47E-02	1.19E-04	MNR	MNR	MNR	MNR	MNR	4.85E+00	MNR	MNR	1.50E-03	4.25E-03	3.22E-03	-3.86E-01
POCP (“smog”) <sup>3)</sup>	kg NMVOCe	2.92E-01	2.45E-02	2.24E-03	3.19E-01	4.71E-03	9.30E-05	MNR	MNR	MNR	MNR	MNR	1.33E+00	MNR	MNR	4.80E-04	1.07E-03	1.33E-03	-1.11E-01
ADP-minerals & metals <sup>4)</sup>	kg Sbe	2.53E-03	1.47E-06	2.92E-06	2.54E-03	2.49E-06	6.86E-08	MNR	MNR	MNR	MNR	MNR	5.26E-03	MNR	MNR	2.53E-07	4.67E-06	3.61E-07	-6.02E-04
ADP-fossil resources	MJ	9.62E+02	1.33E+01	9.19E+00	9.85E+02	1.59E+01	8.66E-02	MNR	MNR	MNR	MNR	MNR	1.20E+04	MNR	MNR	1.62E+00	1.13E+00	1.48E+00	-3.05E+02
Water use <sup>5)</sup>	m <sup>3</sup> e depr.	2.17E+01	3.96E-02	3.00E-01	2.20E+01	7.13E-02	1.20E-03	MNR	MNR	MNR	MNR	MNR	3.28E+02	MNR	MNR	7.26E-03	1.20E-01	8.28E-02	-2.56E+00

1) GWP = Global Warming Potential; 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO<sub>4</sub>e; 3) POCP = Photochemical ozone formation; 4) ADP = Abiotic depletion potential; 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

### ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, PEF

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	4.50E-06	3.31E-08	4.04E-08	4.57E-06	1.22E-07	1.83E-09	MNR	MNR	MNR	MNR	MNR	1.06E-05	MNR	MNR	1.25E-08	9.67E-09	1.05E-08	-1.88E-06
Ionizing radiation <sup>6)</sup>	kBq U235e	5.11E+00	6.14E-02	2.57E-02	5.19E+00	7.59E-02	5.38E-04	MNR	MNR	MNR	MNR	MNR	3.24E+02	MNR	MNR	7.73E-03	5.97E-03	7.86E-03	-1.92E+00

Ecotoxicity (freshwater)	CTUe	2.85E+03	8.45E+00	1.72E+01	2.88E+03	1.43E+01	1.33E+00	MNR	MNR	MNR	MNR	MNR	8.15E+03	MNR	MNR	1.46E+00	8.26E+00	1.91E+02	-7.09E+02
Human toxicity, cancer	CTUh	9.61E-08	6.38E-10	3.45E-10	9.71E-08	3.52E-10	1.77E-11	MNR	MNR	MNR	MNR	MNR	2.67E-07	MNR	MNR	3.59E-11	3.16E-10	6.73E-10	-3.40E-09
Human tox. non-cancer	CTUh	2.18E-06	5.41E-09	6.54E-09	2.19E-06	1.42E-08	5.18E-10	MNR	MNR	MNR	MNR	MNR	8.77E-06	MNR	MNR	1.45E-09	1.24E-08	3.95E-08	-8.00E-07
SQP <sup>7)</sup>	-	2.44E+02	1.83E+00	1.55E+01	2.61E+02	1.84E+01	1.08E-01	MNR	MNR	MNR	MNR	MNR	2.17E+03	MNR	MNR	1.87E+00	1.16E+00	2.32E+00	-7.32E+01

6) EN 15804+A2 disclaimer for Ionizing radiation, human health. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator; 7) SQP = Land use related impacts/soil quality.

### USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy <sup>8)</sup>	MJ	4.57E+01	9.16E-02	5.12E+00	5.09E+01	1.79E-01	5.24E-03	MNR	MNR	MNR	MNR	MNR	2.44E+03	MNR	MNR	1.83E-02	1.08E-01	5.93E-02	-1.03E+01
Renew. PER as material	MJ	8.72E-03	0.00E+00	3.49E+00	3.50E+00	0.00E+00	-3.49E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	-8.72E-03	0.00E+00
Total use of renew. PER	MJ	4.57E+01	9.16E-02	8.61E+00	5.44E+01	1.79E-01	-3.49E+00	MNR	MNR	MNR	MNR	MNR	2.44E+03	MNR	MNR	1.83E-02	1.08E-01	5.06E-02	-1.03E+01
Non-re. PER as energy	MJ	8.93E+02	1.33E+01	7.62E+00	9.14E+02	1.59E+01	8.66E-02	MNR	MNR	MNR	MNR	MNR	1.20E+04	MNR	MNR	1.62E+00	1.13E+00	1.48E+00	-3.05E+02
Non-re. PER as material	MJ	6.81E+01	0.00E+00	1.45E+00	6.96E+01	0.00E+00	-1.45E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	-3.32E+01	-3.32E+01	0.00E+00
Total use of non-re. PER	MJ	9.61E+02	1.33E+01	9.08E+00	9.84E+02	1.59E+01	-1.37E+00	MNR	MNR	MNR	MNR	MNR	1.20E+04	MNR	MNR	1.62E+00	-3.20E+01	-3.17E+01	-3.05E+02
Secondary materials	kg	1.18E+00	6.11E-03	2.43E-01	1.43E+00	4.42E-03	1.00E-04	MNR	MNR	MNR	MNR	MNR	1.23E+00	MNR	MNR	4.51E-04	9.77E-04	1.64E-03	1.06E+00
Renew. secondary fuels	MJ	2.05E-02	1.63E-05	1.83E-02	3.88E-02	4.46E-05	7.69E-07	MNR	MNR	MNR	MNR	MNR	1.00E-02	MNR	MNR	4.55E-06	4.66E-05	2.50E-05	-2.42E-03
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m <sup>3</sup>	5.30E-01	8.51E-04	7.19E-03	5.38E-01	2.06E-03	5.57E-05	MNR	MNR	MNR	MNR	MNR	1.03E+01	MNR	MNR	2.10E-04	4.38E-03	2.97E-03	-1.05E-01

8) PER = Primary energy resources.

### END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	1.13E+01	1.82E-02	2.94E-02	1.14E+01	2.11E-02	4.44E-04	MNR	MNR	MNR	MNR	MNR	4.30E+01	MNR	MNR	2.15E-03	4.52E-03	2.02E-02	-4.43E+00
Non-hazardous waste	kg	1.89E+02	1.48E-01	5.82E-01	1.90E+02	3.47E-01	1.02E-01	MNR	MNR	MNR	MNR	MNR	2.72E+03	MNR	MNR	3.54E-02	1.33E+00	4.35E+00	-8.71E+01
Radioactive waste	kg	2.15E-03	9.45E-05	1.32E-05	2.26E-03	1.07E-04	2.18E-07	MNR	MNR	MNR	MNR	MNR	8.73E-02	MNR	MNR	1.09E-05	2.58E-06	0.00E+00	-6.84E-04

### END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for re-use	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	1.95E+00	0.00E+00	0.00E+00
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	2.66E-01	2.66E-01	0.00E+00	0.00E+00	MNR	MNR	MNR	MNR	MNR	0.00E+00	MNR	MNR	0.00E+00	2.54E+01	0.00E+00	0.00E+00

### ENVIRONMENTAL IMPACTS – EN 15804+A1, CML / ISO 21930

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO <sub>2</sub> e	7.44E+01	1.06E+00	5.90E-01	7.60E+01	1.05E+00	1.69E-01	MNR	MNR	MNR	MNR	MNR	5.58E+02	MNR	MNR	1.07E-01	2.79E+00	2.79E+00	-3.01E+01
Ozone depletion Pot.	kg CFC <sub>11</sub> e	4.70E-06	1.67E-07	6.01E-08	4.93E-06	1.93E-07	6.34E-10	MNR	MNR	MNR	MNR	MNR	2.48E-05	MNR	MNR	1.97E-08	9.27E-09	1.32E-08	-6.95E-07
Acidification	kg SO <sub>2</sub> e	5.73E-01	2.76E-02	1.89E-03	6.03E-01	3.49E-03	4.07E-05	MNR	MNR	MNR	MNR	MNR	2.73E+00	MNR	MNR	3.56E-04	8.57E-04	6.82E-04	-2.62E-01
Eutrophication	kg PO <sub>4</sub> <sup>3</sup> e	2.14E-01	3.08E-03	1.09E-03	2.19E-01	7.95E-04	4.21E-04	MNR	MNR	MNR	MNR	MNR	2.10E+00	MNR	MNR	8.10E-05	4.60E-04	1.11E-02	-7.27E-02
POCP (“smog”)	kg C <sub>2</sub> H <sub>4</sub> e	3.71E-02	7.11E-04	1.85E-04	3.80E-02	1.36E-04	3.79E-05	MNR	MNR	MNR	MNR	MNR	1.12E-01	MNR	MNR	1.39E-05	2.54E-05	3.12E-04	-1.27E-02
ADP-elements	kg Sbe	2.49E-03	1.44E-06	2.65E-06	2.49E-03	2.41E-06	6.80E-08	MNR	MNR	MNR	MNR	MNR	5.25E-03	MNR	MNR	2.45E-07	4.61E-06	3.26E-07	-5.99E-04
ADP-fossil	MJ	9.61E+02	1.33E+01	9.16E+00	9.83E+02	1.59E+01	8.66E-02	MNR	MNR	MNR	MNR	MNR	1.20E+04	MNR	MNR	1.62E+00	1.13E+00	1.48E+00	-3.05E+02

## APPENDIX (EPD HUB ALIGNED)

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management scenarios and power inputs of the luminaires within the same product family

To calculate the Scaled Impact (*SI*), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions  $P_{in}$  and the power input of the base variant  $P_{base}$ .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system). The presented controls factors values in Table A1 are based on BS EN 15193-1:2017. Please refer to this publication or contact Signify directly for more information.

$$TSF = PSF * CSF$$

**Table A1: Light management function (PEP EcoPassport aligned)**

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55



3. Lastly, the GWP of the base variant is then scaled by the TSF.

$$\text{Scaled Impact} = \text{GWP}_{\text{case}} * \text{TSF}$$

Table A2 Scaled GWP per scaling factor (EPD Hub aligned)

PFC	Lamp Name	CCT (K)	Flux [lm]	Power [W]	Efficacy [lm/W]	Efficacy [lm/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
								NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
BGP 020	LED20	3000	1800.00	12.40	145.16	122.00	5.58	5.58	4.19	4.19	3.07	3148.9	2361.7	2361.7	1731.9
	LED20	4000	1800.00	11.80	152.54	126.00	5.87	5.87	4.40	4.40	3.23	3309.0	2481.7	2481.7	1819.9
	LED24	3000	2136.00	14.80	144.32	122.00	5.55	5.55	4.16	4.16	3.05	3130.7	2348.0	2348.0	1721.9
	LED24	4000	2136.00	14.00	152.57	129.00	5.87	5.87	4.40	4.40	3.23	3309.6	2482.2	2482.2	1820.3
	LED27	3000	2403.00	16.40	146.52	123.00	5.64	5.64	4.23	4.23	3.10	3178.5	2383.8	2383.8	1748.1
	LED27	4000	2403.00	15.60	154.04	128.00	5.92	5.92	4.44	4.44	3.26	3341.4	2506.1	2506.1	1837.8
	LED30	3000	2670.00	18.00	148.33	123.00	5.71	5.71	4.28	4.28	3.14	3217.7	2413.3	2413.3	1769.7
	LED30	4000	2670.00	17.20	155.23	131.00	5.97	5.97	4.48	4.48	3.28	3367.4	2525.5	2525.5	1852.0
	LED32	3000	2848.00	19.20	148.33	108.00	5.71	5.71	4.28	4.28	3.14	3217.7	2413.3	2413.3	1769.7
	LED32	4000	2848.00	18.20	156.48	112.00	6.02	6.02	4.51	4.51	3.31	3394.5	2545.9	2545.9	1867.0
	LED34	3000	3026.00	20.50	147.61	108.00	5.68	5.68	4.26	4.26	3.12	3202.0	2401.5	2401.5	1761.1
	LED34	4000	3026.00	19.40	155.98	115.00	6.00	6.00	4.50	4.50	3.30	3383.6	2537.7	2537.7	1861.0
	LED35	3000	3115.00	20.50	151.95	128.00	5.84	5.84	4.38	4.38	3.21	3296.2	2472.1	2472.1	1812.9
	LED35	4000	3115.00	19.60	158.93	135.00	6.11	6.11	4.58	4.58	3.36	3447.5	2585.6	2585.6	1896.1
	LED40	3000	3560.00	23.00	154.78	122.00	5.95	5.95	4.46	4.46	3.27	3357.6	2518.2	2518.2	1846.7
	LED40	4000	3560.00	22.00	161.82	131.00	6.22	6.22	4.67	4.67	3.42	3510.2	2632.7	2632.7	1930.6
	LED45	3000	3960.00	26.00	152.31	128.00	5.86	5.86	4.39	4.39	3.22	3303.9	2477.9	2477.9	1817.1
	LED45	4000	3960.00	25.00	158.40	135.00	6.09	6.09	4.57	4.57	3.35	3436.1	2577.0	2577.0	1889.8
	LED46	3000	4048.00	27.00	149.93	122.00	5.77	5.77	4.32	4.32	3.17	3252.2	2439.2	2439.2	1788.7
	LED46	4000	4048.00	25.50	158.75	131.00	6.11	6.11	4.58	4.58	3.36	3443.5	2582.7	2582.7	1894.0
LED50	3000	4400.00	29.00	151.72	122.00	5.84	5.84	4.38	4.38	3.21	3291.2	2468.4	2468.4	1810.2	
LED50	4000	4400.00	28.00	157.14	129.00	6.04	6.04	4.53	4.53	3.32	3408.8	2556.6	2556.6	1874.8	
LED51	3000	4400.00	29.50	149.15	116.00	5.74	5.74	4.30	4.30	3.16	3235.5	2426.6	2426.6	1779.5	
LED51	4000	4400.00	28.00	157.14	125.00	6.04	6.04	4.53	4.53	3.32	3408.8	2556.6	2556.6	1874.8	
LED56	3000	4872.00	32.50	149.91	112.00	5.77	5.77	4.32	4.32	3.17	3251.8	2438.9	2438.9	1788.5	
LED56	4000	4928.00	31.00	158.97	118.00	6.11	6.11	4.59	4.59	3.36	3448.4	2586.3	2586.3	1896.6	
LED60	3000	5220.00	35.00	149.14	106.00	5.74	5.74	4.30	4.30	3.15	3235.3	2426.4	2426.4	1779.4	
LED60	4000	5280.00	33.50	157.61	113.00	6.06	6.06	4.55	4.55	3.33	3419.0	2564.2	2564.2	1880.4	
LED65	3000	5568.00	38.50	144.62	123.00	5.56	5.56	4.17	4.17	3.06	3137.2	2352.9	2352.9	1725.5	



LED65	4000	5568.00	36.50	152.55	130.00	5.87	5.87	4.40	4.40	3.23	3309.1	2481.8	2481.8	1820.0
LED69	3000	5916.00	41.00	144.29	119.00	5.55	5.55	4.16	4.16	3.05	3130.0	2347.5	2347.5	1721.5
LED69	4000	5916.00	39.00	151.69	127.00	5.83	5.83	4.38	4.38	3.21	3290.6	2467.9	2467.9	1809.8
LED70	3000	6020.00	41.50	145.06	123.00	5.58	5.58	4.18	4.18	3.07	3146.7	2360.0	2360.0	1730.7
LED70	4000	6090.00	39.50	154.18	130.00	5.93	5.93	4.45	4.45	3.26	3344.5	2508.3	2508.3	1839.5

\* Note that if the product is non-dimmable, only the values for "NC (No Control)" are valid; if the driver type is PSU, only the values for "NC (No Control)" and "PS (presence sensing)" for are valid.

## APPENDIX (PEP ECOPASSPORT ALIGNED)

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management functions, the lumen output ( $O_{lum}$ ) and reference service life (RSL) of each product within the same product family.

To calculate the Scaled Impact ( $SI_{pep}$ ), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions  $P_{in}$  and the power input of the base variant  $P_{base}$ .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Using this scaled GWP, we then can apply the PEP Ecopassport method for calculating the environmental impact of the functional unit for a luminary (1000 lumens over 35000 hours), applied to B6, where the Functional Unit application considers the lumen output ( $O_{lum}$ ) and reference service lifetime (RSL) of the product to estimate the final environmental impact. The scaled impact ( $SI_{pep}$ ) is presented in Table A4.

$$GSF = \frac{FU_{pep}}{FU_p} = \frac{1,000}{O_{lum}} * \frac{35,000}{RSL}$$

3. Calculate the GWP scaling factor (PGSF), by multiplying the PSF by the GSF.

$$PGSF = PSF * GSF$$

4. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system), as presented in Table A1.

$$TSF = PGSF * CSF$$

**Table A3: Light management functions (PEP EcoPassport aligned)**

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

5. Lastly, the GWP of the base variant is then scaled by the TSF.

$$\text{Scaled GWP} = \text{GWP}_{\text{case}} * \text{TSF}$$

As described in the EPD, calculations are made based on dataset describing electricity available on the low voltage level in Europe for year 2022 (source Ecoinvent 3.8 database). This value should be adjusted depending on specific project requirements. Presented controls factors and functional unit conversion values are based on the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). Please refer to this publication or contact Signify directly for more information.

**Table A2 Scaled GWP per scaling factor (PEP EcoPassport aligned)**

PFC	Lamp Name	CCT (K)	Flux [lm]	Power [W]	Efficacy [lm/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
							NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
BGP 020	LED20	3000	1800	12	145.2	0.48	0.48	0.36	0.36	0.26	104.6	78.5	78.5	57.5
	LED20	4000	1800	12	152.5	0.45	0.45	0.34	0.34	0.25	99.5	74.7	74.7	54.7
	LED24	3000	2136	15	144.3	0.57	0.57	0.43	0.43	0.31	105.2	78.9	78.9	57.9
	LED24	4000	2136	14	152.6	0.54	0.54	0.40	0.40	0.30	99.5	74.6	74.6	54.7
	LED27	3000	2403	16	146.5	0.63	0.63	0.47	0.47	0.35	103.6	77.7	77.7	57.0
	LED27	4000	2403	16	154.0	0.60	0.60	0.45	0.45	0.33	98.6	73.9	73.9	54.2

LED30	3000	2670	18	148.3	0.69	0.69	0.52	0.52	0.38	102.4	76.8	76.8	56.3
LED30	4000	2670	17	155.2	0.66	0.66	0.50	0.50	0.36	97.8	73.4	73.4	53.8
LED32	3000	2848	19	148.3	0.74	0.74	0.55	0.55	0.41	102.4	76.8	76.8	56.3
LED32	4000	2848	18	156.5	0.70	0.70	0.53	0.53	0.39	97.0	72.8	72.8	53.4
LED34	3000	3026	21	147.6	0.79	0.79	0.59	0.59	0.43	102.9	77.2	77.2	56.6
LED34	4000	3026	19	156.0	0.75	0.75	0.56	0.56	0.41	97.4	73.0	73.0	53.5
LED35	3000	3115	21	152.0	0.79	0.79	0.59	0.59	0.43	99.9	74.9	74.9	55.0
LED35	4000	3115	20	158.9	0.75	0.75	0.57	0.57	0.41	95.5	71.7	71.7	52.5
LED40	3000	3560	23	154.8	0.88	0.88	0.66	0.66	0.49	98.1	73.6	73.6	54.0
LED40	4000	3560	22	161.8	0.85	0.85	0.63	0.63	0.47	93.8	70.4	70.4	51.6
LED45	3000	3960	26	152.3	1.00	1.00	0.75	0.75	0.55	99.7	74.8	74.8	54.8
LED45	4000	3960	25	158.4	0.96	0.96	0.72	0.72	0.53	95.9	71.9	71.9	52.7
LED46	3000	4048	27	149.9	1.04	1.04	0.78	0.78	0.57	101.3	76.0	76.0	55.7
LED46	4000	4048	26	158.7	0.98	0.98	0.74	0.74	0.54	95.7	71.7	71.7	52.6
LED50	3000	4400	29	151.7	1.12	1.12	0.84	0.84	0.61	100.1	75.1	75.1	55.0
LED50	4000	4400	28	157.1	1.08	1.08	0.81	0.81	0.59	96.6	72.5	72.5	53.1
LED51	3000	4400	30	149.2	1.13	1.13	0.85	0.85	0.62	101.8	76.4	76.4	56.0
LED51	4000	4400	28	157.1	1.08	1.08	0.81	0.81	0.59	96.6	72.5	72.5	53.1
LED56	3000	4872	33	149.9	1.25	1.25	0.94	0.94	0.69	101.3	76.0	76.0	55.7
LED56	4000	4928	31	159.0	1.19	1.19	0.89	0.89	0.66	95.5	71.6	71.6	52.5
LED60	3000	5220	35	149.1	1.35	1.35	1.01	1.01	0.74	101.8	76.4	76.4	56.0
LED60	4000	5280	34	157.6	1.29	1.29	0.97	0.97	0.71	96.3	72.3	72.3	53.0
LED65	3000	5568	39	144.6	1.48	1.48	1.11	1.11	0.81	105.0	78.7	78.7	57.7
LED65	4000	5568	37	152.5	1.40	1.40	1.05	1.05	0.77	99.5	74.7	74.7	54.7
LED69	3000	5916	41	144.3	1.58	1.58	1.18	1.18	0.87	105.2	78.9	78.9	57.9
LED69	4000	5916	39	151.7	1.50	1.50	1.13	1.13	0.83	100.1	75.1	75.1	55.1
LED70	3000	6020	42	145.1	1.60	1.60	1.20	1.20	0.88	104.7	78.5	78.5	57.6
LED70	4000	6090	40	154.2	1.52	1.52	1.14	1.14	0.84	98.5	73.9	73.9	54.2

\* Note that if the product is non-dimmable, only the values for "NC (No Control)" are valid; if the driver type is PSU, only the values for "NC (No Control)" and "PS (presence sensing)" for are valid.

