



ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

TownTune Asymmetric-BDP265

Signify N.V.



EPD HUB, HUB-5294

Published on 06.02.2026, last updated on 06.02.2026, valid until 06.02.2031

MANUFACTURER AND SITE

Manufacturer	Signify N.V.
Address	High Tech Campus 48, 5656 AE Eindhoven, The Netherlands
Contact details	sustainability@signify.com
Website	https://www.signify.com/global
Place of production	VALLADOLID, SPAIN
Place(s) of raw material origin	APAC, EU
Place(s) of installation and use	EU
Period for data	Calendar Year 2023

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR version 1.2, 24 Mar 2025
Sector	Electrical product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle to gate with options, A4-A5, B6, and modules C1-C4, D
EPD author	Signify / Sustainability
EPD verification	Independent verification of this EPD and data, according to ISO 14025: <input type="checkbox"/> Internal verification <input checked="" type="checkbox"/> External verification
EPD verifier	Imane Uald Lamkaddam as an authorized verifier for EPD Hub

PRODUCT SPECIFICATION

Product name	TownTune Asymmetric-BDP265
Product number / reference	912300024197 / BDP265 LED40-4S/830 DM50 DDF3 48-4S/60A
GTIN (Global Trade Item Number)	Not applicable
NOBB (Norwegian Building Product Database)	Not applicable
A1-A3 Specific data (%)	3.18

PRODUCT DESCRIPTION

Designed to enhance existing and scalable urban spaces, the TownTune family offers all the latest lighting innovations in terms of performance, quality of light and connectivity. The family consists of four solutions: a Central Post Top (CPT), an Asymmetric Spigot Post Top / Side Entry version (ASY), a version with an extending Lyre post top bracket (Lyre), and a Central Post Top with a Conical Comfort Bowl (CCB). Each TownTune luminaire can be customized with a choice of different shapes on top of the housing, plus there's the option to add a decorative ring, which comes in two colors (excluding CCB). Design options that enable you to create your very own lighting signature and bring a distinctive identity to districts and cities. In addition, every luminaire in the TownTune family is uniquely identifiable, thanks to the Signify Service tag app. By simply scanning a QR code, placed inside the door of the mast or directly on the luminaire, you can instantly access the configuration of the luminaire. This makes maintenance and programming operations faster and easier and enables you to create your digital library of lighting assets and spare parts. TownTune also uses the Philips LEDGINE-O lighting platform, ensuring you always have the right amount and direction of light on your street. Furthermore, thanks to being system ready (SR), TownTune is also future proof. A solution that's ready to be paired with both standalone and advanced control and lighting software applications such as Interact City.

This EPD is intended for business-to-business and/or business-to-consumer communication. Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterization factors EF 3.1. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT CLASSIFICATION

Declared operating voltage, Volt	220 to 240 V
Light source colour temperature, Kelvin	3000K
Protection index for water and dust (IP)	66
Impact resistance index (IK)	10
Luminous flux, Lumens	3240
Electrical power, Watt	28.5
Luminous efficiency, Lm/W	114
Additional characteristic	Not applicable

ABOUT THE MANUFACTURER

Signify is the world leader in lighting for professionals, consumers and lighting for the Internet of Things. Our energy efficient lighting products, systems and services enable our customers to enjoy a superior quality of light, and make people’s lives safer and more comfortable, businesses more productive and cities more liveable.

For more information, please visit: <https://www.signify.com/global>

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	76.69	APAC , EU
Minerals	0	
Fossil materials	23.31	APAC , EU
Bio-based materials	0	

BIOGENIC CARBON CONTENT

Product’s biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	0.432

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 unit
Declared unit mass, kg	6.284
Mass of packaging, kg	1.105
Functional unit (from PEP PSR0014)	Provide lighting that delivers an outgoing artificial luminous flux of 1000 lumens during a reference lifetime of 35000 hours
Reference service life (years)	25
Assigned lifetime (hours)	100000
GWP-total, A1-A3 (kg CO ₂ e)	55.9
GWP-fossil, A1-A3 (kg CO ₂ e)	57
Secondary material, inputs (%)	54.1
Secondary material, outputs (%)	53.8
Total energy use, A1-A3 (kWh)	200
Net freshwater use, A1-A3 (m ³)	2.47E-01

LIFE CYCLE ASSESSMENT

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Installation stage		Use stage							End of life stage				Beyond the system
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	ND	ND	ND	X	ND	X	X	X	X	X
Raw materials	Transport	Manufacturing	Transport	Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demo.	Transport	Waste processing	Disposal	Reuse, Recovery, Recycling

Modules not declared = ND.

CUT - OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. There is no neglected unit process more than 1% of total mass or energy flows. The module-specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

VALIDATION OF DATA

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product’s manufacturing stage. The analysis was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterization factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, ancillary materials, energy & water consumption, material loss and waste generation at the manufacturing site are attributed to the bill of materials of the products, therefore, they are allocated by partitioning the quantities on the base of the total production in kg throughout the year. Thus, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	No allocation
Ancillary materials	Allocated by mass
Manufacturing energy and waste	Allocated by mass

Proxy data is used for certain materials due to their unavailability in the database. Conservative choices have been adopted when exact information was missing. Regarding module C1-C4: EOL scenarios are based on default values from EN 50693. For stages description please refer to section Product life cycle in this EPD report.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA Luminaire EPD Generator v2.2.7. The LCA and EPD have been prepared according to the reference standards, EN 50693, and ISO 14040/14044. Ecoinvent v 3.10.1 and One Click LCA databases were used as sources of environmental data. Allocation used in Ecoinvent 3.10.1 environmental data sources follow the methodology 'allocation, cut-off, EN 15804+A2'.

No other sources were used in the modelling of this EPD.

PRODUCT & MANUFACTURING SITES GROUPING

Type of grouping	No grouping
Grouping method	Not applicable
Variation in GWP-fossil for A1-A3, %	Not applicable

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

PRODUCT LIFE CYCLE

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production. The material losses occurring during the manufacturing processes are treated as per the waste handling practices in the factory, while scenario assumptions are made in the absence of exact data. The study also considers the fuels used by machines as well as losses during electricity transmission.

The product is made of metals, plastics, and electronic components. All components are transported to the production facility, where the main manufacturing processes primarily are associated with assembly. A2 transport distances are calculated always taking the capital city of component country of origin as a starting point and exact manufacturing location as destination. The finished product can be packaged with polyethylene, cardboard, and/or paper as packaging material before shipment to customers. Manufacturing loss, ancillaries and wastes are calculated according to the data that each manufacturing site is sharing with Signify. The total annual amount of waste in kg is allocated to the total annual production in kg at the specific manufacturing site responsible to produce the studied product. Thus, it is possible to allocate it according to the weight of the product analysed in this study.

Co-product allocation is neglected as revenue of co-product is very low, hence, the waste undergoes a conservative waste treatment.

The use of green energy in manufacturing is demonstrated through contractual instruments (GOs, RECs, etc), and its use is ensured throughout the validity period of this EPD.

TRANSPORT AND INSTALLATION (A4-A5)

A4 transport distances are calculated always taking the exact manufacturing location to customer location. If the customer's location is defined as a country or its capital city, the calculation is made to the respective capital city. If the

customer's location is specified as a region, the distance is calculated to the capital city of the best-performing sales country within that region. The transportation method is a combination of lorry and container ship where needed. To be conservative, empty returns are included in this study as implemented through an average load factor in the Ecoinvent transport datapoints. Environmental impacts from installation include waste packaging materials (A5). The packaging waste treatment is assumed to be conservative with incineration without energy recovery. The impacts of energy consumption and the used ancillary materials during installation are considered negligible.

PRODUCT USE AND MAINTENANCE (B1-B7)


During the use phase, the product consumes electricity (B6), which is calculated multiplying the Wattage x Assigned lifetime (hours) x Country energy mix factor. To know which Country energy mix was used in this EPD, please refer to Annex 2.

The Reference service life in years is calculated according to the main application type of the product, based on annual operating hours. Impacts due to electricity production include direct emissions to air, transformation, and transmission losses.

PRODUCT END OF LIFE (C1-C4, D)

Consumption of energy and natural resources in demolition process is assumed to be negligible. It is assumed that the waste is collected separately and transported to the waste treatment centre. The transport distance is 150 km while the transportation method is assumed to be lorry (C2). According to EN 50693:2019, the sequence of treatment operations occurring to the product shall include de-pollution, fractions separation and preparation (dismantling, crushing, shredding, sorting), recycling, other material recovery, energy recovery and disposal. In this study, the default values from table G.4 of EN 50693 is used for treating materials in different waste treatment methods. Due to the material and energy recovery potential of parts in the lighting system, the end-of-life product is converted into recycled raw materials, while the energy recovered from incineration displaces electricity and heat production (D). The benefits and loads of incineration and recycling are included in Module D.

LIFE CYCLE FLOW DIAGRAM - SYSTEM BOUNDARY



ENVIRONMENTAL IMPACT DATA, RESULTS PER DECLARED UNIT

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	5.43E+01	6.34E-01	9.64E-01	5.59E+01	2.20E+00	1.68E+00	ND	ND	ND	ND	ND	9.38E+02	ND	0.00E+00	1.84E-01	1.69E+00	8.67E-01	-2.54E+00
GWP – fossil	kg CO ₂ e	5.40E+01	6.34E-01	2.32E+00	5.70E+01	2.20E+00	1.04E-01	ND	ND	ND	ND	ND	9.33E+02	ND	0.00E+00	1.84E-01	1.69E+00	8.67E-01	-2.53E+00
GWP – biogenic	kg CO ₂ e	1.75E-01	1.43E-04	-1.39E+00	-1.21E+00	4.97E-04	1.58E+00	ND	ND	ND	ND	ND	2.09E+00	ND	0.00E+00	4.02E-05	-3.41E-04	-1.37E-04	-3.53E-03
GWP – LULUC	kg CO ₂ e	8.06E-02	2.84E-04	3.60E-02	1.17E-01	9.82E-04	2.57E-05	ND	ND	ND	ND	ND	2.86E+00	ND	0.00E+00	8.15E-05	1.41E-04	6.85E-05	-4.53E-03
Ozone depletion pot.	kg CFC-11e	6.52E-07	9.36E-09	5.48E-08	7.16E-07	3.24E-08	9.58E-10	ND	ND	ND	ND	ND	1.72E-05	ND	0.00E+00	2.57E-09	1.64E-09	1.08E-09	-1.50E-08
Acidification potential	mol H ⁺ e	3.32E-01	2.36E-03	9.62E-03	3.44E-01	7.48E-03	4.16E-04	ND	ND	ND	ND	ND	5.48E+00	ND	0.00E+00	6.14E-04	1.40E-03	4.64E-04	-2.67E-02
EP-freshwater ²⁾	kg Pe	2.09E-02	4.90E-05	8.15E-04	2.18E-02	1.71E-04	7.01E-06	ND	ND	ND	ND	ND	8.68E-01	ND	0.00E+00	1.43E-05	5.94E-05	9.51E-06	-1.74E-03
EP-marine	kg Ne	5.64E-02	7.57E-04	4.09E-03	6.13E-02	2.46E-03	1.95E-04	ND	ND	ND	ND	ND	8.60E-01	ND	0.00E+00	1.99E-04	4.34E-04	1.04E-03	-2.86E-03
EP-terrestrial	mol Ne	5.73E-01	8.25E-03	2.64E-02	6.08E-01	2.68E-02	1.77E-03	ND	ND	ND	ND	ND	7.71E+00	ND	0.00E+00	2.16E-03	4.32E-03	2.07E-03	-3.15E-02
POCP (“smog”) ³⁾	kg NMVOCe	2.02E-01	3.31E-03	1.04E-02	2.15E-01	1.10E-02	5.04E-04	ND	ND	ND	ND	ND	2.54E+00	ND	0.00E+00	8.54E-04	1.20E-03	5.96E-04	-9.34E-03
ADP-minerals & metals ⁴⁾	kg Sbe	1.36E-03	1.75E-06	1.21E-05	1.37E-03	6.12E-06	2.07E-07	ND	ND	ND	ND	ND	1.26E-02	ND	0.00E+00	6.05E-07	5.60E-06	1.69E-07	-2.37E-04
ADP-fossil resources	MJ	6.64E+02	9.18E+00	3.16E+01	7.05E+02	3.19E+01	7.19E-01	ND	ND	ND	ND	ND	2.17E+04	ND	0.00E+00	2.58E+00	1.53E+00	8.69E-01	-3.10E+01
Water use ⁵⁾	m ³ e depr.	1.50E+01	4.52E-02	8.96E-01	1.60E+01	1.57E-01	8.41E-02	ND	ND	ND	ND	ND	5.92E+02	ND	0.00E+00	1.20E-02	1.24E-01	6.30E-02	-6.15E-01

1) GWP = Global Warming Potential. 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e. 3) POCP = Photochemical ozone formation. 4) ADP = Abiotic depletion potential. 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	3.93E-06	6.29E-08	1.68E-07	4.16E-06	2.20E-07	5.14E-09	ND	ND	ND	ND	ND	1.96E-05	ND	0.00E+00	1.46E-08	1.61E-08	6.42E-09	-1.80E-07
Ionizing radiation ⁶⁾	kBq U235e	2.61E+00	7.96E-03	1.01E-01	2.72E+00	2.77E-02	8.73E-04	ND	ND	ND	ND	ND	6.00E+02	ND	0.00E+00	2.09E-03	5.84E-03	1.34E-03	-2.94E-01
Ecotoxicity (freshwater)	CTUe	6.16E+02	1.29E+00	1.07E+01	6.28E+02	4.51E+00	2.03E+00	ND	ND	ND	ND	ND	3.31E+03	ND	0.00E+00	4.08E-01	3.78E+00	1.28E+02	-1.81E+01
Human toxicity, cancer	CTUh	4.42E-08	1.05E-10	1.08E-09	4.54E-08	3.62E-10	9.73E-11	ND	ND	ND	ND	ND	3.15E-07	ND	0.00E+00	3.13E-11	2.12E-10	1.02E-10	-2.28E-09
Human tox. non-cancer	CTUh	1.10E-06	5.91E-09	2.88E-08	1.13E-06	2.06E-08	3.95E-09	ND	ND	ND	ND	ND	1.63E-05	ND	0.00E+00	1.62E-09	9.75E-09	6.59E-09	-2.21E-07
SQP ⁷⁾	-	1.93E+02	9.16E+00	1.07E+02	3.09E+02	3.21E+01	3.51E-01	ND	ND	ND	ND	ND	4.83E+03	ND	0.00E+00	1.54E+00	2.17E+00	1.10E+00	-1.22E+01

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	5.80E+01	1.25E-01	7.98E+00	6.61E+01	4.37E-01	-1.94E+01	ND	ND	ND	ND	ND	5.96E+03	ND	0.00E+00	3.54E-02	2.00E-01	2.30E-02	-4.50E+00
Renew. PER as material	MJ	1.87E+00	0.00E+00	1.21E+01	1.40E+01	0.00E+00	-1.40E+01	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-4.10E-03	-7.62E-03	0.00E+00
Total use of renew. PER	MJ	5.99E+01	1.25E-01	2.01E+01	8.01E+01	4.37E-01	-3.33E+01	ND	ND	ND	ND	ND	5.96E+03	ND	0.00E+00	3.54E-02	1.96E-01	1.54E-02	-4.50E+00
Non-re. PER as energy	MJ	6.21E+02	9.18E+00	2.51E+01	6.55E+02	3.19E+01	1.74E-01	ND	ND	ND	ND	ND	2.17E+04	ND	0.00E+00	2.58E+00	-2.27E+01	-2.56E+01	-3.10E+01
Non-re. PER as material	MJ	4.00E+01	0.00E+00	-6.80E-01	3.93E+01	0.00E+00	-7.63E-01	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-1.93E+01	-1.93E+01	0.00E+00
Total use of non-re. PER	MJ	6.61E+02	9.18E+00	2.44E+01	6.95E+02	3.19E+01	-5.89E-01	ND	ND	ND	ND	ND	2.17E+04	ND	0.00E+00	2.58E+00	-4.20E+01	-4.49E+01	-3.10E+01
Secondary materials	kg	3.40E+00	0.00E+00	0.00E+00	3.40E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renew. secondary fuels	MJ	2.85E-02	4.93E-05	1.15E-01	1.44E-01	1.72E-04	9.03E-06	ND	ND	ND	ND	ND	2.87E-02	ND	0.00E+00	1.48E-05	7.22E-05	1.37E-05	-3.94E-04
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³	2.26E-01	1.35E-03	2.04E-02	2.47E-01	4.71E-03	1.37E-03	ND	ND	ND	ND	ND	1.88E+01	ND	0.00E+00	3.42E-04	2.33E-03	-3.04E-03	-2.06E-02

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	8.73E+00	1.55E-02	1.27E-01	8.87E+00	5.40E-02	2.21E-02	ND	ND	ND	ND	ND	5.49E+01	ND	0.00E+00	4.50E-03	3.67E-02	3.96E-02	-2.56E-01
Non-hazardous waste	kg	1.94E+02	2.87E-01	8.47E+00	2.02E+02	9.99E-01	1.18E+00	ND	ND	ND	ND	ND	4.25E+03	ND	0.00E+00	8.44E-02	1.01E+00	7.62E+00	-9.51E+00
Radioactive waste	kg	6.51E-04	1.95E-06	2.42E-05	6.78E-04	6.79E-06	2.19E-07	ND	ND	ND	ND	ND	1.54E-01	ND	0.00E+00	5.12E-07	1.44E-06	3.30E-07	-7.21E-05

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for reuse	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	7.56E-02	7.56E-02	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	3.38E+00	0.00E+00	0.00E+00
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	7.60E+00	0.00E+00	0.00E+00
Exported energy – Electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	3.20E+00	0.00E+00	0.00E+00
Exported energy – Heat	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	4.40E+00	0.00E+00	0.00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	5.40E+01	6.31E-01	2.46E+00	5.71E+01	2.18E+00	1.04E-01	ND	ND	ND	ND	ND	9.33E+02	ND	0.00E+00	1.83E-01	1.69E+00	8.65E-01	-2.52E+00
Ozone depletion Pot.	kg CFC-11e	5.84E-07	7.47E-09	5.42E-08	6.45E-07	2.59E-08	8.15E-10	ND	ND	ND	ND	ND	1.44E-05	ND	0.00E+00	2.06E-09	1.40E-09	8.94E-10	-1.27E-08
Acidification	kg SO ₂ e	2.79E-01	1.81E-03	6.84E-03	2.88E-01	5.72E-03	3.05E-04	ND	ND	ND	ND	ND	4.67E+00	ND	0.00E+00	4.70E-04	1.09E-03	3.35E-04	-2.30E-02
Eutrophication	kg PO ₄ ³ e	7.91E-02	4.17E-04	5.01E-03	8.45E-02	1.39E-03	9.50E-05	ND	ND	ND	ND	ND	6.05E-01	ND	0.00E+00	1.14E-04	2.10E-04	1.77E-04	-1.77E-03
POCP (“smog”)	kg C ₂ H ₄ e	2.38E-02	1.54E-04	7.86E-04	2.47E-02	5.09E-04	2.32E-05	ND	ND	ND	ND	ND	2.55E-01	ND	0.00E+00	4.21E-05	6.62E-05	3.11E-05	-1.11E-03
ADP-elements	kg Sbe	1.34E-03	1.71E-06	1.19E-05	1.35E-03	5.97E-06	1.73E-07	ND	ND	ND	ND	ND	1.26E-02	ND	0.00E+00	5.90E-07	5.55E-06	1.47E-07	-2.37E-04
ADP-fossil	MJ	6.21E+02	9.06E+00	2.99E+01	6.60E+02	3.14E+01	7.06E-01	ND	ND	ND	ND	ND	1.11E+04	ND	0.00E+00	2.55E+00	1.44E+00	8.48E-01	-2.63E+01

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG 9)	kg CO ₂ e	5.41E+01	6.34E-01	2.35E+00	5.71E+01	2.20E+00	1.04E-01	ND	ND	ND	ND	ND	9.36E+02	ND	0.00E+00	1.84E-01	1.69E+00	8.67E-01	-2.54E+00

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows - CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide - were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO₂ is set to zero.

ENVIRONMENTAL IMPACT DATA, RESULTS PER FUNCTIONAL UNIT

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ éq/FU	5.86E+00	6.85E-02	1.04E-01	6.04E+00	2.37E-01	1.82E-01	ND	ND	ND	ND	ND	1.01E+02	ND	0.00E+00	1.99E-02	1.82E-01	9.37E-02	-2.74E-01
GWP – fossil	kg CO ₂ éq/FU	5.84E+00	6.85E-02	2.50E-01	6.15E+00	2.37E-01	1.13E-02	ND	ND	ND	ND	ND	1.01E+02	ND	0.00E+00	1.99E-02	1.82E-01	9.37E-02	-2.74E-01
GWP – biogenic	kg CO ₂ éq/FU	1.89E-02	1.55E-05	-1.50E-01	-1.31E-01	5.37E-05	1.70E-01	ND	ND	ND	ND	ND	2.26E-01	ND	0.00E+00	4.34E-06	-3.68E-05	-1.48E-05	-3.82E-04
GWP – LULUC	kg CO ₂ éq/FU	8.71E-03	3.07E-05	3.89E-03	1.26E-02	1.06E-04	2.77E-06	ND	ND	ND	ND	ND	3.09E-01	ND	0.00E+00	8.81E-06	1.52E-05	7.39E-06	-4.89E-04
Ozone depletion pot.	kg CFC-11e/FU	7.04E-08	1.01E-09	5.92E-09	7.74E-08	3.50E-09	1.04E-10	ND	ND	ND	ND	ND	1.86E-06	ND	0.00E+00	2.78E-10	1.77E-10	1.17E-10	-1.63E-09
Acidification potential	mole H ⁺ e/FU	3.59E-02	2.54E-04	1.04E-03	3.72E-02	8.09E-04	4.49E-05	ND	ND	ND	ND	ND	5.92E-01	ND	0.00E+00	6.63E-05	1.51E-04	5.01E-05	-2.89E-03
EP-freshwater ²⁾	kg Pe/FU	2.26E-03	5.29E-06	8.81E-05	2.35E-03	1.85E-05	7.57E-07	ND	ND	ND	ND	ND	9.38E-02	ND	0.00E+00	1.55E-06	6.42E-06	1.03E-06	-1.88E-04
EP-marine	kg Ne/FU	6.10E-03	8.17E-05	4.42E-04	6.62E-03	2.66E-04	2.10E-05	ND	ND	ND	ND	ND	9.29E-02	ND	0.00E+00	2.15E-05	4.69E-05	1.12E-04	-3.09E-04
EP-terrestrial	mol Ne/FU	6.19E-02	8.91E-04	2.86E-03	6.57E-02	2.89E-03	1.91E-04	ND	ND	ND	ND	ND	8.33E-01	ND	0.00E+00	2.34E-04	4.67E-04	2.23E-04	-3.40E-03
POCP (“smog”) ³⁾	kg NMVOCe/	2.18E-02	3.58E-04	1.13E-03	2.33E-02	1.19E-03	5.44E-05	ND	ND	ND	ND	ND	2.74E-01	ND	0.00E+00	9.23E-05	1.29E-04	6.44E-05	-1.01E-03
ADP-minerals & metals ⁴⁾	kg Sbe/FU	1.47E-04	1.90E-07	1.31E-06	1.48E-04	6.62E-07	2.24E-08	ND	ND	ND	ND	ND	1.36E-03	ND	0.00E+00	6.53E-08	6.05E-07	1.83E-08	-2.56E-05
ADP-fossil resources	MJ/FU	7.17E+01	9.92E-01	3.41E+00	7.61E+01	3.44E+00	7.77E-02	ND	ND	ND	ND	ND	2.34E+03	ND	0.00E+00	2.79E-01	1.65E-01	9.39E-02	-3.34E+00
Water use ⁵⁾	m ³ e priv./FU	1.62E+00	4.88E-03	9.67E-02	1.72E+00	1.70E-02	9.09E-03	ND	ND	ND	ND	ND	6.39E+01	ND	0.00E+00	1.29E-03	1.34E-02	6.81E-03	-6.64E-02

1) GWP = Global Warming Potential. 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e. 3) POCP = Photochemical ozone formation. 4) ADP = Abiotic depletion potential. 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence /FU	4.24E-07	6.80E-09	1.81E-08	4.49E-07	2.37E-08	5.55E-10	ND	ND	ND	ND	ND	2.11E-06	ND	0.00E+00	1.58E-09	1.73E-09	6.93E-10	-1.95E-08
Ionizing radiation ⁶⁾	kBq U235e/FU	2.82E-01	8.60E-04	1.10E-02	2.94E-01	3.00E-03	9.43E-05	ND	ND	ND	ND	ND	6.48E+01	ND	0.00E+00	2.26E-04	6.31E-04	1.44E-04	-3.18E-02
Ecotoxicity (freshwater)	CTUe/FU	6.65E+01	1.40E-01	1.15E+00	6.78E+01	4.87E-01	2.19E-01	ND	ND	ND	ND	ND	3.57E+02	ND	0.00E+00	4.41E-02	4.08E-01	1.38E+01	-1.95E+00
Human toxicity, cancer	CTUh/FU	4.78E-09	1.13E-11	1.16E-10	4.90E-09	3.91E-11	1.05E-11	ND	ND	ND	ND	ND	3.41E-08	ND	0.00E+00	3.38E-12	2.29E-11	1.10E-11	-2.46E-10
Human tox. non-cancer	CTUh/FU	1.18E-07	6.38E-10	3.11E-09	1.22E-07	2.23E-09	4.27E-10	ND	ND	ND	ND	ND	1.77E-06	ND	0.00E+00	1.75E-10	1.05E-09	7.12E-10	-2.38E-08
SQP ⁷⁾	-/FU	2.08E+01	9.90E-01	1.15E+01	3.33E+01	3.47E+00	3.80E-02	ND	ND	ND	ND	ND	5.22E+02	ND	0.00E+00	1.67E-01	2.35E-01	1.19E-01	-1.31E+00

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ/FU	6.27E+00	1.35E-02	8.62E-01	7.15E+00	4.72E-02	-2.09E+00	ND	ND	ND	ND	ND	6.43E+02	ND	0.00E+00	3.83E-03	2.16E-02	2.48E-03	-4.86E-01
Renew. PER as material	MJ/FU	2.02E-01	0.00E+00	1.31E+00	1.51E+00	0.00E+00	-1.51E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-4.43E-04	-8.23E-04	0.00E+00
Total use of renew. PER	MJ/FU	6.47E+00	1.35E-02	2.17E+00	8.65E+00	4.72E-02	-3.60E+00	ND	ND	ND	ND	ND	6.43E+02	ND	0.00E+00	3.83E-03	2.12E-02	1.66E-03	-4.86E-01
Non-re. PER as energy	MJ/FU	6.71E+01	9.92E-01	2.71E+00	7.08E+01	3.44E+00	1.88E-02	ND	ND	ND	ND	ND	2.34E+03	ND	0.00E+00	2.79E-01	-2.45E+00	-2.76E+00	-3.34E+00
Non-re. PER as material	MJ/FU	4.32E+00	0.00E+00	-7.34E-02	4.25E+00	0.00E+00	-8.24E-02	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-2.08E+00	-2.09E+00	0.00E+00
Total use of non-re. PER	MJ/FU	7.14E+01	9.92E-01	2.64E+00	7.51E+01	3.44E+00	-6.36E-02	ND	ND	ND	ND	ND	2.34E+03	ND	0.00E+00	2.79E-01	-4.54E+00	-4.85E+00	-3.34E+00
Secondary materials	kg/FU	3.67E-01	0.00E+00	0.00E+00	3.67E-01	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renew. secondary fuels	MJ/FU	3.07E-03	5.32E-06	1.24E-02	1.55E-02	1.86E-05	9.76E-07	ND	ND	ND	ND	ND	3.10E-03	ND	0.00E+00	1.60E-06	7.80E-06	1.48E-06	-4.26E-05
Non-ren. secondary fuels	MJ/FU	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³ /FU	2.44E-02	1.46E-04	2.21E-03	2.67E-02	5.09E-04	1.48E-04	ND	ND	ND	ND	ND	2.03E+00	ND	0.00E+00	3.70E-05	2.52E-04	-3.29E-04	-2.22E-03

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg/FU	9.43E-01	1.68E-03	1.37E-02	9.59E-01	5.83E-03	2.39E-03	ND	ND	ND	ND	ND	5.93E+00	ND	0.00E+00	4.86E-04	3.97E-03	4.28E-03	-2.77E-02
Non-hazardous waste	kg/FU	2.09E+01	3.10E-02	9.15E-01	2.19E+01	1.08E-01	1.28E-01	ND	ND	ND	ND	ND	4.59E+02	ND	0.00E+00	9.12E-03	1.09E-01	8.23E-01	-1.03E+00
Radioactive waste	kg/FU	7.04E-05	2.10E-07	2.62E-06	7.32E-05	7.34E-07	2.36E-08	ND	ND	ND	ND	ND	1.66E-02	ND	0.00E+00	5.53E-08	1.56E-07	3.56E-08	-7.79E-06

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for reuse	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	8.16E-03	8.16E-03	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	3.65E-01	0.00E+00	0.00E+00
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	8.21E-01	0.00E+00	0.00E+00
Exported energy – Electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	3.46E-01	0.00E+00	0.00E+00
Exported energy – Heat	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	4.75E-01	0.00E+00	0.00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ eq./FU	5.84E+00	6.81E-02	2.66E-01	6.17E+00	2.36E-01	1.12E-02	ND	ND	ND	ND	ND	1.01E+02	ND	0.00E+00	1.98E-02	1.82E-01	9.35E-02	-2.73E-01
Ozone depletion Pot.	kg CFC ₁₁ /FU	6.30E-08	8.06E-10	5.86E-09	6.97E-08	2.79E-09	8.80E-11	ND	ND	ND	ND	ND	1.55E-06	ND	0.00E+00	2.22E-10	1.51E-10	9.66E-11	-1.37E-09
Acidification	kg SO ₂ e/FU	3.01E-02	1.95E-04	7.39E-04	3.11E-02	6.17E-04	3.30E-05	ND	ND	ND	ND	ND	5.05E-01	ND	0.00E+00	5.08E-05	1.18E-04	3.62E-05	-2.49E-03
Eutrophication	kg PO ₄ ³ e/FU	8.54E-03	4.50E-05	5.42E-04	9.13E-03	1.50E-04	1.03E-05	ND	ND	ND	ND	ND	6.53E-02	ND	0.00E+00	1.23E-05	2.27E-05	1.91E-05	-1.91E-04
POCP (“smog”)	kg C ₂ H ₄ e/FU	2.57E-03	1.66E-05	8.49E-05	2.67E-03	5.50E-05	2.51E-06	ND	ND	ND	ND	ND	2.75E-02	ND	0.00E+00	4.55E-06	7.15E-06	3.36E-06	-1.19E-04
ADP-elements	kg Sbe/FU	1.45E-04	1.85E-07	1.29E-06	1.46E-04	6.45E-07	1.87E-08	ND	ND	ND	ND	ND	1.36E-03	ND	0.00E+00	6.38E-08	5.99E-07	1.59E-08	-2.56E-05
ADP-fossil	MJ/FU	6.71E+01	9.78E-01	3.23E+00	7.13E+01	3.39E+00	7.62E-02	ND	ND	ND	ND	ND	1.20E+03	ND	0.00E+00	2.75E-01	1.55E-01	9.16E-02	-2.84E+00

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e/FU	5.84E+00	6.85E-02	2.54E-01	6.17E+00	2.37E-01	1.13E-02	ND	ND	ND	ND	ND	1.01E+02	ND	0.00E+00	1.99E-02	1.82E-01	9.37E-02	-2.74E-01

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows - CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide - were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO₂ is set to zero.

SCENARIO DOCUMENTATION

DATA SOURCES

Manufacturing energy scenario documentation – A3 (Energy data source)

1. Energy supply, electricity production, co-generation oil and gas, Heat and power co-generation, natural gas, combined cycle power plant, 400MW electrical, Spain, ecoinvent 3.10.1, 0.0249 kgCO₂e/MJ
2. Energy supply, electricity production, solar photovoltaic, Electricity production, photovoltaic, 570kWp open ground installation, multi-Si, Spain, ecoinvent 3.10.1, 0.0673 kgCO₂e/kWh

Transport scenario documentation - A4

1. Transport, freight, lorry >32 metric ton, EURO5, 2760.17 km
2. Transport, freight, sea, container ship, 0.0 km

Installation scenario documentation - A5 (Waste materials data source)

1. Market for corrugated board box, 1.039 kg
2. Market for printed paper, offset, 0.051 kg
3. Market for packaging film, low density polyethylene, 0.015 kg

Use stages scenario documentation - B6-B7 (Energy data source)

1. Energy supply, electricity transformation and distribution, distribution low voltage, Market group for electricity, low voltage, Europe, 2850.0 kWh

TRANSPORT SCENARIO DOCUMENTATION - A4

Scenario parameter	Value
Capacity utilization (including empty return) %	50 %
Bulk density of transported products / kg/m ³	8.90E+01
Volume capacity utilization factor (factor: =1 or <1 or ≥1 for compressed or nested packaged products)	1

INSTALLATION SCENARIO DOCUMENTATION - A5

Scenario parameter	Value
Ancillary materials for installation (specified by material) / kg or other units as appropriate	0
Water use / m ³	0
Other resource use / kg	0
Direct emissions to ambient air, soil and water / kg	0

USE STAGES SCENARIO DOCUMENTATION - B6-B7 USE OF ENERGY AND WATER

Scenario information	Value
Ancillary materials specified by material / kg or units as appropriate	Not applicable
Net fresh water consumption / m ³	0
Power output of equipment / kW	28.5
Characteristic performance, e.g., energy efficiency, emissions, variation of performance with capacity utilization, etc. / Units as appropriate	For more details see product classification table and product description.
Further assumptions for scenario development, e.g., frequency and period of use, number of occupants / Units as appropriate	For more details see product classification table and product description.

END OF LIFE SCENARIO DOCUMENTATION

Scenario information	Value
Collection process – kg collected separately	6.284
Collection process – kg collected with mixed waste	0
Recovery process – kg for re-use	0
Recovery process – kg for recycling	3.38E+00
Recovery process – kg for energy recovery	0
Disposal (total) – kg for final deposition	2.20E+00
Scenario assumptions e.g. transportation	Lorry, 16-32 metric ton, EURO5; 150 km

THIRD-PARTY VERIFICATION STATEMENT

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.



Program assistant: Xinyuan Zhang



The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.

[Verified tools](#)

Tool verifier: Hai Ha Nguyen

Tool verification validity: 28 March 2025 - 27 March 2028

APPENDIX 1

MATERIAL COMPOSITION

The product material composition is illustrated in the table below. The material weight is given in grams and in percentage on total product weight.

Table 1: Material composition

Material	Weight (g)	Weight-%
Aluminium	4631	73.7
Copper	12.68	0.2
Other Plastics	1193.52	18.99
Paint	159	2.53
PCB Alu	27.9	0.44
PCB Copper	32.08	0.51
PCB Iron	28.05	0.45
PCB Non-ferrous metal	0.01	0
PCB Support	112.4	1.79
PCB Tin	1.94	0.03
Stainless Steel	2	0.03
Steel	83.04	1.32

APPENDIX 2

USE PHASE (B6) VALUES FOR DIFFERENT COUNTRY MIX

In this EPD the B6 impact has been calculated using the energy mix of **EU**. The table in this appendix is useful for conversion and comparison of B6 values with other country energy mix. The Global Warming Potential Total (GWP tot) value is illustrated for each country. The value refers to 1 kwh.

Example on how to use the table:

If for example this EPD was done according to EU energy mix and you want to see how the GWP total changes according to a Finland country energy mix, you can take the original value in the results table here highlighted in yellow:

ENVIRONMENTAL IMPACT DATA, RESULTS PER DECLARED UNIT

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	1.08E+01	2.33E-01	5.06E-01	1.15E+01	3.27E+00	1.68E+00	ND	ND	ND	ND	ND	4.06E-02	ND	0.00E+00	2.88E-02	5.13E-01	2.80E-01	-9.88E-01

Divide that value according to the EU value from the following table (EU = 3.30E-01) and then multiplying for the Finland value from the same table (FINLAND = 1.54E-01).

Thus, the calculation of this example would be:

New B6 GWP tot for Finland = $(4.06E-02 / 3.30E-01) \times 1.54E-01 = 1.89E-02$.

Country	GWP tot (kg CO2 eq. per kwh)		
AFRICA	7.30E-01	GERMANY	3.90E-01
APAC	9.50E-01	INDIA	1.50E+00
AUSTRALIA	8.40E-01	ITALY	3.50E-01
AUSTRIA	2.30E-01	LATAM	3.90E-01
BELGIUM	2.00E-01	NAM	4.50E-01
CHINA	1.02E+00	NETHERLANDS	3.90E-01
DENMARK	1.60E-01	NORWAY	4.50E-02
EU	3.30E-01	ROW	7.30E-01
FINLAND	1.54E-01	SPAIN	2.10E-01
FRANCE	8.70E-02	SWEDEN	3.70E-02
		UK	2.60E-01

Source Ecoinvent 3.10.1

APPENDIX 3 - EPD HUB ALIGNED

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management scenarios and power inputs of the luminaires within the same product family.

To calculate the Scaled Impact (*SI*), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions P_{in} and the power input of the base variant P_{base} .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system). The presented controls factors values in Table A1 are based on BS EN 15193-1:2017. Please refer to this publication or contact Signify directly for more information.

$$TSF = PSF * CSF$$

Table 1: Light management function (PEP EcoPassport aligned)

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

3. Lastly, the GWP of the base variant is then scaled by the TSF.

$$\text{Scaled Impact} = \text{GWP}_{\text{case}} * \text{TSF}$$

The following list of product configurations is not exhaustive. Please use the formula defined in point 1 above to calculate the exact power scaling factor (PSF) for any specific configuration.

Table 2: GWP per scaling factor (EPD Hub aligned)

	12NC or Product Family Code	Description	Flux [Lm]	Power [W]	Efficacy [L/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
							NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
1	BDP265	BDP265LED8-4S740DM50	656	5.6	117.143	0.196	0.196	0.147	0.147	0.108	184.24	138.18	138.18	101.332
2	BDP265	BDP265LED10-4S740DM50	820	6.8	120.588	0.239	0.239	0.179	0.179	0.131	223.72	167.79	167.79	123.046
3	BDP265	BDP265LED12-4S740DM50	984	7.7	127.792	0.270	0.270	0.203	0.203	0.149	253.33	189.9975	189.9975	139.3315
4	BDP265	BDP265LED14-4S740DM50	1148	8.9	128.989	0.312	0.312	0.234	0.234	0.172	292.81	219.6075	219.6075	161.0455
5	BDP265	BDP265LED16-4S740DM50	1312	10	131.200	0.351	0.351	0.263	0.263	0.193	329	246.75	246.75	180.95
6	BDP265	BDP265LED18-4S740DM50	1476	11.2	131.786	0.393	0.393	0.295	0.295	0.216	368.48	276.36	276.36	202.664
7	BDP265	BDP265LED20-4S740DM50	1640	12.4	132.258	0.435	0.435	0.326	0.326	0.239	407.96	305.97	305.97	224.378
8	BDP265	BDP265LED22-4S740DM50	1782	13.6	131.029	0.477	0.477	0.358	0.358	0.262	447.44	335.58	335.58	246.092
9	BDP265	BDP265LED24-4S740DM50	1944	15	129.600	0.526	0.526	0.395	0.395	0.289	493.5	370.125	370.125	271.425
10	BDP265	BDP265LED27-4S740DM50	2187	17	128.647	0.596	0.596	0.447	0.447	0.328	559.3	419.475	419.475	307.615
11	BDP265	BDP265LED30-4S740DM50	2430	19	127.895	0.667	0.667	0.500	0.500	0.367	625.1	468.825	468.825	343.805
12	BDP265	BDP265LED34-4S740DM50	2754	20	137.700	0.702	0.702	0.526	0.526	0.386	658	493.5	493.5	361.9

13	BDP265	BDP265LED35-4S740DM50	2835	20.5	138.293	0.719	0.719	0.539	0.539	0.396	674.45	505.8375	505.8375	370.9475
14	BDP265	BDP265LED39-4S740DM50	3159	23	137.348	0.807	0.807	0.605	0.605	0.444	756.7	567.525	567.525	416.185
15	BDP265	BDP265LED40-4S740DM50	3240	23.5	137.872	0.825	0.825	0.618	0.618	0.454	773.15	579.8625	579.8625	425.2325
16	BDP265	BDP265LED44-4S740DM50	3564	26	137.077	0.912	0.912	0.684	0.684	0.502	855.4	641.55	641.55	470.47
17	BDP265	BDP265LED45-4S740DM50	3645	27	135.000	0.947	0.947	0.711	0.711	0.521	888.3	666.225	666.225	488.565
18	BDP265	BDP265LED50-4S740DM50	4050	28.5	142.105	1.000	1.000	0.750	0.750	0.550	937.65	703.2375	703.2375	515.7075
19	BDP265	BDP265LED55-4S740DM50	4536	31.5	144.000	1.105	1.105	0.829	0.829	0.608	1036.35	777.2625	777.2625	569.9925
20	BDP265	BDP265LED59-4S740DM50	4860	33.5	145.075	1.175	1.175	0.882	0.882	0.646	1102.15	826.6125	826.6125	606.1825
21	BDP265	BDP265LED64-4S740DM50	5120	37	138.378	1.298	1.298	0.974	0.974	0.714	1217.3	912.975	912.975	669.515
22	BDP265	BDP265LED69-4S740DM50	5600	40	140.000	1.404	1.404	1.053	1.053	0.772	1316	987	987	723.8
23	BDP265	BDP265LED74-4S740DM50	5920	43	137.674	1.509	1.509	1.132	1.132	0.830	1414.7	1061.025	1061.025	778.085
24	BDP265	BDP265LED79-4S740DM50	6240	44.5	140.225	1.561	1.561	1.171	1.171	0.859	1464.05	1098.0375	1098.0375	805.2275
25	BDP265	BDP265LED84-4S740DM50	6720	47.5	141.474	1.667	1.667	1.250	1.250	0.917	1562.75	1172.0625	1172.0625	859.5125
26	BDP265	BDP265LED90-4S740DM50	7200	51	141.176	1.789	1.789	1.342	1.342	0.984	1677.9	1258.425	1258.425	922.845
27	BDP265	BDP265LED94-4S740DM50	7520	54	139.259	1.895	1.895	1.421	1.421	1.042	1776.6	1332.45	1332.45	977.13
28	BDP265	BDP265LED109-4S740DM50	8800	63	139.683	2.211	2.211	1.658	1.658	1.216	2072.7	1554.525	1554.525	1139.985
29	BDP265	BDP265LED120-4S740DM50	9600	71	135.211	2.491	2.491	1.868	1.868	1.370	2335.9	1751.925	1751.925	1284.745
30	BDP265	BDP265LED130-4S740DM50	10270	77	133.377	2.702	2.702	2.026	2.026	1.486	2533.3	1899.975	1899.975	1393.315
31	BDP265	BDP265LED6-4S722DM50	492	5.6	87.857	0.196	0.196	0.147	0.147	0.108	184.24	138.18	138.18	101.332
32	BDP265	BDP265LED8-4S722DM50	656	7.1	92.394	0.249	0.249	0.187	0.187	0.137	233.59	175.1925	175.1925	128.4745
33	BDP265	BDP265LED10-4S722DM50	810	8.8	92.045	0.309	0.309	0.232	0.232	0.170	289.52	217.14	217.14	159.236
34	BDP265	BDP265LED12-4S722DM50	984	10	98.400	0.351	0.351	0.263	0.263	0.193	329	246.75	246.75	180.95

35	BDP265	BDP265LED14-4S722DM50	1148	11.6	98.966	0.407	0.407	0.305	0.305	0.224	381.64	286.23	286.23	209.902
36	BDP265	BDP265LED16-4S722DM50	1296	13.2	98.182	0.463	0.463	0.347	0.347	0.255	434.28	325.71	325.71	238.854
37	BDP265	BDP265LED18-4S722DM50	1458	14.8	98.514	0.519	0.519	0.389	0.389	0.286	486.92	365.19	365.19	267.806
38	BDP265	BDP265LED20-4S722DM50	1620	16.6	97.590	0.582	0.582	0.437	0.437	0.320	546.14	409.605	409.605	300.377
39	BDP265	BDP265LED22-4S722DM50	1782	18.4	96.848	0.646	0.646	0.484	0.484	0.355	605.36	454.02	454.02	332.948
40	BDP265	BDP265LED24-4S722DM50	1944	20.5	94.829	0.719	0.719	0.539	0.539	0.396	674.45	505.8375	505.8375	370.9475
41	BDP265	BDP265LED27-4S722DM50	2187	21	104.143	0.737	0.737	0.553	0.553	0.405	690.9	518.175	518.175	379.995
42	BDP265	BDP265LED30-4S722DM50	2430	23.5	103.404	0.825	0.825	0.618	0.618	0.454	773.15	579.8625	579.8625	425.2325
43	BDP265	BDP265LED34-4S722DM50	2754	27	102.000	0.947	0.947	0.711	0.711	0.521	888.3	666.225	666.225	488.565
44	BDP265	BDP265LED35-4S722DM50	2835	27.5	103.091	0.965	0.965	0.724	0.724	0.531	904.75	678.5625	678.5625	497.6125
45	BDP265	BDP265LED39-4S722DM50	3120	31	100.645	1.088	1.088	0.816	0.816	0.598	1019.9	764.925	764.925	560.945
46	BDP265	BDP265LED40-4S722DM50	3200	32	100.000	1.123	1.123	0.842	0.842	0.618	1052.8	789.6	789.6	579.04
47	BDP265	BDP265LED44-4S722DM50	3520	35.5	99.155	1.246	1.246	0.934	0.934	0.685	1167.95	875.9625	875.9625	642.3725
48	BDP265	BDP265LED45-4S722DM50	3600	36.5	98.630	1.281	1.281	0.961	0.961	0.704	1200.85	900.6375	900.6375	660.4675
49	BDP265	BDP265LED50-4S722DM50	4000	38	105.263	1.333	1.333	1.000	1.000	0.733	1250.2	937.65	937.65	687.61
50	BDP265	BDP265LED55-4S722DM50	4480	42.5	105.412	1.491	1.491	1.118	1.118	0.820	1398.25	1048.6875	1048.6875	769.0375
51	BDP265	BDP265LED59-4S722DM50	4800	45.5	105.495	1.596	1.596	1.197	1.197	0.878	1496.95	1122.7125	1122.7125	823.3225
52	BDP265	BDP265LED64-4S722DM50	5120	50	102.400	1.754	1.754	1.316	1.316	0.965	1645	1233.75	1233.75	904.75
53	BDP265	BDP265LED69-4S722DM50	5600	54	103.704	1.895	1.895	1.421	1.421	1.042	1776.6	1332.45	1332.45	977.13
54	BDP266	BDP265LED74-4S722DM50	5846	59	99.085	2.070	2.070	1.553	1.553	1.139	1941.1	1455.825	1455.825	1067.605
55	BDP267	BDP265LED79-4S722DM50	6400	60	106.667	2.105	2.105	1.579	1.579	1.158	1974	1480.5	1480.5	1085.7
56	BDP268	BDP265LED84-4S722DM50	6720	65	103.385	2.281	2.281	1.711	1.711	1.254	2138.5	1603.875	1603.875	1176.175

57	BDP269	BDP265LED90-4S722DM50	7200	70	102.857	2.456	2.456	1.842	1.842	1.351	2303	1727.25	1727.25	1266.65
58	BDP270	BDP265LED94-4S722DM50	7426	74	100.351	2.596	2.596	1.947	1.947	1.428	2434.6	1825.95	1825.95	1339.03
59	BDP271	BDP265LED6-4S830DM50	492	5	98.400	0.175	0.175	0.132	0.132	0.096	164.5	123.375	123.375	90.475
60	BDP272	BDP265LED8-4S830DM50	656	6.5	100.923	0.228	0.228	0.171	0.171	0.125	213.85	160.3875	160.3875	117.6175
61	BDP273	BDP265LED10-4S830DM50	820	7.9	103.797	0.277	0.277	0.208	0.208	0.152	259.91	194.9325	194.9325	142.9505
62	BDP274	BDP265LED12-4S830DM50	984	9.1	108.132	0.319	0.319	0.239	0.239	0.176	299.39	224.5425	224.5425	164.6645
63	BDP275	BDP265LED14-4S830DM50	1148	10.4	110.385	0.365	0.365	0.274	0.274	0.201	342.16	256.62	256.62	188.188
64	BDP276	BDP265LED16-4S830DM50	1312	11.8	111.186	0.414	0.414	0.311	0.311	0.228	388.22	291.165	291.165	213.521
65	BDP277	BDP265LED18-4S830DM50	1458	13.2	110.455	0.463	0.463	0.347	0.347	0.255	434.28	325.71	325.71	238.854
66	BDP278	BDP265LED20-4S830DM50	1620	14.8	109.459	0.519	0.519	0.389	0.389	0.286	486.92	365.19	365.19	267.806
67	BDP279	BDP265LED22-4S830DM50	1782	16.4	108.659	0.575	0.575	0.432	0.432	0.316	539.56	404.67	404.67	296.758
68	BDP280	BDP265LED24-4S830DM50	1944	18	108.000	0.632	0.632	0.474	0.474	0.347	592.2	444.15	444.15	325.71
69	BDP281	BDP265LED27-4S830DM50	2187	19	115.105	0.667	0.667	0.500	0.500	0.367	625.1	468.825	468.825	343.805
70	BDP282	BDP265LED30-4S830DM50	2430	21	115.714	0.737	0.737	0.553	0.553	0.405	690.9	518.175	518.175	379.995
71	BDP283	BDP265LED34-4S830DM50	2754	24	114.750	0.842	0.842	0.632	0.632	0.463	789.6	592.2	592.2	434.28
72	BDP284	BDP265LED35-4S830DM50	2835	24.5	115.714	0.860	0.860	0.645	0.645	0.473	806.05	604.5375	604.5375	443.3275
73	BDP285	BDP265LED39-4S830DM50	3159	27.5	114.873	0.965	0.965	0.724	0.724	0.531	904.75	678.5625	678.5625	497.6125
74	BDP286	BDP265LED40-4S830DM50	3240	28.5	113.684	1.000	1.000	0.750	0.750	0.550	937.65	703.2375	703.2375	515.7075
75	BDP287	BDP265LED44-4S830DM50	3520	31.5	111.746	1.105	1.105	0.829	0.829	0.608	1036.35	777.2625	777.2625	569.9925
76	BDP288	BDP265LED45-4S830DM50	3600	32	112.500	1.123	1.123	0.842	0.842	0.618	1052.8	789.6	789.6	579.04
77	BDP289	BDP265LED50-4S830DM50	4000	36	111.111	1.263	1.263	0.947	0.947	0.695	1184.4	888.3	888.3	651.42
78	BDP290	BDP265LED55-4S830DM50	4480	37.5	119.467	1.316	1.316	0.987	0.987	0.724	1233.75	925.3125	925.3125	678.5625

79	BDP291	BDP265LED59-4S830DM50	4800	40.5	118.519	1.421	1.421	1.066	1.066	0.782	1332.45	999.3375	999.3375	732.8475
80	BDP292	BDP265LED64-4S830DM50	5120	44.5	115.056	1.561	1.561	1.171	1.171	0.859	1464.05	1098.0375	1098.0375	805.2275
81	BDP293	BDP265LED69-4S830DM50	5600	48	116.667	1.684	1.684	1.263	1.263	0.926	1579.2	1184.4	1184.4	868.56
82	BDP294	BDP265LED74-4S830DM50	5920	52	113.846	1.825	1.825	1.368	1.368	1.004	1710.8	1283.1	1283.1	940.94
83	BDP295	BDP265LED79-4S830DM50	6400	54	118.519	1.895	1.895	1.421	1.421	1.042	1776.6	1332.45	1332.45	977.13
84	BDP296	BDP265LED84-4S830DM50	6720	57	117.895	2.000	2.000	1.500	1.500	1.100	1875.3	1406.475	1406.475	1031.415
85	BDP297	BDP265LED90-4S830DM50	7200	62	116.129	2.175	2.175	1.632	1.632	1.196	2039.8	1529.85	1529.85	1121.89
86	BDP298	BDP265LED94-4S830DM50	7520	65	115.692	2.281	2.281	1.711	1.711	1.254	2138.5	1603.875	1603.875	1176.175
87	BDP299	BDP265LED109-4S830DM50	8690	77	112.857	2.702	2.702	2.026	2.026	1.486	2533.3	1899.975	1899.975	1393.315
88	BDP300	BDP265LED6-4S827DM50	492	5.4	91.111	0.189	0.189	0.142	0.142	0.104	177.66	133.245	133.245	97.713
89	BDP301	BDP265LED8-4S827DM50	656	6.9	95.072	0.242	0.242	0.182	0.182	0.133	227.01	170.2575	170.2575	124.8555
90	BDP302	BDP265LED10-4S827DM50	820	8.4	97.619	0.295	0.295	0.221	0.221	0.162	276.36	207.27	207.27	151.998
91	BDP303	BDP265LED12-4S827DM50	984	9.7	101.443	0.340	0.340	0.255	0.255	0.187	319.13	239.3475	239.3475	175.5215
92	BDP304	BDP265LED14-4S827DM50	1148	11.2	102.500	0.393	0.393	0.295	0.295	0.216	368.48	276.36	276.36	202.664
93	BDP305	BDP265LED16-4S827DM50	1296	12.6	102.857	0.442	0.442	0.332	0.332	0.243	414.54	310.905	310.905	227.997
94	BDP306	BDP265LED18-4S827DM50	1458	14.4	101.250	0.505	0.505	0.379	0.379	0.278	473.76	355.32	355.32	260.568
95	BDP307	BDP265LED20-4S827DM50	1620	16	101.250	0.561	0.561	0.421	0.421	0.309	526.4	394.8	394.8	289.52
96	BDP308	BDP265LED22-4S827DM50	1782	17.6	101.250	0.618	0.618	0.463	0.463	0.340	579.04	434.28	434.28	318.472
97	BDP309	BDP265LED24-4S827DM50	1944	18.2	106.813	0.639	0.639	0.479	0.479	0.351	598.78	449.085	449.085	329.329
98	BDP310	BDP265LED27-4S827DM50	2187	20.5	106.683	0.719	0.719	0.539	0.539	0.396	674.45	505.8375	505.8375	370.9475
99	BDP311	BDP265LED30-4S827DM50	2430	22.5	108.000	0.789	0.789	0.592	0.592	0.434	740.25	555.1875	555.1875	407.1375
100	BDP312	BDP265LED34-4S827DM50	2754	26	105.923	0.912	0.912	0.684	0.684	0.502	855.4	641.55	641.55	470.47

PEP ECOPASSPORT ALIGNED

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management functions, the lumen output (O_{lum}) and reference service life (RSL) of each product within the same product family.

To calculate the Scaled Impact (SI_{pep}), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions P_{in} and the power input of the base variant P_{base} .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Using this scaled GWP, we then can apply the PEP Ecopassport method for calculating the environmental impact of the functional unit for a luminary (1000 lumens over 35000 hours), applied to B6, where the Functional Unit application considers the lumen output (O_{lum}) and reference service lifetime (RSL) of the product to estimate the final environmental impact. The scaled impact (SI_{pep}) is presented in Table A4.

$$GSF = \frac{FU_{pep}}{FU_p} = \frac{1,000}{O_{lum}} * \frac{35,000}{RSL}$$

3. Calculate the GWP scaling factor ($PGSF$), by multiplying the PSF by the GSF.

$$PGSF = PSF * GSF$$

- Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system), as presented in Table A1.

$$TSF = PGSF * CSF$$

Table 3: Light management functions (PEP EcoPassport aligned)

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

- Lastly, the GWP of the base variant is then scaled by the TSF.

$$Scaled\ GWP = GWP_{case} * TSF$$

Table 4: Impact per scaling factor (PEP EcoPassport aligned)

	12NC or Product Family Code	Description	Flux [Lm]	Power [W]	Efficacy [L/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
							NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
1	BDP265	BDP265LED8-4S740DM50	656	5.6	117.1	0.196	0.105	0.079	0.079	0.058	98.3	73.7	73.7	54.1
2	BDP265	BDP265LED10-4S740DM50	820	6.8	120.6	0.239	0.102	0.076	0.076	0.056	95.5	71.6	71.6	52.5
3	BDP265	BDP265LED12-4S740DM50	984	7.7	127.8	0.270	0.096	0.072	0.072	0.053	90.1	67.6	67.6	49.6
4	BDP265	BDP265LED14-4S740DM50	1148	8.9	129.0	0.312	0.095	0.071	0.071	0.052	89.3	67.0	67.0	49.1
5	BDP265	BDP265LED16-4S740DM50	1312	10.0	131.2	0.351	0.094	0.070	0.070	0.051	87.8	65.8	65.8	48.3
6	BDP265	BDP265LED18-4S740DM50	1476	11.2	131.8	0.393	0.093	0.070	0.070	0.051	87.4	65.5	65.5	48.1
7	BDP265	BDP265LED20-4S740DM50	1640	12.4	132.3	0.435	0.093	0.070	0.070	0.051	87.1	65.3	65.3	47.9
8	BDP265	BDP265LED22-4S740DM50	1782	13.6	131.0	0.5	0.1	0.1	0.1	0.1	87.9	65.9	65.9	48.3
9	BDP265	BDP265LED24-4S740DM50	1944	15.0	129.6	0.5	0.1	0.1	0.1	0.1	88.9	66.6	66.6	48.9
10	BDP265	BDP265LED27-4S740DM50	2187	17.0	128.6	0.6	0.1	0.1	0.1	0.1	89.5	67.1	67.1	49.2
11	BDP265	BDP265LED30-4S740DM50	2430	19.0	127.9	0.7	0.1	0.1	0.1	0.1	90.0	67.5	67.5	49.5
12	BDP265	BDP265LED34-4S740DM50	2754	20.0	137.7	0.7	0.1	0.1	0.1	0.0	83.6	62.7	62.7	46.0
13	BDP265	BDP265LED35-4S740DM50	2835	20.5	138.3	0.7	0.1	0.1	0.1	0.0	83.3	62.4	62.4	45.8
14	BDP265	BDP265LED39-4S740DM50	3159	23.0	137.3	0.8	0.1	0.1	0.1	0.0	83.8	62.9	62.9	46.1
15	BDP265	BDP265LED40-4S740DM50	3240	23.5	137.9	0.8	0.1	0.1	0.1	0.0	83.5	62.6	62.6	45.9
16	BDP265	BDP265LED44-4S740DM50	3564	26.0	137.1	0.9	0.1	0.1	0.1	0.0	84.0	63.0	63.0	46.2
17	BDP265	BDP265LED45-4S740DM50	3645	27.0	135.0	0.9	0.1	0.1	0.1	0.1	85.3	64.0	64.0	46.9
18	BDP265	BDP265LED50-4S740DM50	4050	28.5	142.1	1.0	0.1	0.1	0.1	0.0	81.0	60.8	60.8	44.6

19	BDP265	BDP265LED55-4S740DM50	4536	31.5	144.0	1.1	0.1	0.1	0.1	0.0	80.0	60.0	60.0	44.0
20	BDP265	BDP265LED59-4S740DM50	4860	33.5	145.1	1.2	0.1	0.1	0.1	0.0	79.4	59.5	59.5	43.7
21	BDP265	BDP265LED64-4S740DM50	5120	37.0	138.4	1.3	0.1	0.1	0.1	0.0	83.2	62.4	62.4	45.8
22	BDP265	BDP265LED69-4S740DM50	5600	40.0	140.0	1.4	0.1	0.1	0.1	0.0	82.3	61.7	61.7	45.2
23	BDP265	BDP265LED74-4S740DM50	5920	43.0	137.7	1.5	0.1	0.1	0.1	0.0	83.6	62.7	62.7	46.0
24	BDP265	BDP265LED79-4S740DM50	6240	44.5	140.2	1.6	0.1	0.1	0.1	0.0	82.1	61.6	61.6	45.2
25	BDP265	BDP265LED84-4S740DM50	6720	47.5	141.5	1.7	0.1	0.1	0.1	0.0	81.4	61.0	61.0	44.8
26	BDP265	BDP265LED90-4S740DM50	7200	51.0	141.2	1.8	0.1	0.1	0.1	0.0	81.6	61.2	61.2	44.9
27	BDP265	BDP265LED94-4S740DM50	7520	54.0	139.3	1.9	0.1	0.1	0.1	0.0	82.7	62.0	62.0	45.5
28	BDP265	BDP265LED109-4S740DM50	8800	63.0	139.7	2.2	0.1	0.1	0.1	0.0	82.4	61.8	61.8	45.3
29	BDP265	BDP265LED120-4S740DM50	9600	71.0	135.2	2.5	0.1	0.1	0.1	0.0	85.2	63.9	63.9	46.8
30	BDP265	BDP265LED130-4S740DM50	10270	77.0	133.4	2.7	0.1	0.1	0.1	0.1	86.3	64.8	64.8	47.5
31	BDP265	BDP265LED6-4S722DM50	492	5.6	87.9	0.2	0.1	0.1	0.1	0.1	131.1	98.3	98.3	72.1
32	BDP265	BDP265LED8-4S722DM50	656	7.1	92.4	0.2	0.1	0.1	0.1	0.1	124.6	93.5	93.5	68.5
33	BDP265	BDP265LED10-4S722DM50	810	8.8	92.0	0.3	0.1	0.1	0.1	0.1	125.1	93.8	93.8	68.8
34	BDP265	BDP265LED12-4S722DM50	984	10.0	98.4	0.4	0.1	0.1	0.1	0.1	117.0	87.8	87.8	64.4
35	BDP265	BDP265LED14-4S722DM50	1148	11.6	99.0	0.4	0.1	0.1	0.1	0.1	116.4	87.3	87.3	64.0
36	BDP265	BDP265LED16-4S722DM50	1296	13.2	98.2	0.5	0.1	0.1	0.1	0.1	117.3	88.0	88.0	64.5
37	BDP265	BDP265LED18-4S722DM50	1458	14.8	98.5	0.5	0.1	0.1	0.1	0.1	116.9	87.7	87.7	64.3
38	BDP265	BDP265LED20-4S722DM50	1620	16.6	97.6	0.6	0.1	0.1	0.1	0.1	118.0	88.5	88.5	64.9
39	BDP265	BDP265LED22-4S722DM50	1782	18.4	96.8	0.6	0.1	0.1	0.1	0.1	118.9	89.2	89.2	65.4
40	BDP265	BDP265LED24-4S722DM50	1944	20.5	94.8	0.7	0.1	0.1	0.1	0.1	121.4	91.1	91.1	66.8

41	BDP265	BDP265LED27-4S722DM50	2187	21.0	104.1	0.7	0.1	0.1	0.1	0.1	110.6	82.9	82.9	60.8
42	BDP265	BDP265LED30-4S722DM50	2430	23.5	103.4	0.8	0.1	0.1	0.1	0.1	111.4	83.5	83.5	61.2
43	BDP265	BDP265LED34-4S722DM50	2754	27.0	102.0	0.9	0.1	0.1	0.1	0.1	112.9	84.7	84.7	62.1
44	BDP265	BDP265LED35-4S722DM50	2835	27.5	103.1	1.0	0.1	0.1	0.1	0.1	111.7	83.8	83.8	61.4
45	BDP265	BDP265LED39-4S722DM50	3120	31.0	100.6	1.1	0.1	0.1	0.1	0.1	114.4	85.8	85.8	62.9
46	BDP265	BDP265LED40-4S722DM50	3200	32.0	100.0	1.1	0.1	0.1	0.1	0.1	115.2	86.4	86.4	63.3
47	BDP265	BDP265LED44-4S722DM50	3520	35.5	99.2	1.2	0.1	0.1	0.1	0.1	116.1	87.1	87.1	63.9
48	BDP265	BDP265LED45-4S722DM50	3600	36.5	98.6	1.3	0.1	0.1	0.1	0.1	116.7	87.6	87.6	64.2
49	BDP265	BDP265LED50-4S722DM50	4000	38.0	105.3	1.3	0.1	0.1	0.1	0.1	109.4	82.0	82.0	60.2
50	BDP265	BDP265LED55-4S722DM50	4480	42.5	105.4	1.5	0.1	0.1	0.1	0.1	109.2	81.9	81.9	60.1
51	BDP265	BDP265LED59-4S722DM50	4800	45.5	105.5	1.6	0.1	0.1	0.1	0.1	109.2	81.9	81.9	60.0
52	BDP265	BDP265LED64-4S722DM50	5120	50.0	102.4	1.8	0.1	0.1	0.1	0.1	112.5	84.3	84.3	61.8
53	BDP265	BDP265LED69-4S722DM50	5600	54.0	103.7	1.9	0.1	0.1	0.1	0.1	111.0	83.3	83.3	61.1
54	BDP266	BDP265LED74-4S722DM50	5846	59.0	99.1	2.1	0.1	0.1	0.1	0.1	116.2	87.2	87.2	63.9
55	BDP267	BDP265LED79-4S722DM50	6400	60.0	106.7	2.1	0.1	0.1	0.1	0.1	108.0	81.0	81.0	59.4
56	BDP268	BDP265LED84-4S722DM50	6720	65.0	103.4	2.3	0.1	0.1	0.1	0.1	111.4	83.5	83.5	61.3
57	BDP269	BDP265LED90-4S722DM50	7200	70.0	102.9	2.5	0.1	0.1	0.1	0.1	112.0	84.0	84.0	61.6
58	BDP270	BDP265LED94-4S722DM50	7426	74.0	100.4	2.6	0.1	0.1	0.1	0.1	114.7	86.1	86.1	63.1
59	BDP271	BDP265LED6-4S830DM50	492	5.0	98.4	0.2	0.1	0.1	0.1	0.1	117.0	87.8	87.8	64.4
60	BDP272	BDP265LED8-4S830DM50	656	6.5	100.9	0.2	0.1	0.1	0.1	0.1	114.1	85.6	85.6	62.8
61	BDP273	BDP265LED10-4S830DM50	820	7.9	103.8	0.3	0.1	0.1	0.1	0.1	110.9	83.2	83.2	61.0
62	BDP274	BDP265LED12-4S830DM50	984	9.1	108.1	0.3	0.1	0.1	0.1	0.1	106.5	79.9	79.9	58.6

63	BDP275	BDP265LED14-4S830DM50	1148	10.4	110.4	0.4	0.1	0.1	0.1	0.1	104.3	78.2	78.2	57.4
64	BDP276	BDP265LED16-4S830DM50	1312	11.8	111.2	0.4	0.1	0.1	0.1	0.1	103.6	77.7	77.7	57.0
65	BDP277	BDP265LED18-4S830DM50	1458	13.2	110.5	0.5	0.1	0.1	0.1	0.1	104.3	78.2	78.2	57.3
66	BDP278	BDP265LED20-4S830DM50	1620	14.8	109.5	0.5	0.1	0.1	0.1	0.1	105.2	78.9	78.9	57.9
67	BDP279	BDP265LED22-4S830DM50	1782	16.4	108.7	0.6	0.1	0.1	0.1	0.1	106.0	79.5	79.5	58.3
68	BDP280	BDP265LED24-4S830DM50	1944	18.0	108.0	0.6	0.1	0.1	0.1	0.1	106.6	80.0	80.0	58.6
69	BDP281	BDP265LED27-4S830DM50	2187	19.0	115.1	0.7	0.1	0.1	0.1	0.1	100.0	75.0	75.0	55.0
70	BDP282	BDP265LED30-4S830DM50	2430	21.0	115.7	0.7	0.1	0.1	0.1	0.1	99.5	74.6	74.6	54.7
71	BDP283	BDP265LED34-4S830DM50	2754	24.0	114.8	0.8	0.1	0.1	0.1	0.1	100.3	75.3	75.3	55.2
72	BDP284	BDP265LED35-4S830DM50	2835	24.5	115.7	0.9	0.1	0.1	0.1	0.1	99.5	74.6	74.6	54.7
73	BDP285	BDP265LED39-4S830DM50	3159	27.5	114.9	1.0	0.1	0.1	0.1	0.1	100.2	75.2	75.2	55.1
74	BDP286	BDP265LED40-4S830DM50	3240	28.5	113.7	1.0	0.1	0.1	0.1	0.1	101.3	76.0	76.0	55.7
75	BDP287	BDP265LED44-4S830DM50	3520	31.5	111.7	1.1	0.1	0.1	0.1	0.1	103.0	77.3	77.3	56.7
76	BDP288	BDP265LED45-4S830DM50	3600	32.0	112.5	1.1	0.1	0.1	0.1	0.1	102.4	76.8	76.8	56.3
77	BDP289	BDP265LED50-4S830DM50	4000	36.0	111.1	1.3	0.1	0.1	0.1	0.1	103.6	77.7	77.7	57.0
78	BDP290	BDP265LED55-4S830DM50	4480	37.5	119.5	1.3	0.1	0.1	0.1	0.1	96.4	72.3	72.3	53.0
79	BDP291	BDP265LED59-4S830DM50	4800	40.5	118.5	1.4	0.1	0.1	0.1	0.1	97.2	72.9	72.9	53.4
80	BDP292	BDP265LED64-4S830DM50	5120	44.5	115.1	1.6	0.1	0.1	0.1	0.1	100.1	75.1	75.1	55.0
81	BDP293	BDP265LED69-4S830DM50	5600	48.0	116.7	1.7	0.1	0.1	0.1	0.1	98.7	74.0	74.0	54.3
82	BDP294	BDP265LED74-4S830DM50	5920	52.0	113.8	1.8	0.1	0.1	0.1	0.1	101.1	75.9	75.9	55.6
83	BDP295	BDP265LED79-4S830DM50	6400	54.0	118.5	1.9	0.1	0.1	0.1	0.1	97.2	72.9	72.9	53.4
84	BDP296	BDP265LED84-4S830DM50	6720	57.0	117.9	2.0	0.1	0.1	0.1	0.1	97.7	73.3	73.3	53.7

85	BDP297	BDP265LED90-4S830DM50	7200	62.0	116.1	2.2	0.1	0.1	0.1	0.1	99.2	74.4	74.4	54.5
86	BDP298	BDP265LED94-4S830DM50	7520	65.0	115.7	2.3	0.1	0.1	0.1	0.1	99.5	74.6	74.6	54.7
87	BDP299	BDP265LED109-4S830DM50	8690	77.0	112.9	2.7	0.1	0.1	0.1	0.1	102.0	76.5	76.5	56.1
88	BDP300	BDP265LED6-4S827DM50	492	5.4	91.1	0.2	0.1	0.1	0.1	0.1	126.4	94.8	94.8	69.5
89	BDP301	BDP265LED8-4S827DM50	656	6.9	95.1	0.2	0.1	0.1	0.1	0.1	121.1	90.8	90.8	66.6
90	BDP302	BDP265LED10-4S827DM50	820	8.4	97.6	0.3	0.1	0.1	0.1	0.1	118.0	88.5	88.5	64.9
91	BDP303	BDP265LED12-4S827DM50	984	9.7	101.4	0.3	0.1	0.1	0.1	0.1	113.5	85.1	85.1	62.4
92	BDP304	BDP265LED14-4S827DM50	1148	11.2	102.5	0.4	0.1	0.1	0.1	0.1	112.3	84.3	84.3	61.8
93	BDP305	BDP265LED16-4S827DM50	1296	12.6	102.9	0.4	0.1	0.1	0.1	0.1	112.0	84.0	84.0	61.6
94	BDP306	BDP265LED18-4S827DM50	1458	14.4	101.3	0.5	0.1	0.1	0.1	0.1	113.7	85.3	85.3	62.6
95	BDP307	BDP265LED20-4S827DM50	1620	16.0	101.3	0.6	0.1	0.1	0.1	0.1	113.7	85.3	85.3	62.6
96	BDP308	BDP265LED22-4S827DM50	1782	17.6	101.3	0.6	0.1	0.1	0.1	0.1	113.7	85.3	85.3	62.6
97	BDP309	BDP265LED24-4S827DM50	1944	18.2	106.8	0.6	0.1	0.1	0.1	0.1	107.8	80.9	80.9	59.3
98	BDP310	BDP265LED27-4S827DM50	2187	20.5	106.7	0.7	0.1	0.1	0.1	0.1	107.9	81.0	81.0	59.4
99	BDP311	BDP265LED30-4S827DM50	2430	22.5	108.0	0.8	0.1	0.1	0.1	0.1	106.6	80.0	80.0	58.6
100	BDP312	BDP265LED34-4S827DM50	2754	26.0	105.9	0.9	0.1	0.1	0.1	0.1	108.7	81.5	81.5	59.8