

ENVIRONMENTAL PRODUCT DECLARATION

IN ACCORDANCE WITH EN 15804+A2 & ISO 14025

UrbanFlex small BGP/BPP/BRP/BVP730

Signify N.V.



MANUFACTURER AND SITE

Manufacturer	Signify N.V.
Address	High Tech Campus 48, 5656 AE Eindhoven, The Netherlands
Contact details	sustainability@signify.com
Website	https://www.signify.com/global
Place of production	VALLADOLID, SPAIN
Place(s) of raw material origin	APAC, EU
Place(s) of installation and use	EU
Period for data	Calendar Year 2023

EPD STANDARDS, SCOPE AND VERIFICATION

Program operator	EPD Hub, hub@epdhub.com
Reference standard	EN 15804:2012+A2:2019/AC:2021 and ISO 14025
PCR	EPD Hub Core PCR version 1.2, 24 Mar 2025
Sector	Electrical product
Category of EPD	Third party verified EPD
Scope of the EPD	Cradle to gate with options, A4-A5, B6, and modules C1-C4, D
EPD author	Signify / Sustainability
EPD verification	Independent verification of this EPD and data, according to ISO 14025: ☐ Internal verification ☒ External verification
EPD verifier	Haiha Nguyen as an authorized verifier for EPD Hub

PRODUCT SPECIFICATION

Product name	UrbanFlex small BGP/BPP/BRP/BVP730
Product number / reference	912300060121 / BPP730 LED100-4S/722 II PSD D9 DM11 FG S
GTIN (Global Trade Item Number)	Not applicable
NOBB (Norwegian Building Product Database)	Not applicable
A1-A3 Specific data (%)	2.53

PRODUCT DESCRIPTION

Cities want to be attractive, welcoming, and safe places where residents thrive, businesses prosper, and people love to visit. It's the reason we designed UrbanFlex - a flexible street lighting solution for all types of urban applications. UrbanFlex is designed for customers looking for ways to achieve uniformity in design and quality of light with elegant, energy efficient and sustainable products. The UrbanFlex signature style is modern and flawless to give your cityscape a visually coherent, elegant and distinctive identity. Available in two popular sizes, it also comes with a range of mountings and dedicated brackets and poles. And because we're conscious about the impact of light on the environment and biodiversity, we have also equipped UrbanFlex with our dedicated light recipe to preserve dark skies. Thanks to the built in LEDGINE-O platform, and the wide range of application-tailored optics, UrbanFlex delivers best-in-class performance in a broad range of city lighting applications. By being System Ready, this luminaire offers connectivity and dimming options, while it can be paired with lighting management systems like Interact, and any existing and upcoming sensors innovations. In addition, every UrbanFlex luminaire is uniquely identifiable, thanks to the Signify Service tag app, making maintenance and programming operations faster and easier, and enabling you to create a digital library of lighting assets and spare parts.

This EPD is intended for business-to-business and/or business-to-consumer communication. Life Cycle Assessment study has been performed in accordance with the requirements of EN 15804, EPD Hub PCR version 1.2 (24 Mar 2025) and JRC characterization factors EF 3.1. The manufacturer has the sole ownership, liability, and responsibility for the EPD. EPDs within the same product category but from different programs may not be comparable. EPDs of construction products may not be comparable if they do not comply with EN 15804 and if they are not compared in a building context.

PRODUCT CLASSIFICATION

Declared operating voltage, Volt	220-240
Light source colour temperature, Kelvin	2200
Protection index for water and dust (IP)	66
Impact resistance index (IK)	9
Luminous flux, Lumens	8800
Electrical power, Watt	85
Luminous efficiency, Lm/W	104
Additional characteristic	Not applicable

ABOUT THE MANUFACTURER

Signify is the world leader in lighting for professionals, consumers and lighting for the Internet of Things. Our energy efficient lighting products, systems and services enable our customers to enjoy a superior quality of light, and make people's lives safer and more comfortable, businesses more productive and cities more liveable.

For more information, please visit: <https://www.signify.com/global>

PRODUCT RAW MATERIAL MAIN COMPOSITION

Raw material category	Amount, mass- %	Material origin
Metals	72.72	APAC , EU
Minerals	12.52	APAC , EU
Fossil materials	14.76	APAC , EU
Bio-based materials	0	EU

BIOGENIC CARBON CONTENT

Product's biogenic carbon content at the factory gate

Biogenic carbon content in product, kg C	0
Biogenic carbon content in packaging, kg C	1.208

ENVIRONMENTAL DATA SUMMARY

Declared unit	1 unit
Declared unit mass, kg	8.453
Mass of packaging, kg	3.103
Functional unit (from PEP PSR0014)	Provide lighting that delivers an outgoing artificial luminous flux of 1000 lumens during a reference lifetime of 35000 hours
Reference service life (years)	25
Assigned lifetime (hours)	100000
GWP-total, A1-A3 (kg CO ₂ e)	88.8
GWP-fossil, A1-A3 (kg CO ₂ e)	92.4
Secondary material, inputs (%)	42.3
Secondary material, outputs (%)	56.1
Total energy use, A1-A3 (kWh)	310
Net freshwater use, A1-A3 (m ³)	4.66E-01

LIFE CYCLE ASSESSMENT

SYSTEM BOUNDARY

This EPD covers the life-cycle modules listed in the following table.

Product stage			Installation stage		Use stage							End of life stage				Beyond the system
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	ND	ND	ND	ND	ND	X	ND	X	X	X	X	X
Raw materials	Transport	Manufacturing	Transport	Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	Deconstr./demo.	Transport	Waste processing	Disposal	Reuse, Recovery, Recycling

Modules not declared = ND.

CUT - OFF CRITERIA

The study does not exclude any modules or processes which are stated mandatory in the reference standard and the applied PCR. The study does not exclude any hazardous materials or substances. There is no neglected unit process more than 1% of total mass or energy flows. The module-specific total neglected input and output flows also do not exceed 5% of energy usage or mass.

The production of capital equipment, construction activities, and infrastructure, maintenance and operation of capital equipment, personnel-related activities, energy and water use related to company management and sales activities are excluded.

VALIDATION OF DATA

Data collection for production, transport, and packaging was conducted using time and site-specific information, as defined in the general information section on page 1 and 2. Upstream process calculations rely on generic data as defined in the Bibliography section. Manufacturer-provided specific and generic data were used for the product's manufacturing stage. The analysis was performed in One Click LCA EPD Generator, with the 'Cut-Off, EN 15804+A2' allocation method, and characterization factors according to EN 15804:2012+A2:2019/AC:2021 and JRC EF 3.1.

ALLOCATION, ESTIMATES AND ASSUMPTIONS

Allocation is required if some material, energy, and waste data cannot be measured separately for the product under investigation. All allocations are done as per the reference standards and the applied PCR. In this study, ancillary materials, energy & water consumption, material loss and waste generation at the manufacturing site are attributed to the bill of materials of the products, therefore, they are allocated by partitioning the quantities on the base of the total production in kg throughout the year. Thus, allocation has been done in the following ways:

Data type	Allocation
Raw materials	No allocation
Packaging materials	No allocation
Ancillary materials	Allocated by mass
Manufacturing energy and waste	Allocated by mass

Proxy data is used for certain materials due to their unavailability in the database. Conservative choices have been adopted when exact information was missing. Regarding module C1-C4: EOL scenarios are based on default values from EN 50693. For stages description please refer to section Product life cycle in this EPD report.

LCA SOFTWARE AND BIBLIOGRAPHY

This EPD has been created using One Click LCA Luminaire EPD Generator v2.2.7. The LCA and EPD have been prepared according to the reference standards, EN 50693, and ISO 14040/14044. Ecoinvent v 3.10.1 and One Click LCA databases were used as sources of environmental data. Allocation used in Ecoinvent 3.10.1 environmental data sources follow the methodology 'allocation, cut-off, EN 15804+A2'.

No other sources were used in the modelling of this EPD.

PRODUCT & MANUFACTURING SITES GROUPING

Type of grouping	No grouping
Grouping method	Not applicable
Variation in GWP-fossil for A1-A3, %	Not applicable

SUBSTANCES, REACH - VERY HIGH CONCERN

The product does not contain any REACH SVHC substances in amounts greater than 0,1 % (1000 ppm).

PRODUCT LIFE CYCLE

MANUFACTURING AND PACKAGING (A1-A3)

The environmental impacts considered for the product stage cover the manufacturing of raw materials used in the production. The material losses occurring during the manufacturing processes are treated as per the waste handling practices in the factory, while scenario assumptions are made in the absence of exact data. The study also considers the fuels used by machines as well as losses during electricity transmission.

The product is made of metals, plastics, and electronic components. All components are transported to the production facility, where the main manufacturing processes primarily are associated with assembly. A2 transport distances are calculated always taking the capital city of component country of origin as a starting point and exact manufacturing location as destination. The finished product can be packaged with polyethylene, cardboard, and/or paper as packaging material before shipment to customers. Manufacturing loss, ancillaries and wastes are calculated according to the data that each manufacturing site is sharing with Signify. The total annual amount of waste in kg is allocated to the total annual production in kg at the specific manufacturing site responsible to produce the studied product. Thus, it is possible to allocate it according to the weight of the product analysed in this study.

Co-product allocation is neglected as revenue of co-product is very low, hence, the waste undergoes a conservative waste treatment.

The use of green energy in manufacturing is demonstrated through contractual instruments (GOs, RECs, etc), and its use is ensured throughout the validity period of this EPD.

TRANSPORT AND INSTALLATION (A4-A5)

A4 transport distances are calculated always taking the exact manufacturing location to customer location. If the customer's location is defined as a country or its capital city, the calculation is made to the respective capital city. If the

customer's location is specified as a region, the distance is calculated to the capital city of the best-performing sales country within that region. The transportation method is a combination of lorry and container ship where needed. To be conservative, empty returns are included in this study as implemented through an average load factor in the Ecoinvent transport datapoints. Environmental impacts from installation include waste packaging materials (A5). The packaging waste treatment is assumed to be conservative with incineration without energy recovery. The impacts of energy consumption and the used ancillary materials during installation are considered negligible.

PRODUCT USE AND MAINTENANCE (B1-B7)

During the use phase, the product consumes electricity (B6), which is calculated multiplying the Wattage x Assigned lifetime (hours) x Country energy mix factor. To know which Country energy mix was used in this EPD, please refer to Annex 2.

The Reference service life in years is calculated according to the main application type of the product, based on annual operating hours. Impacts due to electricity production include direct emissions to air, transformation, and transmission losses.

PRODUCT END OF LIFE (C1-C4, D)

Consumption of energy and natural resources in demolition process is assumed to be negligible. It is assumed that the waste is collected separately and transported to the waste treatment centre. The transport distance is 150 km while the transportation method is assumed to be lorry (C2). According to EN 50693:2019, the sequence of treatment operations occurring to the product shall include de-pollution, fractions separation and preparation (dismantling, crushing, shredding, sorting), recycling, other material recovery, energy recovery and disposal. In this study, the default values from table G.4 of EN 50693 is used for treating materials in different waste treatment methods. Due to the material and energy recovery potential of parts in the lighting system, the end-of-life product is converted into recycled raw materials, while the energy recovered from incineration displaces electricity and heat production (D). The benefits and loads of incineration and recycling are included in Module D.

LIFE CYCLE FLOW DIAGRAM - SYSTEM BOUNDARY



ENVIRONMENTAL IMPACT DATA, RESULTS PER DECLARED UNIT

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ e	8.75E+01	3.74E-01	9.19E-01	8.88E+01	3.44E+00	4.73E+00	ND	ND	ND	ND	ND	2.80E+03	ND	0.00E+00	2.49E-01	6.04E-01	8.91E-02	-1.39E+01
GWP – fossil	kg CO ₂ e	8.71E+01	3.74E-01	4.98E+00	9.24E+01	3.43E+00	3.16E-01	ND	ND	ND	ND	ND	2.78E+03	ND	0.00E+00	2.49E-01	6.05E-01	6.19E-01	-1.38E+01
GWP – biogenic	kg CO ₂ e	2.65E-01	7.56E-05	-4.16E+00	-3.89E+00	7.78E-04	4.41E+00	ND	ND	ND	ND	ND	6.24E+00	ND	0.00E+00	5.44E-05	-4.25E-04	-5.30E-01	-3.17E-03
GWP – LULUC	kg CO ₂ e	1.36E-01	1.80E-04	1.00E-01	2.37E-01	1.54E-03	7.21E-05	ND	ND	ND	ND	ND	8.54E+00	ND	0.00E+00	1.10E-04	1.61E-04	1.06E-04	-3.23E-03
Ozone depletion pot.	kg CFC ₁₁ e	1.49E-06	5.47E-09	1.18E-07	1.61E-06	5.07E-08	2.69E-09	ND	ND	ND	ND	ND	5.13E-05	ND	0.00E+00	3.48E-09	1.51E-09	1.47E-09	-5.20E-08
Acidification potential	mol H ⁺ e	6.21E-01	4.65E-03	2.28E-02	6.49E-01	1.17E-02	1.17E-03	ND	ND	ND	ND	ND	1.64E+01	ND	0.00E+00	8.31E-04	1.39E-03	6.12E-04	-1.54E-01
EP-freshwater ²⁾	kg Pe	3.50E-02	2.31E-05	2.02E-03	3.70E-02	2.67E-04	1.97E-05	ND	ND	ND	ND	ND	2.59E+00	ND	0.00E+00	1.94E-05	6.77E-05	9.15E-05	-8.20E-03
EP-marine	kg Ne	9.54E-02	1.22E-03	1.05E-02	1.07E-01	3.85E-03	5.48E-04	ND	ND	ND	ND	ND	2.57E+00	ND	0.00E+00	2.69E-04	3.48E-04	1.96E-03	-1.81E-02
EP-terrestrial	mol Ne	1.00E+00	1.35E-02	6.41E-02	1.08E+00	4.19E-02	4.99E-03	ND	ND	ND	ND	ND	2.30E+01	ND	0.00E+00	2.93E-03	3.73E-03	2.43E-03	-1.88E-01
POCP (“smog”) ³⁾	kg NMVOCe	3.35E-01	4.08E-03	2.29E-02	3.62E-01	1.73E-02	1.42E-03	ND	ND	ND	ND	ND	7.57E+00	ND	0.00E+00	1.16E-03	1.08E-03	9.17E-04	-5.66E-02
ADP-minerals & metals ⁴⁾	kg Sbe	3.02E-03	8.08E-07	2.30E-05	3.04E-03	9.58E-06	5.83E-07	ND	ND	ND	ND	ND	3.76E-02	ND	0.00E+00	8.18E-07	6.81E-06	2.10E-07	-3.18E-04
ADP-fossil resources	MJ	9.86E+02	5.13E+00	6.88E+01	1.06E+03	4.98E+01	2.02E+00	ND	ND	ND	ND	ND	6.47E+04	ND	0.00E+00	3.50E+00	1.58E+00	1.31E+00	-1.40E+02
Water use ⁵⁾	m ³ e depr.	2.36E+01	2.19E-02	1.80E+00	2.54E+01	2.46E-01	2.37E-01	ND	ND	ND	ND	ND	1.76E+03	ND	0.00E+00	1.62E-02	5.49E-02	3.65E-02	-1.15E+00

1) GWP = Global Warming Potential. 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO₄e. 3) POCP = Photochemical ozone formation. 4) ADP = Abiotic depletion potential. 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence	6.65E-06	2.83E-08	4.07E-07	7.09E-06	3.44E-07	1.44E-08	ND	ND	ND	ND	ND	5.83E-05	ND	0.00E+00	1.98E-08	1.83E-08	1.01E-08	-7.42E-07
Ionizing radiation ⁶⁾	kBq U235e	3.37E+00	3.80E-03	2.48E-01	3.63E+00	4.34E-02	2.46E-03	ND	ND	ND	ND	ND	1.79E+03	ND	0.00E+00	2.83E-03	5.91E-03	2.26E-03	-7.96E-01
Ecotoxicity (freshwater)	CTUe	6.61E+02	6.19E-01	2.54E+01	6.87E+02	7.05E+00	5.72E+00	ND	ND	ND	ND	ND	9.86E+03	ND	0.00E+00	5.53E-01	1.78E+00	1.65E+02	-4.20E+01
Human toxicity, cancer	CTUh	6.38E-08	6.79E-11	2.59E-09	6.64E-08	5.67E-10	2.74E-10	ND	ND	ND	ND	ND	9.40E-07	ND	0.00E+00	4.24E-11	1.36E-10	4.16E-10	-6.43E-09
Human tox. non-cancer	CTUh	1.77E-06	2.68E-09	6.76E-08	1.84E-06	3.23E-08	1.11E-08	ND	ND	ND	ND	ND	4.88E-05	ND	0.00E+00	2.19E-09	7.49E-09	1.10E-08	-3.09E-07
SQP ⁷⁾	-	2.95E+02	3.70E+00	2.55E+02	5.53E+02	5.02E+01	9.87E-01	ND	ND	ND	ND	ND	1.44E+04	ND	0.00E+00	2.09E+00	2.67E+00	1.93E+00	-2.95E+01

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ	8.71E+01	6.07E-02	1.00E+01	9.72E+01	6.83E-01	-5.42E+01	ND	ND	ND	ND	ND	1.78E+04	ND	0.00E+00	4.79E-02	2.26E-01	-9.80E+00	-3.65E+00
Renew. PER as material	MJ	2.50E+00	0.00E+00	3.64E+01	3.89E+01	0.00E+00	-3.89E+01	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-1.03E-02	-1.52E-02	0.00E+00
Total use of renew. PER	MJ	8.96E+01	6.07E-02	4.65E+01	1.36E+02	6.83E-01	-9.31E+01	ND	ND	ND	ND	ND	1.78E+04	ND	0.00E+00	4.79E-02	2.16E-01	-9.82E+00	-3.65E+00
Non-re. PER as energy	MJ	9.54E+02	5.14E+00	5.90E+01	1.02E+03	4.98E+01	1.32E-01	ND	ND	ND	ND	ND	6.47E+04	ND	0.00E+00	3.50E+00	-5.89E+00	-1.42E+01	-1.40E+02
Non-re. PER as material	MJ	2.43E+01	0.00E+00	5.87E-01	2.49E+01	0.00E+00	-2.52E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-5.32E+00	-1.71E+01	0.00E+00
Total use of non-re. PER	MJ	9.78E+02	5.14E+00	5.96E+01	1.04E+03	4.98E+01	-2.39E+00	ND	ND	ND	ND	ND	6.47E+04	ND	0.00E+00	3.50E+00	-1.12E+01	-3.13E+01	-1.40E+02
Secondary materials	kg	3.58E+00	0.00E+00	0.00E+00	3.58E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renew. secondary fuels	MJ	3.22E-02	2.08E-05	3.36E-01	3.69E-01	2.69E-04	2.54E-05	ND	ND	ND	ND	ND	8.55E-02	ND	0.00E+00	2.00E-05	7.71E-05	1.63E-05	-4.05E-04
Non-ren. secondary fuels	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³	4.25E-01	6.32E-04	4.03E-02	4.66E-01	7.37E-03	3.85E-03	ND	ND	ND	ND	ND	5.59E+01	ND	0.00E+00	4.63E-04	9.33E-04	-7.79E-03	-5.15E-02

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg	1.52E+01	8.11E-03	2.87E-01	1.55E+01	8.44E-02	6.23E-02	ND	ND	ND	ND	ND	1.64E+02	ND	0.00E+00	6.09E-03	1.95E-02	2.86E-02	-2.82E+00
Non-hazardous waste	kg	2.77E+02	1.40E-01	1.49E+01	2.92E+02	1.56E+00	3.32E+00	ND	ND	ND	ND	ND	1.27E+04	ND	0.00E+00	1.14E-01	8.71E-01	1.41E+01	-2.93E+01
Radioactive waste	kg	8.38E-04	9.30E-07	5.88E-05	8.98E-04	1.06E-05	6.15E-07	ND	ND	ND	ND	ND	4.59E-01	ND	0.00E+00	6.93E-07	1.45E-06	5.55E-07	-1.92E-04

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for reuse	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	1.02E-01	1.02E-01	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	4.74E+00	0.00E+00	0.00E+00
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	2.31E+00	0.00E+00	0.00E+00
Exported energy – Electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	9.73E-01	0.00E+00	0.00E+00
Exported energy – Heat	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	1.34E+00	0.00E+00	0.00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ e	8.70E+01	3.72E-01	5.41E+00	9.28E+01	3.41E+00	3.15E-01	ND	ND	ND	ND	ND	2.78E+03	ND	0.00E+00	2.48E-01	6.04E-01	1.17E+00	-1.38E+01
Ozone depletion Pot.	kg CFC-11e	1.26E-06	4.36E-09	1.22E-07	1.39E-06	4.04E-08	2.29E-09	ND	ND	ND	ND	ND	4.28E-05	ND	0.00E+00	2.78E-09	1.26E-09	1.19E-09	-4.82E-08
Acidification	kg SO ₂ e	5.24E-01	3.68E-03	1.57E-02	5.43E-01	8.94E-03	8.59E-04	ND	ND	ND	ND	ND	1.39E+01	ND	0.00E+00	6.36E-04	1.11E-03	4.50E-04	-1.33E-01
Eutrophication	kg PO ₄ ³ e	1.11E-01	4.89E-04	1.31E-02	1.25E-01	2.18E-03	2.67E-04	ND	ND	ND	ND	ND	1.80E+00	ND	0.00E+00	1.55E-04	1.76E-04	1.08E-03	-8.15E-03
POCP ("smog")	kg C ₂ H ₄ e	4.06E-02	2.08E-04	1.78E-03	4.26E-02	7.97E-04	6.53E-05	ND	ND	ND	ND	ND	7.60E-01	ND	0.00E+00	5.70E-05	6.62E-05	1.59E-04	-7.63E-03
ADP-elements	kg Sbe	3.00E-03	7.90E-07	2.26E-05	3.02E-03	9.34E-06	4.86E-07	ND	ND	ND	ND	ND	3.74E-02	ND	0.00E+00	7.99E-07	6.78E-06	1.96E-07	-3.16E-04
ADP-fossil	MJ	9.31E+02	5.08E+00	6.48E+01	1.00E+03	4.91E+01	1.98E+00	ND	ND	ND	ND	ND	3.32E+04	ND	0.00E+00	3.45E+00	1.49E+00	1.28E+00	-1.28E+02

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG 9)	kg CO ₂ e	8.72E+01	3.74E-01	5.08E+00	9.27E+01	3.43E+00	3.16E-01	ND	ND	ND	ND	ND	2.79E+03	ND	0.00E+00	2.49E-01	6.05E-01	6.19E-01	-1.39E+01

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows - CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide - were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO₂ is set to zero.

ENVIRONMENTAL IMPACT DATA, RESULTS PER FUNCTIONAL UNIT

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ¹⁾	kg CO ₂ éq/FU	3.48E+00	1.49E-02	3.66E-02	3.53E+00	1.37E-01	1.88E-01	ND	ND	ND	ND	ND	1.11E+02	ND	0.00E+00	9.92E-03	2.40E-02	3.55E-03	-5.51E-01
GWP – fossil	kg CO ₂ éq/FU	3.46E+00	1.49E-02	1.98E-01	3.68E+00	1.37E-01	1.26E-02	ND	ND	ND	ND	ND	1.11E+02	ND	0.00E+00	9.91E-03	2.40E-02	2.46E-02	-5.51E-01
GWP – biogenic	kg CO ₂ éq/FU	1.05E-02	3.01E-06	-1.65E-01	-1.55E-01	3.09E-05	1.75E-01	ND	ND	ND	ND	ND	2.48E-01	ND	0.00E+00	2.16E-06	-1.69E-05	-2.11E-02	-1.26E-04
GWP – LULUC	kg CO ₂ éq/FU	5.42E-03	7.14E-06	3.99E-03	9.41E-03	6.11E-05	2.87E-06	ND	ND	ND	ND	ND	3.40E-01	ND	0.00E+00	4.39E-06	6.41E-06	4.20E-06	-1.28E-04
Ozone depletion pot.	kg CFC-11e/FU	5.92E-08	2.18E-10	4.69E-09	6.42E-08	2.02E-09	1.07E-10	ND	ND	ND	ND	ND	2.04E-06	ND	0.00E+00	1.39E-10	6.01E-11	5.85E-11	-2.07E-09
Acidification potential	mole H ⁺ e/FU	2.47E-02	1.85E-04	9.05E-04	2.58E-02	4.66E-04	4.65E-05	ND	ND	ND	ND	ND	6.51E-01	ND	0.00E+00	3.30E-05	5.52E-05	2.43E-05	-6.11E-03
EP-freshwater ²⁾	kg Pe/FU	1.39E-03	9.19E-07	8.03E-05	1.47E-03	1.06E-05	7.84E-07	ND	ND	ND	ND	ND	1.03E-01	ND	0.00E+00	7.71E-07	2.69E-06	3.64E-06	-3.26E-04
EP-marine	kg Ne/FU	3.80E-03	4.86E-05	4.17E-04	4.26E-03	1.53E-04	2.18E-05	ND	ND	ND	ND	ND	1.02E-01	ND	0.00E+00	1.07E-05	1.38E-05	7.78E-05	-7.18E-04
EP-terrestrial	mol Ne/FU	3.98E-02	5.38E-04	2.55E-03	4.29E-02	1.66E-03	1.98E-04	ND	ND	ND	ND	ND	9.15E-01	ND	0.00E+00	1.16E-04	1.48E-04	9.65E-05	-7.48E-03
POCP (“smog”) ³⁾	kg NMVOCe/	1.33E-02	1.62E-04	9.09E-04	1.44E-02	6.86E-04	5.64E-05	ND	ND	ND	ND	ND	3.01E-01	ND	0.00E+00	4.60E-05	4.29E-05	3.65E-05	-2.25E-03
ADP-minerals & metals ⁴⁾	kg Sbe/FU	1.20E-04	3.21E-08	9.15E-07	1.21E-04	3.81E-07	2.32E-08	ND	ND	ND	ND	ND	1.49E-03	ND	0.00E+00	3.26E-08	2.71E-07	8.35E-09	-1.26E-05
ADP-fossil resources	MJ/FU	3.92E+01	2.04E-01	2.74E+00	4.22E+01	1.98E+00	8.04E-02	ND	ND	ND	ND	ND	2.57E+03	ND	0.00E+00	1.39E-01	6.29E-02	5.22E-02	-5.59E+00
Water use ⁵⁾	m ³ e priv. /FU	9.37E-01	8.73E-04	7.14E-02	1.01E+00	9.79E-03	9.43E-03	ND	ND	ND	ND	ND	7.02E+01	ND	0.00E+00	6.45E-04	2.18E-03	1.45E-03	-4.58E-02

1) GWP = Global Warming Potential. 2) EP = Eutrophication potential. Required characterisation method and data are in kg P-eq. Multiply by 3,07 to get PO4e. 3) POCP = Photochemical ozone formation. 4) ADP = Abiotic depletion potential. 5) EN 15804+A2 disclaimer for Abiotic depletion and Water use and optional indicators except Particulate matter and Ionizing radiation, human health. The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

ADDITIONAL (OPTIONAL) ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Particulate matter	Incidence /FU	2.64E-07	1.13E-09	1.62E-08	2.82E-07	1.37E-08	5.74E-10	ND	ND	ND	ND	ND	2.32E-06	ND	0.00E+00	7.87E-10	7.30E-10	4.00E-10	-2.95E-08
Ionizing radiation ⁶⁾	kBq U235e/FU	1.34E-01	1.51E-04	9.85E-03	1.44E-01	1.73E-03	9.77E-05	ND	ND	ND	ND	ND	7.11E+01	ND	0.00E+00	1.13E-04	2.35E-04	8.99E-05	-3.17E-02
Ecotoxicity (freshwater)	CTUe/FU	2.63E+01	2.46E-02	1.01E+00	2.73E+01	2.80E-01	2.27E-01	ND	ND	ND	ND	ND	3.92E+02	ND	0.00E+00	2.20E-02	7.07E-02	6.56E+00	-1.67E+00
Human toxicity, cancer	CTUh/FU	2.54E-09	2.70E-12	1.03E-10	2.64E-09	2.25E-11	1.09E-11	ND	ND	ND	ND	ND	3.74E-08	ND	0.00E+00	1.69E-12	5.40E-12	1.65E-11	-2.56E-10
Human tox. non-cancer	CTUh/FU	7.02E-08	1.07E-10	2.69E-09	7.30E-08	1.28E-09	4.43E-10	ND	ND	ND	ND	ND	1.94E-06	ND	0.00E+00	8.70E-11	2.98E-10	4.37E-10	-1.23E-08
SQP ⁷⁾	-/FU	1.17E+01	1.47E-01	1.01E+01	2.20E+01	2.00E+00	3.93E-02	ND	ND	ND	ND	ND	5.73E+02	ND	0.00E+00	8.30E-02	1.06E-01	7.69E-02	-1.17E+00

USE OF NATURAL RESOURCES

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Renew. PER as energy ⁸⁾	MJ/FU	3.46E+00	2.42E-03	3.99E-01	3.87E+00	2.72E-02	-2.15E+00	ND	ND	ND	ND	ND	7.06E+02	ND	0.00E+00	1.91E-03	9.00E-03	-3.90E-01	-1.45E-01
Renew. PER as material	MJ/FU	9.96E-02	0.00E+00	1.45E+00	1.55E+00	0.00E+00	-1.55E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-4.08E-04	-6.06E-04	0.00E+00
Total use of renew. PER	MJ/FU	3.56E+00	2.42E-03	1.85E+00	5.42E+00	2.72E-02	-3.70E+00	ND	ND	ND	ND	ND	7.06E+02	ND	0.00E+00	1.91E-03	8.59E-03	-3.90E-01	-1.45E-01
Non-re. PER as energy	MJ/FU	3.79E+01	2.04E-01	2.35E+00	4.05E+01	1.98E+00	5.26E-03	ND	ND	ND	ND	ND	2.57E+03	ND	0.00E+00	1.39E-01	-2.34E-01	-5.66E-01	-5.58E+00
Non-re. PER as material	MJ/FU	9.68E-01	0.00E+00	2.34E-02	9.91E-01	0.00E+00	-1.00E-01	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	-2.12E-01	-6.79E-01	0.00E+00
Total use of non-re. PER	MJ/FU	3.89E+01	2.04E-01	2.37E+00	4.15E+01	1.98E+00	-9.52E-02	ND	ND	ND	ND	ND	2.57E+03	ND	0.00E+00	1.39E-01	-4.46E-01	-1.25E+00	-5.58E+00
Secondary materials	kg/FU	1.42E-01	0.00E+00	0.00E+00	1.42E-01	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Renew. secondary fuels	MJ/FU	1.28E-03	8.28E-07	1.34E-02	1.47E-02	1.07E-05	1.01E-06	ND	ND	ND	ND	ND	3.40E-03	ND	0.00E+00	7.95E-07	3.06E-06	6.47E-07	-1.61E-05
Non-ren. secondary fuels	MJ/FU	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Use of net fresh water	m ³ /FU	1.69E-02	2.51E-05	1.60E-03	1.85E-02	2.93E-04	1.53E-04	ND	ND	ND	ND	ND	2.23E+00	ND	0.00E+00	1.84E-05	3.71E-05	-3.10E-04	-2.05E-03

8) PER = Primary energy resources.

END OF LIFE – WASTE

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Hazardous waste	kg/FU	6.04E-01	3.23E-04	1.14E-02	6.16E-01	3.36E-03	2.48E-03	ND	ND	ND	ND	ND	6.51E+00	ND	0.00E+00	2.42E-04	7.77E-04	1.14E-03	-1.12E-01
Non-hazardous waste	kg/FU	1.10E+01	5.55E-03	5.92E-01	1.16E+01	6.21E-02	1.32E-01	ND	ND	ND	ND	ND	5.04E+02	ND	0.00E+00	4.55E-03	3.47E-02	5.60E-01	-1.16E+00
Radioactive waste	kg/FU	3.33E-05	3.70E-08	2.34E-06	3.57E-05	4.22E-07	2.45E-08	ND	ND	ND	ND	ND	1.83E-02	ND	0.00E+00	2.76E-08	5.79E-08	2.21E-08	-7.62E-06

END OF LIFE – OUTPUT FLOWS

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Components for reuse	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Materials for recycling	kg	0.00E+00	0.00E+00	4.05E-03	4.05E-03	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	1.89E-01	0.00E+00	0.00E+00
Materials for energy rec	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
Exported energy	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	9.20E-02	0.00E+00	0.00E+00
Exported energy – Electricity	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	3.87E-02	0.00E+00	0.00E+00
Exported energy – Heat	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	ND	ND	ND	ND	ND	0.00E+00	ND	0.00E+00	0.00E+00	5.32E-02	0.00E+00	0.00E+00

ENVIRONMENTAL IMPACTS – EN 15804+A1, CML

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
Global Warming Pot.	kg CO ₂ eq./FU	3.46E+00	1.48E-02	2.15E-01	3.69E+00	1.36E-01	1.25E-02	ND	ND	ND	ND	ND	1.11E+02	ND	0.00E+00	9.86E-03	2.40E-02	4.63E-02	-5.47E-01
Ozone depletion Pot.	kg CFC ₁₁ /FU	5.02E-08	1.73E-10	4.84E-09	5.52E-08	1.61E-09	9.11E-11	ND	ND	ND	ND	ND	1.70E-06	ND	0.00E+00	1.11E-10	5.02E-11	4.73E-11	-1.92E-09
Acidification	kg SO ₂ e/FU	2.08E-02	1.46E-04	6.25E-04	2.16E-02	3.56E-04	3.42E-05	ND	ND	ND	ND	ND	5.54E-01	ND	0.00E+00	2.53E-05	4.40E-05	1.79E-05	-5.27E-03
Eutrophication	kg PO ₄ ³ e/FU	4.42E-03	1.95E-05	5.21E-04	4.96E-03	8.66E-05	1.06E-05	ND	ND	ND	ND	ND	7.17E-02	ND	0.00E+00	6.15E-06	7.00E-06	4.30E-05	-3.24E-04
POCP (“smog”)	kg C ₂ H ₄ e/FU	1.61E-03	8.26E-06	7.07E-05	1.69E-03	3.17E-05	2.60E-06	ND	ND	ND	ND	ND	3.02E-02	ND	0.00E+00	2.27E-06	2.63E-06	6.33E-06	-3.03E-04
ADP-elements	kg Sbe/FU	1.19E-04	3.14E-08	8.99E-07	1.20E-04	3.71E-07	1.93E-08	ND	ND	ND	ND	ND	1.49E-03	ND	0.00E+00	3.18E-08	2.70E-07	7.78E-09	-1.26E-05
ADP-fossil	MJ/FU	3.70E+01	2.02E-01	2.58E+00	3.98E+01	1.95E+00	7.89E-02	ND	ND	ND	ND	ND	1.32E+03	ND	0.00E+00	1.37E-01	5.92E-02	5.08E-02	-5.08E+00

ADDITIONAL INDICATOR – GWP-GHG

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP-GHG ⁹⁾	kg CO ₂ e/FU	3.47E+00	1.49E-02	2.02E-01	3.69E+00	1.37E-01	1.26E-02	ND	ND	ND	ND	ND	1.11E+02	ND	0.00E+00	9.92E-03	2.41E-02	2.46E-02	-5.51E-01

9) This indicator includes all greenhouse gases excluding biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. In addition, the characterisation factors for the flows - CH₄ fossil, CH₄ biogenic and Dinitrogen monoxide - were updated. This indicator is identical to the GWP-total of EN 15804:2012+A2:2019 except that the characterization factor for biogenic CO₂ is set to zero.

SCENARIO DOCUMENTATION

DATA SOURCES

Manufacturing energy scenario documentation – A3 (Energy data source)

1. Energy supply, electricity production, co-generation oil and gas, Heat and power co-generation, natural gas, combined cycle power plant, 400MW electrical, Spain, ecoinvent 3.10.1, 0.0249 kgCO₂e/MJ
2. Energy supply, electricity production, solar photovoltaic, Electricity production, photovoltaic, 570kWp open ground installation, multi-Si, Spain, ecoinvent 3.10.1, 0.0673 kgCO₂e/kWh

Transport scenario documentation - A4

1. Transport, freight, lorry >32 metric ton, EURO5, 2760.17 km
2. Transport, freight, sea, container ship, 0.0 km

Installation scenario documentation - A5 (Waste materials data source)

1. Market for corrugated board box, 3.05 kg
2. Market for printed paper, offset, 0.001 kg
3. Market for packaging film, low density polyethylene, 0.052 kg

Use stages scenario documentation - B6-B7 (Energy data source)

1. Energy supply, electricity transformation and distribution, distribution low voltage, Market group for electricity, low voltage, Europe, 8500.0 kWh

TRANSPORT SCENARIO DOCUMENTATION - A4

Scenario parameter	Value
Capacity utilization (including empty return) %	50 %
Bulk density of transported products / kg/m ³	4.39E+02
Volume capacity utilization factor (factor: =1 or <1 or ≥1 for compressed or nested packaged products)	1

INSTALLATION SCENARIO DOCUMENTATION - A5

Scenario parameter	Value
Ancillary materials for installation (specified by material) / kg or other units as appropriate	0
Water use / m ³	0
Other resource use / kg	0
Direct emissions to ambient air, soil and water / kg	0

USE STAGES SCENARIO DOCUMENTATION - B6-B7 USE OF ENERGY AND WATER

Scenario information	Value
Ancillary materials specified by material / kg or units as appropriate	Not applicable
Net fresh water consumption / m ³	0
Power output of equipment / kW	85
Characteristic performance, e.g., energy efficiency, emissions, variation of performance with capacity utilization, etc. / Units as appropriate	For more details see product classification table and product description.
Further assumptions for scenario development, e.g., frequency and period of use, number of occupants / Units as appropriate	For more details see product classification table and product description.

END OF LIFE SCENARIO DOCUMENTATION

Scenario information	Value
Collection process – kg collected separately	8.453
Collection process – kg collected with mixed waste	0
Recovery process – kg for re-use	0
Recovery process – kg for recycling	4.74E+00
Recovery process – kg for energy recovery	0
Disposal (total) – kg for final deposition	3.55E+00
Scenario assumptions e.g. transportation	Lorry, 16-32 metric ton, EURO5; 150 km

THIRD-PARTY VERIFICATION STATEMENT

EPD Hub declares that this EPD is verified in accordance with ISO 14025 by an independent, third-party verifier. The project report on the Life Cycle Assessment and the report(s) on features of environmental relevance are filed at EPD Hub. EPD Hub PCR and ECO Platform verification checklist are used.

EPD Hub is not able to identify any unjustified deviations from the PCR and EN 15804+A2 in the Environmental Product Declaration and its project report.

EPD Hub maintains its independence as a third-party body; it was not involved in the execution of the LCA or in the development of the declaration and has no conflicts of interest regarding this verification.

The company-specific data and upstream and downstream data have been examined as regards plausibility and consistency. The publisher is responsible for ensuring the factual integrity and legal compliance of this declaration.



Program assistant: Xinyuan Zhang



The software used in creation of this LCA and EPD is verified by EPD Hub to conform to the procedural and methodological requirements outlined in ISO 14025:2010, ISO 14040/14044, EN 15804+A2, and EPD Hub Core Product Category Rules and General Program Instructions.

[Verified tools](#)

Tool verifier: Hai Ha Nguyen

Tool verification validity: 28 March 2025 - 27 March 2028

APPENDIX 1

MATERIAL COMPOSITION

The product material composition is illustrated in the table below. The material weight is given in grams and in percentage on total product weight.

Table 1: Material composition

Material	Weight (g)	Weight-%
Aluminium	5616.71	66.44
Brass	7.01	0.08
Copper	42.31	0.5
Glass	853.0	10.09
Other Plastics	505.38	5.98
Paint	588.29	6.96
PCB Alu	42.2	0.5
PCB Copper	118.57	1.4
PCB Iron	102.0	1.21
PCB Non-ferrous metal	0.54	0.01
PCB Support	137.39	1.63
PCB Tin	8.4	0.1

PP / PS-High Impact PS / ABS	17.03	0.2
Silica Sand	205.0	2.43
Steel	205.89	2.44
Tin	3.74	0.04

APPENDIX 2

USE PHASE (B6) VALUES FOR DIFFERENT COUNTRY MIX

In this EPD the B6 impact has been calculated using the energy mix of EU. The table in this appendix is useful for conversion and comparison of B6 values with other energy country mix. The Global Warming Potential Total (GWP tot) value is illustrated for each country. The value refers to 1 kwh.

Example on how to use the table:

If for example this EPD was done according to EU energy mix and you want to see how the GWP total changes according to a Finland country energy mix, you can take the original value in the results table here highlighted in yellow:

ENVIRONMENTAL IMPACT DATA, RESULTS PER DECLARED UNIT

The estimated impact results are only relative statements which do not indicate the end points of the impact categories, exceeding threshold values, safety margins or risks.

CORE ENVIRONMENTAL IMPACT INDICATORS – EN 15804+A2, EF 3.1

Impact category	Unit	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
GWP – total ⁽¹⁾	kg CO ₂ e	4.44E-01	4.75E-03	2.34E-02	4.72E-01	9.50E-04	8.13E-03	ND	ND	ND	ND	ND	4.06E-02	ND	0.00E+00	5.50E-04	2.23E-03	7.33E-04	-2.82E-02

Divide that value according to the EU value from the following table (EU = 3.30E-01) and then multiplying for the Finland value from the same table (FINLAND = 1.54E-01).

Thus, the calculation of this example would be:

New B6 GWP tot for Finland = (4.06E-02 / 3.30E-01) x 1.54E-01 = 1.89E-02.

Country	GWP tot (kg CO2 eq. per kwh)		
AFRICA	7.30E-01	GERMANY	3.90E-01
APAC	9.50E-01	INDIA	1.50E+00
AUSTRALIA	8.40E-01	ITALY	3.50E-01
AUSTRIA	2.30E-01	LATAM	3.90E-01
BELGIUM	2.00E-01	NAM	4.50E-01
CHINA	1.02E+00	NETHERLANDS	3.90E-01
DENMARK	1.60E-01	NORWAY	4.50E-02
EU	3.30E-01	ROW	7.30E-01
FINLAND	1.54E-01	SPAIN	2.10E-01
FRANCE	8.70E-02	SWEDEN	3.70E-02
		UK	2.60E-01

Source Ecoinvent 3.10.1

APPENDIX 3 - EPD HUB ALIGNED

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management scenarios and power inputs of the luminaires within the same product family.

To calculate the Scaled Impact (*SI*), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions P_{in} and the power input of the base variant P_{base} .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system). The presented controls factors values in Table A1 are based on BS EN 15193-1:2017. Please refer to this publication or contact Signify directly for more information.

$$TSF = PSF * CSF$$

Table 1: Light management function (PEP EcoPassport aligned)

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

- Lastly, the GWP of the base variant is then scaled by the TSF.

$$\text{Scaled Impact} = \text{GWP}_{\text{case}} * \text{TSF}$$

The following list of product configurations is not exhaustive. Please use the formula defined in point 1 above to calculate the exact power scaling factor (PSF) for any specific configuration.

Table 2: GWP per scaling factor (EPD Hub aligned)

	12NC or Product Family Code	Description	Flux [lm]	Power [W]	Efficacy [lm/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
							NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
1	BGP/BPP/BRP/BVP730	LED34-4S/757	3094	19	159.5	0.228	0.228	0.171	0.171	0.125	637.6	478.2	478.2	349.6
2	BGP/BPP/BRP/BVP730	LED40-4S/757	3640	23	158.3	0.271	0.271	0.203	0.203	0.149	757.9	567.7	567.7	416.7
3	BGP/BPP/BRP/BVP730	LED50-4S/757	4550	28	159.6	0.335	0.335	0.251	0.251	0.184	936.8	701.9	701.9	514.6
4	BGP/BPP/BRP/BVP730	LED60-4S/757	5460	34	158.3	0.406	0.406	0.304	0.304	0.223	1135.4	850.1	850.1	623.6
5	BGP/BPP/BRP/BVP730	LED70-4S/757	6300	40	155.6	0.476	0.476	0.357	0.357	0.262	1331.1	998.4	998.4	732.7
6	BGP/BPP/BRP/BVP730	LED80-4S/757	7200	47	153.2	0.553	0.553	0.415	0.415	0.304	1546.5	1160.5	1160.5	850.1
7	BGP/BPP/BRP/BVP730	LED90-4S/757	8100	54	150.0	0.635	0.635	0.476	0.476	0.349	1775.8	1331.1	1331.1	976.0
8	BGP/BPP/BRP/BVP730	LED100-4S/757	8900	61	145.9	0.718	0.718	0.538	0.538	0.395	2007.9	1504.5	1504.5	1104.6
9	BGP/BPP/BRP/BVP730	LED110-4S/757	9900	64	154.7	0.753	0.753	0.565	0.565	0.414	2105.8	1580.0	1580.0	1157.8
10	BGP/BPP/BRP/BVP730	LED120-4S/757	10800	71	152.1	0.835	0.835	0.626	0.626	0.459	2335.1	1750.6	1750.6	1283.6

11	BGP/BPP/BRP/BVP730	LED130-4S/757	11570	78	148.3	0.918	0.918	0.689	0.689	0.505	2567.2	1926.8	1926.8	1412.2
12	BGP/BPP/BRP/BVP730	LED140-4S/757	12460	85	146.6	1.0	1.0	0.75	0.75	0.55	2796.5	2097.4	2097.4	1538.1
13	BGP/BPP/BRP/BVP730	LED34-4S/740	3094	19	159.5	0.228	0.228	0.171	0.171	0.125	637.6	478.2	478.2	349.6
14	BGP/BPP/BRP/BVP730	LED40-4S/740	3640	23	158.3	0.271	0.271	0.203	0.203	0.149	757.9	567.7	567.7	416.7
15	BGP/BPP/BRP/BVP730	LED50-4S/740	4550	28	159.6	0.335	0.335	0.251	0.251	0.184	936.8	701.9	701.9	514.6
16	BGP/BPP/BRP/BVP730	LED60-4S/740	5400	34	156.5	0.406	0.406	0.304	0.304	0.223	1135.4	850.1	850.1	623.6
17	BGP/BPP/BRP/BVP730	LED70-4S/740	6300	40	155.6	0.476	0.476	0.357	0.357	0.262	1331.1	998.4	998.4	732.7
18	BGP/BPP/BRP/BVP730	LED80-4S/740	7200	47	153.2	0.553	0.553	0.415	0.415	0.304	1546.5	1160.5	1160.5	850.1
19	BGP/BPP/BRP/BVP730	LED90-4S/740	8100	54	150.0	0.635	0.635	0.476	0.476	0.349	1775.8	1331.1	1331.1	976.0
20	BGP/BPP/BRP/BVP730	LED100-4S/740	8900	61	145.9	0.718	0.718	0.538	0.538	0.395	2007.9	1504.5	1504.5	1104.6
21	BGP/BPP/BRP/BVP730	LED110-4S/740	9900	64	154.7	0.753	0.753	0.565	0.565	0.414	2105.8	1580.0	1580.0	1157.8
22	BGP/BPP/BRP/BVP730	LED120-4S/740	10800	71	152.1	0.835	0.835	0.626	0.626	0.459	2335.1	1750.6	1750.6	1283.6
23	BGP/BPP/BRP/BVP730	LED130-4S/740	11570	78	148.3	0.918	0.918	0.689	0.689	0.505	2567.2	1926.8	1926.8	1412.2
24	BGP/BPP/BRP/BVP730	LED140-4S/740	12460	85	146.6	1.0	1.0	0.75	0.75	0.55	2796.5	2097.4	2097.4	1538.1

25	BGP/BPP/BRP/BVP730	LED34-4S/730	3094	20	150.9	0.241	0.241	0.181	0.181	0.133	674.0	506.2	506.2	371.9
26	BGP/BPP/BRP/BVP730	LED40-4S/730	3640	24	148.6	0.288	0.288	0.216	0.216	0.158	805.4	604.0	604.0	441.8
27	BGP/BPP/BRP/BVP730	LED50-4S/730	4550	30	149.2	0.359	0.359	0.269	0.269	0.197	1003.9	752.3	752.3	550.9
28	BGP/BPP/BRP/BVP730	LED60-4S/730	5400	37	145.9	0.435	0.435	0.326	0.326	0.239	1216.5	911.7	911.7	668.4
29	BGP/BPP/BRP/BVP730	LED70-4S/730	6300	44	144.8	0.512	0.512	0.384	0.384	0.282	1431.8	1073.9	1073.9	788.6
30	BGP/BPP/BRP/BVP730	LED80-4S/730	7200	50	144.0	0.588	0.588	0.441	0.441	0.323	1644.3	1233.3	1233.3	903.3
31	BGP/BPP/BRP/BVP730	LED90-4S/730	8010	58	138.1	0.682	0.682	0.512	0.512	0.375	1907.2	1431.8	1431.8	1048.7
32	BGP/BPP/BRP/BVP730	LED100-4S/730	9000	62	145.2	0.729	0.729	0.547	0.547	0.401	2038.6	1529.7	1529.7	1121.4
33	BGP/BPP/BRP/BVP730	LED110-4S/730	9900	69	143.5	0.812	0.812	0.609	0.609	0.447	2270.8	1703.1	1703.1	1250.0
34	BGP/BPP/BRP/BVP730	LED120-4S/730	10680	76	140.5	0.894	0.894	0.67	0.67	0.492	2500.1	1873.7	1873.7	1375.9
35	BGP/BPP/BRP/BVP730	LED130-4S/730	11570	84	137.7	0.988	0.988	0.741	0.741	0.543	2762.9	2072.2	2072.2	1518.5
36	BGP/BPP/BRP/BVP730	LED34-4S/727	3094	23	134.5	0.271	0.271	0.203	0.203	0.149	757.9	567.7	567.7	416.7
37	BGP/BPP/BRP/BVP730	LED40-4S/727	3640	28	132.4	0.324	0.324	0.243	0.243	0.178	906.1	679.5	679.5	497.8
38	BGP/BPP/BRP/BVP730	LED50-4S/727	4500	34	132.4	0.4	0.4	0.3	0.3	0.22	1118.6	838.9	838.9	615.2

39	BGP/BPP/BRP/BVP730	LED60-4S/727	5400	42	130.1	0.488	0.488	0.366	0.366	0.268	1364.7	1023.5	1023.5	749.5
40	BGP/BPP/BRP/BVP730	LED70-4S/727	6300	49	128.6	0.576	0.576	0.432	0.432	0.317	1610.8	1208.1	1208.1	886.5
41	BGP/BPP/BRP/BVP730	LED80-4S/727	7120	57	124.9	0.671	0.671	0.503	0.503	0.369	1876.5	1406.6	1406.6	1031.9
42	BGP/BPP/BRP/BVP730	LED90-4S/727	8100	62	130.6	0.729	0.729	0.547	0.547	0.401	2038.6	1529.7	1529.7	1121.4
43	BGP/BPP/BRP/BVP730	LED100-4S/727	9000	70	128.6	0.824	0.824	0.618	0.618	0.453	2304.3	1728.2	1728.2	1266.8
44	BGP/BPP/BRP/BVP730	LED110-4S/727	9790	79	123.9	0.929	0.929	0.697	0.697	0.511	2597.9	1949.2	1949.2	1429.0
45	BGP/BPP/BRP/BVP730	LED34-4S/722	3094	26	119.0	0.306	0.306	0.229	0.229	0.168	855.7	640.4	640.4	469.8
46	BGP/BPP/BRP/BVP730	LED40-4S/722	3640	30	119.3	0.359	0.359	0.269	0.269	0.197	1003.9	752.3	752.3	550.9
47	BGP/BPP/BRP/BVP730	LED50-4S/722	4500	38	116.9	0.453	0.453	0.34	0.34	0.249	1266.8	950.8	950.8	696.3
48	BGP/BPP/BRP/BVP730	LED60-4S/722	5400	47	114.9	0.553	0.553	0.415	0.415	0.304	1546.5	1160.5	1160.5	850.1
49	BGP/BPP/BRP/BVP730	LED70-4S/722	6300	53	118.9	0.624	0.624	0.468	0.468	0.343	1745.0	1308.8	1308.8	959.2
50	BGP/BPP/BRP/BVP730	LED80-4S/722	7200	62	116.1	0.729	0.729	0.547	0.547	0.401	2038.6	1529.7	1529.7	1121.4
51	BGP/BPP/BRP/BVP730	LED90-4S/722	8100	71	114.1	0.835	0.835	0.626	0.626	0.459	2335.1	1750.6	1750.6	1283.6
52	BGP/BPP/BRP/BVP730	LED100-4S/722	8900	80	111.2	0.941	0.941	0.706	0.706	0.518	2631.5	1974.3	1974.3	1448.6

53	BGP/BPP/BRP/BVP730	LED34-4S/840	3094	22	137.5	0.265	0.265	0.199	0.199	0.146	741.1	556.5	556.5	408.3
54	BGP/BPP/BRP/BVP730	LED40-4S/840	3640	26	137.4	0.312	0.312	0.234	0.234	0.172	872.5	654.4	654.4	481.0
55	BGP/BPP/BRP/BVP730	LED50-4S/840	4550	33	137.9	0.388	0.388	0.291	0.291	0.213	1085.0	813.8	813.8	595.7
56	BGP/BPP/BRP/BVP730	LED60-4S/840	5400	40	135.0	0.471	0.471	0.353	0.353	0.259	1317.2	987.2	987.2	724.3
57	BGP/BPP/BRP/BVP730	LED70-4S/840	6300	48	132.6	0.559	0.559	0.419	0.419	0.307	1563.2	1171.7	1171.7	858.5
58	BGP/BPP/BRP/BVP730	LED80-4S/840	7200	55	130.9	0.647	0.647	0.485	0.485	0.356	1809.3	1356.3	1356.3	995.6
59	BGP/BPP/BRP/BVP730	LED90-4S/840	8100	60	135.0	0.706	0.706	0.529	0.529	0.388	1974.3	1479.3	1479.3	1085.0
60	BGP/BPP/BRP/BVP730	LED100-4S/840	9000	68	132.4	0.8	0.8	0.6	0.6	0.44	2237.2	1677.9	1677.9	1230.5
61	BGP/BPP/BRP/BVP730	LED110-4S/840	9790	76	128.8	0.894	0.894	0.67	0.67	0.492	2500.1	1873.7	1873.7	1375.9
62	BGP/BPP/BRP/BVP730	LED34-4S/830	3094	23	134.5	0.271	0.271	0.203	0.203	0.149	757.9	567.7	567.7	416.7
63	BGP/BPP/BRP/BVP730	LED40-4S/830	3640	28	132.4	0.324	0.324	0.243	0.243	0.178	906.1	679.5	679.5	497.8
64	BGP/BPP/BRP/BVP730	LED50-4S/830	4500	34	132.4	0.4	0.4	0.3	0.3	0.22	1118.6	838.9	838.9	615.2
65	BGP/BPP/BRP/BVP730	LED60-4S/830	5400	42	130.1	0.488	0.488	0.366	0.366	0.268	1364.7	1023.5	1023.5	749.5
66	BGP/BPP/BRP/BVP730	LED70-4S/830	6300	49	128.6	0.576	0.576	0.432	0.432	0.317	1610.8	1208.1	1208.1	886.5

67	BGP/BPP/BRP/BVP730	LED80-4S/830	7120	57	124.9	0.671	0.671	0.503	0.503	0.369	1876.5	1406.6	1406.6	1031.9
68	BGP/BPP/BRP/BVP730	LED90-4S/830	8100	62	130.6	0.729	0.729	0.547	0.547	0.401	2038.6	1529.7	1529.7	1121.4
69	BGP/BPP/BRP/BVP730	LED100-4S/830	9000	70	128.6	0.824	0.824	0.618	0.618	0.453	2304.3	1728.2	1728.2	1266.8
70	BGP/BPP/BRP/BVP730	LED110-4S/830	9790	79	123.9	0.929	0.929	0.697	0.697	0.511	2597.9	1949.2	1949.2	1429.0
71	BGP/BPP/BRP/BVP730	LED40-4S/827	3640	30	123.4	0.347	0.347	0.26	0.26	0.191	970.4	727.1	727.1	534.1
72	BGP/BPP/BRP/BVP730	LED50-4S/827	4500	37	121.6	0.435	0.435	0.326	0.326	0.239	1216.5	911.7	911.7	668.4
73	BGP/BPP/BRP/BVP730	LED60-4S/827	5400	45	120.0	0.529	0.529	0.397	0.397	0.291	1479.3	1110.2	1110.2	813.8
74	BGP/BPP/BRP/BVP730	LED70-4S/827	6300	53	118.9	0.624	0.624	0.468	0.468	0.343	1745.0	1308.8	1308.8	959.2
75	BGP/BPP/BRP/BVP730	LED80-4S/827	7200	59	122.0	0.694	0.694	0.52	0.52	0.382	1940.8	1454.2	1454.2	1068.3
76	BGP/BPP/BRP/BVP730	LED90-4S/827	8100	68	119.1	0.8	0.8	0.6	0.6	0.44	2237.2	1677.9	1677.9	1230.5
77	BGP/BPP/BRP/BVP730	LED100-4S/827	8900	76	117.1	0.894	0.894	0.67	0.67	0.492	2500.1	1873.7	1873.7	1375.9

PEP ECOPASSPORT ALIGNED

This section represents the scaling method for the **B6 module**, following the PEP EcoPassport PSR for luminaries (PSR-0014-ed2.0-EN-2023 07 13). The GWP results were scaled from a reference variant of a product family, based on various light management functions, the lumen output (O_{lum}) and reference service life (RSL) of each product within the same product family.

To calculate the Scaled Impact (SI_{pep}), we have followed the below methods:

1. Calculate the power scaling factor (PSF), which is the ratio of the power input of the variant in questions P_{in} and the power input of the base variant P_{base} .

$$PSF = \frac{P_{in}}{P_{base}}$$

2. Using this scaled GWP, we then can apply the PEP Ecopassport method for calculating the environmental impact of the functional unit for a luminary (1000 lumens over 35000 hours), applied to B6, where the Functional Unit application considers the lumen output (O_{lum}) and reference service lifetime (RSL) of the product to estimate the final environmental impact. The scaled impact (SI_{pep}) is presented in Table A4.

$$GSF = \frac{FU_{pep}}{FU_p} = \frac{1,000}{O_{lum}} * \frac{35,000}{RSL}$$

3. Calculate the GWP scaling factor ($PGSF$), by multiplying the PSF by the GSF.

$$PGSF = PSF * GSF$$

4. Calculate the Total Scaling factor by multiplying the PSF by the control scaling factor (CSF), where the CSF is determined according the relevant control factor scenario (e.g. if the luminaire has a presence detection system), as presented in Table A1.

$$TSF = PGSF * CSF$$

Table 3: Light management functions (PEP EcoPassport aligned)

Scenario	Abbrev.	CSF
No control	NC	1
Daylight dependency factor	DD	0.75
Presence sensing	PS	0.75
Daylight dependency and presence sensing	DD+PS	0.55

5. Lastly, the GWP of the base variant is then scaled by the TSF.

$$Scaled\ GWP = GWP_{case} * TSF$$

Table 4: Impact per scaling factor (PEP EcoPassport aligned)

	12NC or Product Family Code	Description	Flux [lm]	Power [W]	Efficacy [lm/W]	PSF	Total Scaling Factor (TSF)				Scaled Impacts (GWP100 B6 - kg CO2eq.)			
							NC	DD	PS	DD+PS	NC	DD	PS	DD+PS
1	BGP/BPP/BRP/BVP730	LED34-4S/757	3094	19	159.5	0.228	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
2	BGP/BPP/BRP/BVP730	LED40-4S/757	3640	23	158.3	0.271	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
3	BGP/BPP/BRP/BVP730	LED50-4S/757	4550	28	159.6	0.335	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
4	BGP/BPP/BRP/BVP730	LED60-4S/757	5460	34	158.3	0.406	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
5	BGP/BPP/BRP/BVP730	LED70-4S/757	6300	40	155.6	0.476	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
6	BGP/BPP/BRP/BVP730	LED80-4S/757	7200	47	153.2	0.553	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
7	BGP/BPP/BRP/BVP730	LED90-4S/757	8100	54	150.0	0.635	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
8	BGP/BPP/BRP/BVP730	LED100-4S/757	8900	61	145.9	0.718	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
9	BGP/BPP/BRP/BVP730	LED110-4S/757	9900	64	154.7	0.753	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
10	BGP/BPP/BRP/BVP730	LED120-4S/757	10800	71	152.1	0.835	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
11	BGP/BPP/BRP/BVP730	LED130-4S/757	11570	78	148.3	0.918	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
12	BGP/BPP/BRP/BVP730	LED140-4S/757	12460	85	146.6	1.0	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9

13	BGP/BPP/BRP/BVP730	LED34-4S/740	3094	19	159.5	0.228	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
14	BGP/BPP/BRP/BVP730	LED40-4S/740	3640	23	158.3	0.271	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
15	BGP/BPP/BRP/BVP730	LED50-4S/740	4550	28	159.6	0.335	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
16	BGP/BPP/BRP/BVP730	LED60-4S/740	5400	34	156.5	0.406	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
17	BGP/BPP/BRP/BVP730	LED70-4S/740	6300	40	155.6	0.476	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
18	BGP/BPP/BRP/BVP730	LED80-4S/740	7200	47	153.2	0.553	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
19	BGP/BPP/BRP/BVP730	LED90-4S/740	8100	54	150.0	0.635	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
20	BGP/BPP/BRP/BVP730	LED100-4S/740	8900	61	145.9	0.718	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
21	BGP/BPP/BRP/BVP730	LED110-4S/740	9900	64	154.7	0.753	0.026	0.019	0.019	0.014	72.7	53.1	53.1	39.2
22	BGP/BPP/BRP/BVP730	LED120-4S/740	10800	71	152.1	0.835	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
23	BGP/BPP/BRP/BVP730	LED130-4S/740	11570	78	148.3	0.918	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
24	BGP/BPP/BRP/BVP730	LED140-4S/740	12460	85	146.6	1.0	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
25	BGP/BPP/BRP/BVP730	LED34-4S/730	3094	20	150.9	0.241	0.027	0.02	0.02	0.015	75.5	55.9	55.9	41.9
26	BGP/BPP/BRP/BVP730	LED40-4S/730	3640	24	148.6	0.288	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9

27	BGP/BPP/BRP/BVP730	LED50-4S/730	4550	30	149.2	0.359	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
28	BGP/BPP/BRP/BVP730	LED60-4S/730	5400	37	145.9	0.435	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
29	BGP/BPP/BRP/BVP730	LED70-4S/730	6300	44	144.8	0.512	0.029	0.022	0.022	0.016	81.1	61.5	61.5	44.7
30	BGP/BPP/BRP/BVP730	LED80-4S/730	7200	50	144.0	0.588	0.029	0.022	0.022	0.016	81.1	61.5	61.5	44.7
31	BGP/BPP/BRP/BVP730	LED90-4S/730	8010	58	138.1	0.682	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5
32	BGP/BPP/BRP/BVP730	LED100-4S/730	9000	62	145.2	0.729	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
33	BGP/BPP/BRP/BVP730	LED110-4S/730	9900	69	143.5	0.812	0.028	0.021	0.021	0.015	78.3	58.7	58.7	41.9
34	BGP/BPP/BRP/BVP730	LED120-4S/730	10680	76	140.5	0.894	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5
35	BGP/BPP/BRP/BVP730	LED130-4S/730	11570	84	137.7	0.988	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5
36	BGP/BPP/BRP/BVP730	LED34-4S/727	3094	23	134.5	0.271	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
37	BGP/BPP/BRP/BVP730	LED40-4S/727	3640	28	132.4	0.324	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
38	BGP/BPP/BRP/BVP730	LED50-4S/727	4500	34	132.4	0.4	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
39	BGP/BPP/BRP/BVP730	LED60-4S/727	5400	42	130.1	0.488	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
40	BGP/BPP/BRP/BVP730	LED70-4S/727	6300	49	128.6	0.576	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3

41	BGP/BPP/BRP/BVP730	LED80-4S/727	7120	57	124.9	0.671	0.033	0.025	0.025	0.018	92.3	69.9	69.9	50.3
42	BGP/BPP/BRP/BVP730	LED90-4S/727	8100	62	130.6	0.729	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
43	BGP/BPP/BRP/BVP730	LED100-4S/727	9000	70	128.6	0.824	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
44	BGP/BPP/BRP/BVP730	LED110-4S/727	9790	79	123.9	0.929	0.033	0.025	0.025	0.018	92.3	69.9	69.9	50.3
45	BGP/BPP/BRP/BVP730	LED34-4S/722	3094	26	119.0	0.306	0.035	0.026	0.026	0.019	97.9	72.7	72.7	53.1
46	BGP/BPP/BRP/BVP730	LED40-4S/722	3640	30	119.3	0.359	0.034	0.026	0.026	0.019	95.1	72.7	72.7	53.1
47	BGP/BPP/BRP/BVP730	LED50-4S/722	4500	38	116.9	0.453	0.035	0.026	0.026	0.019	97.9	72.7	72.7	53.1
48	BGP/BPP/BRP/BVP730	LED60-4S/722	5400	47	114.9	0.553	0.036	0.027	0.027	0.02	100.7	75.5	75.5	55.9
49	BGP/BPP/BRP/BVP730	LED70-4S/722	6300	53	118.9	0.624	0.035	0.026	0.026	0.019	97.9	72.7	72.7	53.1
50	BGP/BPP/BRP/BVP730	LED80-4S/722	7200	62	116.1	0.729	0.036	0.027	0.027	0.02	100.7	75.5	75.5	55.9
51	BGP/BPP/BRP/BVP730	LED90-4S/722	8100	71	114.1	0.835	0.036	0.027	0.027	0.02	100.7	75.5	75.5	55.9
52	BGP/BPP/BRP/BVP730	LED100-4S/722	8900	80	111.2	0.941	0.037	0.028	0.028	0.02	103.5	78.3	78.3	55.9
53	BGP/BPP/BRP/BVP730	LED34-4S/840	3094	22	137.5	0.265	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5
54	BGP/BPP/BRP/BVP730	LED40-4S/840	3640	26	137.4	0.312	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5

55	BGP/BPP/BRP/BVP730	LED50-4S/840	4550	33	137.9	0.388	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5
56	BGP/BPP/BRP/BVP730	LED60-4S/840	5400	40	135.0	0.471	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
57	BGP/BPP/BRP/BVP730	LED70-4S/840	6300	48	132.6	0.559	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
58	BGP/BPP/BRP/BVP730	LED80-4S/840	7200	55	130.9	0.647	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
59	BGP/BPP/BRP/BVP730	LED90-4S/840	8100	60	135.0	0.706	0.03	0.022	0.022	0.017	83.9	61.5	61.5	47.5
60	BGP/BPP/BRP/BVP730	LED100-4S/840	9000	68	132.4	0.8	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
61	BGP/BPP/BRP/BVP730	LED110-4S/840	9790	76	128.8	0.894	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
62	BGP/BPP/BRP/BVP730	LED34-4S/830	3094	23	134.5	0.271	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
63	BGP/BPP/BRP/BVP730	LED40-4S/830	3640	28	132.4	0.324	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
64	BGP/BPP/BRP/BVP730	LED50-4S/830	4500	34	132.4	0.4	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5
65	BGP/BPP/BRP/BVP730	LED60-4S/830	5400	42	130.1	0.488	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
66	BGP/BPP/BRP/BVP730	LED70-4S/830	6300	49	128.6	0.576	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
67	BGP/BPP/BRP/BVP730	LED80-4S/830	7120	57	124.9	0.671	0.033	0.025	0.025	0.018	92.3	69.9	69.9	50.3
68	BGP/BPP/BRP/BVP730	LED90-4S/830	8100	62	130.6	0.729	0.031	0.023	0.023	0.017	86.7	64.3	64.3	47.5

69	BGP/BPP/BRP/BVP730	LED100-4S/830	9000	70	128.6	0.824	0.032	0.024	0.024	0.018	89.5	67.1	67.1	50.3
70	BGP/BPP/BRP/BVP730	LED110-4S/830	9790	79	123.9	0.929	0.033	0.025	0.025	0.018	92.3	69.9	69.9	50.3
71	BGP/BPP/BRP/BVP730	LED40-4S/827	3640	30	123.4	0.347	0.033	0.025	0.025	0.018	92.3	69.9	69.9	50.3
72	BGP/BPP/BRP/BVP730	LED50-4S/827	4500	37	121.6	0.435	0.034	0.026	0.026	0.019	95.1	72.7	72.7	53.1
73	BGP/BPP/BRP/BVP730	LED60-4S/827	5400	45	120.0	0.529	0.034	0.026	0.026	0.019	95.1	72.7	72.7	53.1
74	BGP/BPP/BRP/BVP730	LED70-4S/827	6300	53	118.9	0.624	0.035	0.026	0.026	0.019	97.9	72.7	72.7	53.1
75	BGP/BPP/BRP/BVP730	LED80-4S/827	7200	59	122.0	0.694	0.034	0.026	0.026	0.019	95.1	72.7	72.7	53.1
76	BGP/BPP/BRP/BVP730	LED90-4S/827	8100	68	119.1	0.8	0.034	0.026	0.026	0.019	95.1	72.7	72.7	53.1
77	BGP/BPP/BRP/BVP730	LED100-4S/827	8900	76	117.1	0.894	0.035	0.026	0.026	0.019	97.9	72.7	72.7	53.1