



Stand-alone 3 hours compliant Exit Signs

Exit Sign

Safety is important for building owners, and therefore having proper emergency lighting in place is a major concern for them. The Exit Signs EM155C and EM159C offer an easy solution for stand alone emergency lighting, that is fully compliant with European regulations. The lithium battery (LiFePO4) has many advantages over nickel based products, as it has a longer lifetime, better discharge behavior, is produced in a more welfare friendly way and can be recycled. Legends, recessed mounting kit as well as suspension kit are available as accessories.

Benefits

- · Meets European standards for emergency lighting luminaires.
- Lithium based battery type provides longer lifetime, low self discharge and high temperature tolerance.
- Welfare friendly solution versus nickel-based products as the battery can be recycled.

Features

- · 3 hours emergency lighting
- $\boldsymbol{\cdot}$ Manual and Self-Test options
- Up to 30 m viewing distance, luminance higher than 20cd/m²
- · Maintained / Non- Maintained Emergency lighting
- · Recessed kit and Suspension kits available as accessories

Application

- Exit and Emergency
- Offices
- · Retail
- Hospitality
- Manufacturing


Exit Sign

Versions



Emergency Exit Sign EM159C SPP01

Dimensional drawing



Product details



Emergency Slim Exit Sign EM155C DET02



Emergency Slim Exit Sign EM155C DET01



Emergency Exit Sign EM159C DET02



Emergency Exit Sign all legends

Exit Sign

Product details



Emergency Exit Sign EM159C DET01



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.