



# Stand-alone 3 hours compliant emergency lighting spot

## Emergency Spot

Safety is important for building owners, and therefore having proper emergency lighting in place is a major concern for them. The Emergency spot EM150B offers an easy solution for stand-alone emergency lighting, that is fully compliant with European regulations. The lithium battery (LiFePO4) has many advantages over nickel-based products, as it has a longer lifetime, better discharge behavior, is produced in a more welfare friendly way and can be recycled. Two interchangeable lenses are supplied with the product, to adjust the beam angle to the application.

### Benefits

- Meets European standards for emergency lighting luminaires.
- Lithium based battery type provides longer lifetime, low self discharge and high temperature tolerance.
- Welfare friendly solution versus nickel-based products as the battery can be recycled.

### Features

- Two interchangeable lens optics; corridor and open area
- Non-Maintained Emergency lighting
- 3 hours emergency lighting
- Manual and Self-Test options

### Application

- Exit and Emergency
- Offices
- Retail
- Hospitality
- Manufacturing


## Emergency Spot

### Versions



EM150B Emergency spot

### Dimensional drawing



# Emergency Spot

General Information	
Driver included	Yes
Lamp family code	-
Number of gear units	Unit
Light Technical	
Correlated Colour Temperature (Nom)	6500 K
Colour rendering index (CRI)	>80
Luminous efficacy (rated) (nom.)	130 lm/W
Luminous Flux	135 lm
Optic type	Open area or corridor optic
Upwards light output ratio	0.96
Operating and Electrical	
Protection class IEC	Safety class II
Input Voltage	220-240 V
Line Frequency	50 Hz
Power Consumption	2 W
Suitable for random switching	Not applicable
Controls and Dimming	
Dimmable	No
Embedded control	-
Maximum dim level	Not applicable
Mechanical and Housing	
Optical cover type	-
Housing Colour	White
Mech. impact protection code	IK04
Ingress protection code	IP20
Emergency Operation	
Central Emergency	No
Emergency flux	135 lm
Rated duration of the emergency lighting (when fully charged)	3 h
Approval and Application	
Ambient temperature range	+5 to +45 °C
CE mark	Yes
ENEC mark	-
Flammability mark	-
Glow-wire test	-
Initial Performance (IEC Compliant)	
Initial chromaticity	0.33
Luminous flux tolerance	+/-5%

## Emergency Operation

Order Code	Full Product Name	Emergency lighting
912401483504	EM150B REC 1S OA/CO NM3 ELP WH IP20	Emergency lighting 3-hour duration Pro version
912401483505	EM150B REC 1S OA/CO NM3 ELB WH IP20	Emergency lighting 3-hours duration basic version

## Emergency Spot



© 2025 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

[www.lighting.philips.com](http://www.lighting.philips.com)  
2025, December 13 - data subject to change