



# Best in class Extruded Aluminium batten with high Lumen Efficacy. Sleek but robust design

## Smartbright BN100 Batten

High performance LED batten, can replace 2x40W conventional batten suitable for Classroom, hostel room, corridor, small shops, community center, club, small warehouse lighting applications.

### Benefits

- Long Useful life
- Volumetric distribution improving safety in industrial environment
- Sleek aesthetic design complements interiors

### Features

- Suitable for Surface & suspension mounting
- Extruded aluminium housing
- Slim integrated design, easy to install
- Energy Saving of up to 60% compared to conventional lighting

### Application

- General Indoor Lighting
- Industrial usage


### Warnings and Safety

- Meant for use in Indoor environment only


Smartbright BN100 Batten

Dimensional drawing

Dimensions



Product : GreenBay  
Type : BY400V  
Application : Indoor



| General Information             |   |
|---------------------------------|---|
| Driver included                 | Yes   |
| Light Technical                 |   |
| Beam angle of light source      | 120 degree(s)                               |
| Color rendering index (CRI)     | >80   |
| Luminous Efficacy (rated) (Nom) | 105 lm/W                                    |
| Luminous Flux                   | 4,000 lm                                    |
| Optic type                      | -   |
| Operating and Electrical        |   |
| Protection class IEC            | Safety class II                             |
| Input Voltage                   | 220-240 V                                   |
| Controls and Dimming            |   |
| Dimmable                        | No  |
| Mechanical and Housing          |   |
| Optical cover type              | Polycarbonate                               |
| Housing Color                   | Aluminum and gray                           |
| Mech. impact protection code    | IK02  |
| Ingress protection code         | IP20  |
| Approval and Application        |   |
| Ambient temperature range       | 0 to +45 °C                                 |
| Flammability mark               | For mounting on normally flammable surfaces |

Light Technical

| Order Code   | Full Product Name              | Correlated Color Temperature (Nom) |
|--------------|--------------------------------|------------------------------------|
| 919515811980 | BN100C LED40S-6500 PSU L120 GR | 6500 K                             |
| 919515811981 | BN100C LED40S-4000 PSU L120 GR | 4000 K                             |

Operating and Electrical

| Order Code   | Full Product Name              | Power Consumption |
|--------------|--------------------------------|-------------------|
| 919515811980 | BN100C LED40S-6500 PSU L120 GR | 40 W              |

| Order Code   | Full Product Name              | Power Consumption |
|--------------|--------------------------------|-------------------|
| 919515811981 | BN100C LED40S-4000 PSU L120 GR | 41 W              |

## Smartbright BN100 Batten

