

Maxos accessories

9MX056



9MX056 TL-D / TL5 swivel device

The swivel device is a versatile mechanical connecting device for Maxos TL-D and TL5 light-lines and enables variable angles between the light-lines. The minimum angle is 45 degrees. Due to its attractive design it is often used in application areas such as shops, schools and museums. Up to four light-lines can be connected with one swivel device. The housing is made of plastic, with a white or silver coating, and with inner supporting elements made of steel. If needed, the swivel device can accommodate lighting control sensors, loudspeakers, etc. It is pre-mounted with an adjustable quick hanger with a 1.25 m steel suspension wire. One dedicated coupling piece (9MX056 CP-SD WH/SI) per trunking section is necessary to connect the trunking to the swivel device. Electrical components for mains feed-through have to be ordered as required.

Benefits

- -

Versions

9MX056 BC49 SI



Maxos_end_pieces_electrical_connector

Product details



Maxos 4MX056 TL-D
extended trunking section
M300/E300/M600/E600 and
blind cover, used to close the
spaces in the trunking where
no electrical units are
mounted

Operating and Electrical

Protection class IEC -

Mechanical and Housing

Ingress protection code -

Accessory color White

Approval and Application

CE mark Yes

Product Data

Product family code 9MX056 [ACC MAXOS]

