

**PHILIPS**

**Lighting**



# Product Description

## MASTER TL-D Eco

Low-pressure mercury discharge lamps with a tubular 26 mm envelope

### Benefits

- Simple lamp-for-lamp replacement for more than 10% energy savings
- Makes lighting installations compliant with latest indoor lighting standards
- Relatively high efficacy, both initially and during lifetime, with high lumen maintenance

### Features

- The only T8 fluorescent lamp that saves more than 10% of energy in existing indoor luminaires
- Can be directly retrofitted into existing fluorescent fittings operating on conventional EM or HF gear in indoor applications
- Uses the latest highly efficient phosphors and special filling gas
- High-quality lighting with good color rendering (CRI>80)
- Light output comparable to other TL-D Super 80 colors
- Lumen maintenance and lifetime the same as other TL-D Super 80 colors
- Dimmable

### Application

- Indoor working areas (office, public/government buildings, schools, hospitals, etc.) with ambient temperatures above 15 °C

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.


# MASTER TL-D Eco

## Versions



LPPR TL-D8ECO

## Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
MASTER TL-D Eco 51W/865	28 mm	1,500.0 mm	1,507.1 mm	1,504.7 mm	1,514.2 mm
SLV/25					

