

PHILIPS

Lighting



MSR – bright vivid colors, always

MSR

The high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

Benefits

- Optimal light collection
- Excellent color characteristics
- Brightness on stage

Features

- Single ended lamp concept
- High CRI
- Daylight Color Temperatures

Application

- Theatre stages
- Discos
- Events
- Shows

Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Versions




XPPR_XDMSR_0018-Product photo




XPPR_XDMSR_0025

Dimensional drawing



Product	D (max)	O	L (min)	L (max)	L	C (max)	F
MSR 1200 1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm
MSR 1200/2.1CT/3	40 mm	10.0 mm	84 mm	86 mm	85 mm	175 mm	53 mm
MSR 700/2 1CT/8	30 mm	8.0 mm	74 mm	76 mm	75 mm	152 mm	42 mm



Product	D (max)	O	L (min)	L (max)	L	C (max)	F (max)	F	F (min)
MSR 575/2 10H 1CT/4	30 mm	7.0 mm	64 mm	66 mm	65 mm	125 mm	36 mm	35 mm	34 mm

General Information

Operating Position UNIVERSAL

Controls and Dimming

Dimmable No

General Information

Order Code	Full Product Name	Cap-Base
928078105114	MSR 1200 1CT/3	G22
928171505114	MSR 700/2 1CT/8	G22

Order Code	Full Product Name	Cap-Base
928171805114	MSR 1200/2.1CT/3	G22
928171605115	MSR 575/2 10H 1CT/4	GX9.5

Light Technical

Order Code	Full Product Name	Correlated Color		Color		Luminous Flux
		Temperature (Nom)	rendering index (CRI)	Color Code	Color	
928078105114	MSR 1200 1CT/3	5900 K	80	-	103,000 lm	
928171505114	MSR 700/2 1CT/8	7200 K	80	2	55,000 lm	
928171805114	MSR	7200 K	85	2	104,000 lm	
		1200/2.1CT/3				

Order Code	Full Product Name	Correlated Color		Color		Luminous Flux
		Temperature (Nom)	rendering index (CRI)	Color Code	Color	
928171605115	MSR 575/2 10H	6990 K	73	2	47,000 lm	
		1CT/4				

Operating and Electrical

Order Code	Full Product Name	Lamp Current (Nom)	Power Consumption
928078105114	MSR 1200 1CT/3	13.8 A	1,200 W
928171505114	MSR 700/2 1CT/8	11 A	700 W

Order Code	Full Product Name	Lamp Current (Nom)	Power Consumption
928171805114	MSR 1200/2.1CT/3	13.8 A	1,200 W
928171605115	MSR 575/2 10H 1CT/4	6.75 A	575 W

