Sophisticated yet simple energy-efficient lighting control solutions

Dynalite Integration Devices

Within any modern project, many third-party systems can be found performing different roles. Each separate system may use a different protocol for communication. Dynalite has developed a range of gateway devices that can be used to synchronize these systems' functions into one integrated system solution.

Benefits
- By utilizing the correct gateway, different systems can be integrated, allowing end-users access to a fully automated site from one interface.
- By successfully integrating third-party systems with a Dynalite solution, repetitive end-user interaction is reduced.

Application
- Retail and Hospitality, Office and Industry
- Public spaces, Stadiums and multi-purpose Event Centers
- Residential

Dynalite Integration Devices

Versions

**DPMI940-DALI Dry Contact Interface**


Product photo IRT9090_01

SlimBlend SR-RC400B VPC ACL


PDEG Ethernet Gateway

Dimensional drawing

38 mm (1.49 in)

106 mm (4.17 in)

99 mm (3.89 in)

PHILIPS

110 mm (4.33 in)

59 mm (2.3 in)

95 mm (3.8 in)

105 mm (4.1 in)

75 mm (2.9 in)

165 mm (6.50 in)

18 mm (0.71 in)

53 mm (2.09 in)

34 mm (1.34 in)

59 mm (2.32 in)

95 mm (3.74 in)

105 mm (4.13 in)

75 mm (2.95 in)

59 mm (2.32 in)

95 mm (3.74 in)

105 mm (4.13 in)

75 mm (2.95 in)

Dynalite Integration Devices

Product details

Front of the PDEG Ethernet Gateway

DDMIDC8 Low Level Input Integrator front

DDNG-KNX Front

www.lighting.philips.com

2023, August 2 – data subject to change