






























Ledalite architectural recessed luminaires deliver the highest quality lighting solutions to satisfy your projects needs through innovative technologies and attention to detail.

Reference	
★ ★ ★	High applicability
★ ★	Medium applicability
★	Low applicability
-	Non-applicable



		\$		\$\$		\$\$\$
Applications	Family	ArcForm Duo	Pique Duo	Shine	SilkSpace Definition	BloomBox
	Education	★ ★ ★		★ ★ ★		★ ★ ★
	Office	★ ★ ★		★ ★		★ ★ ★
	Healthcare	★ ★ ★		★ ★ ★		★ ★
	Fashion and Retail	★ ★ ★		★ ★		★
	Design Ready, 10-Day QuickShip	Design ready – Quick Ship Guide		Design ready – Quick Ship Guide		-
Features and Specifications	Sizes	2x2, 2x4, 1x4		1x1, 1x2, 2x2, 2x4, 1x4, 20"x2', 20"x4', 20"x60" 30"x30" 600x1200mm, 750x750mm, 600x600mm, 300x1200mm, 300x600mm, 300x300mm		2x2
	Watts (Max)	59		63		29
	lm/W (Max)	152		138		171
	Lumens (Max)	8000		8000		5000
	IES TM-21-11	L ₇₀ >102K		L ₈₀ >60K		L ₇₀ >72K
	Product Height	3-15/16" (4-11/16" @ Driver)		4-3/8"		2-1/5"
	Light Distribution	Batwing (MesoOptics) or Lambertian (Silk)		Lambertian (Silk)		Batwing (Micro Cells)
	Spacing Ratio	10'x10' OC (Batwing) or 8'x8' OC (Lambertian)		8x8' OC		14'x14' OC
	CCT	Static: 2700K, 3000K, 3500K, 4000K, 5000K Tunable White: 2700K-6500K BioUp: 2700K-5000K (on request)		Static: 2700K, 3000K, 3500K, 4000K, 5000K Tunable White: 2700K-6500K (on request) BioUp: 2700K-5000K (on request)		Static: 3500K, 4000K
	CRI	90+		90+		90+
	Ceiling Types	Compatible with 15/16" lay-in acoustical ceilings using exposed grid suspension (NEMA type G). For 9/16" slot T-grid ceilings, fixture will sit 5/16" above bottom of Tee. Integrated tabs are provided for different T-grid heights. Optional drywall kit trim mount		Compatible with 15/16" lay-in acoustical ceilings using exposed grid suspension (NEMA type G). For 9/16" slot T-grid ceilings, fixture will sit 5/16" above bottom of Tee. Integrated tabs are provided for different T-grid heights. Optional drywall kit trim mount		Compatible with 15/16" lay-in acoustical ceilings using exposed grid suspension (NEMA type G). For 9/16" slot T-grid ceilings, fixture will sit 5/16" above bottom of Tee. Integrated tabs are provided for different T-grid heights. Optional drywall trim kit.
	Housing Types	T-Grid, Drywall, & Chicago Plenum		T-Grid, Drywall, & Chicago Plenum		T-Grid & Drywall
	Emergency Options	Integral Battery Pack or GTD		Integral Battery Pack		-
	Service from Below	-				
Integrated Controls	Optional Pre-Installed 6' Flex Whip					-
	Interact Pro CS (Day/Occ)					
	Interact Pro RA (Radio Node)					-
	Interact Pro Enterprise SB (Day/Occ + IoT)					
Driver Options	Lutron Athena and Vive			On request		-
	Advance 0-10V					
	Advance DALI-2 D4i					-
	Advance Sensor Ready					
	Lutron Ecosystem LDE1					-
Certifications	IC Rating Direct Contact					
	DLC	V5.1 Standard & Premium		V5.1 Standard & Premium		V5.1 – Premium
	Declare					
Links	Spec Sheet	