



	Best	Best	Best	Best	Best	Best
Product	Capella Small	Capella Medium	RoadStar Small	RoadStar Medium	RoadScope	RoadScope
Prefix	CPLS	CPLM	GPLS	GPLM	S-RSCF	S-RSCF-C
Lumen Output Range	Up to 10,896	Up to 20,800	Up to 16,856	Up to 32,924	LEDgine	ComfortEdge™
Efficacy	Up to 140 LPW	Up to 136 LPW	Up to 127 LPW	Up to 124 LPW	Up to 34,801	Up to 18,724
Distribution	LE2, LE3, LE4, LE5	LE2, LE3, LE4, LE5	R2S, R2M, R3S, R3M, R3W, 4, 5	R2S, R2M, R3S, R3M, R3W, 4, 5	Up to 198 LPW	Up to 152 LPW
Roof	-	-	-	-	1, 2, 2B, 3, 3W, 4, 5	2, 3, 4, 5
Flat, SAG Lens	✓	✓	-	-	Flat Lens Optional	Flat Lens Standard
Color Temperature	3000K, 4000K	3000K, 4000K	3000K, 4000K	3000K, 4000K	2700K, 3000K, 4000K (70/80 CRI)	2700K, 3000K, 4000K (70/80 CRI)
Mounting Height Range	15' - 25'	20' - 35'	15' - 25'	20' - 35'	15' - 35'	15' - 25'
0 Uplight	✓	✓	✓	✓	✓	✓
DALI	✓	✓	✓	✓	✓	✓
Service Tag	✓	✓	✓	✓	✓	✓
Photocell	PH8, PH8/347, PH8/480, PHXL	PH8, PH8/347, PH8/480, PHXL	PH8, PH8/347, PH8/480, PHXL	PH8, PH8/347, PH8/480, PHXL	PH8, PH8/347, PH8/480, PHXL	PH8, PH8/347, PH8/480, PHXL
Receptacle	RCD, RDC7	RCD, RDC7	RCD7	RCD7	TLRD7, TLRSR	TLRD7, TLRSR
Shielding	HS	HS	HS	HS	HSS, CSS, FSS, LSS, RSS	Consult Factory
API (Factory Installed NEMA Label)	✓	✓	-	-	API (ANSI C135.15 - 2020 compliant)	API (ANSI C135.15 - 2020 compliant)
Additional Surge Protection	✓	✓	✓	✓	SP2, SP1X, SP2X	SP2, SP1X, SP2X
Finish	Black, Bronze, Grey, White	Black, Bronze, Grey, White	Black, Bronze, Grey, White	Black, Bronze, Grey, White	Black, Bronze, Grey, White	Black, Bronze, Grey, White
IP Rating	IP66	IP66	IP66	IP66	IP66	IP66
Vibration	3G	3G	3G	3G	3G	3G
DLC Listing	Premium	Premium	Premium	Premium	Premium	Premium
Certifications	Dark Skies, cUL	Dark Skies, cUL	Dark Skies, cUL	Dark Skies, cUL	Dark Skies, cUL	Dark Skies, cUL
Lifetime Per TM21	L70 > 60,000 hours	L70 > 60,000 hours	L70 > 60,000 hours	L70 > 60,000 hours	L70 > 102,000 hours	L70 > 102,000 hours
Limited Warranty	10 years	10 years	10 years	10 years	10 years	10 years
Link						